

## ESPRIMO Mobile U Series Small size, big business

Issue March 2008

Pages 4

Being frequently on the road? Moving from location to location? Sometimes being stuck between meetings? Business people like you need the perfect companion on the move!

The ESPRIMO Mobile U9200 – an ultra portable notebook – with latest Intel® Centrino® Duo processor technology keeps you working productive, wherever you decide to work. It is the perfect combination of low weight, long independency from power socket and unlimited connectivity.

This professional notebook features a superb 12.1-inch WXGA display, with integrated ConfCamera. In combination with embedded UMTS/HSDPA you stay in touch with your colleagues, partners and customer – whenever and wherever you are. And once back at the office, the port replicator instantly transforms your ESPRIMO Mobile in a fully-fledged PC.

### Elegance

- Designed for demanding mobile users, ESPRIMO Mobile is the perfect synthesis of form, function and style
- Elegant family design, extremely small package fits even on the smallest airplane table

### Ergonomics

- Enjoy the viewing quality of 12.1-inch wide format WXGA TFT display with integrated ConfCamera
- Port replicator for simple connection to all your peripherals

### Connectivity

- Always connected to your emails  
Wireless high-speed connectivity everywhere with embedded LAN, WLAN and UMTS/HSDPA
- Integrated ConfCamera for on-the-fly videoconferencing

### Reliability

- Long independency with long battery runtime and further extension with second battery
- Germany's quality standard in award-winning best-in-class manufacturing

### Manageability

- Seamless integration in heterogeneous enterprise management systems
- Sophisticated family concept with BIOS / BIM compatibility



System	ESPRIMO Mobile U9200
<b>Processor</b> <b>Intel® Celeron® Processor</b> Second level cache Front side bus (FSB) <b>Intel® Core™2 Duo Processor</b> Second level cache Front side bus (FSB) <b>Intel® Core™2 Duo Processor</b> Second level cache Front side bus (FSB)	Celeron 540 - - T7250 (2.0 GHz) 2 MB 800 MHz T7500 (2.2GHz) T7700 (2.4GHz)* 4 MB 800Mhz
<b>Chipset</b> Northbridge Southbridge	Intel® GM965 ICH 8-M
<b>Memory</b> DIMM slots DDR2-667 SDRAM, 667 MHz	2 up to 4 GB
<b>BIOS</b> BIOS Flash EPROM	BIOS based on Phoenix TrustedCore Notebook
<b>Interfaces</b> SIM card slot Express card 34 Memory card slot (SD, MS, xD and MSPRO) USB 2.0 S-Video out (TV-out)without adapter cable VGA Modem RJ-11 LAN RJ-45 Audio-in (line-in / microphone) Audio-out (line-out / headphone) DC-in 20V Kensington Lock Docking connector for Port Replicator	1 1 1 3 1 1 optional 1 1 1 1 1 1
<b>Port Replicator interfaces (optional):</b> USB 2.0 VGA DVI-D Serial port Parallel port LAN RJ-45 PS/2 DC-in Microphone Headphone Power on switch Kensington Lock	4 1 1 1 1 1 1 1 1 1 1 1 2
<b>Integrated ConfCamera</b>	1.3MPix
<b>Modem on board</b> 56K V.92 modem MDC1.5	optional
<b>LAN on board</b> built-in 10/100/1000 Mbps Marvell 88E8055	x
<b>Wireless Technologies (WLAN)</b> Import and usage according to country-specific regulations. 3 Dual band WLAN antennas, 2 UMTS antennas Intel® Pro Wireless 4965 a/g/n Atheros Minicard b/g 802.11 b/g WiFi certified integrated UMTS/HSUPA Option GTM378 - 3.6Mbit/s download* 384Kbit upload also supported are GPRS and EDGE or higher * upgrade to 7.2MBit possible	optional optional x optional
<b>Bluetooth</b> Bluetooth V2.0	x
<b>Audio</b> Stereo speakers Sound chip Internal microphone (array)	x Realtek ALC262 2
<b>Keyboard and pointing device</b> Keyboard Touchpad Application Button Status LED	Spill-proof 86 keys, 19mm pitch, 2.7mm key stroke x 1x Wireless x
<b>Graphics</b> Intel® X3100 integrated graphics (shared memory up to 358 MB)* Direct X9 Pixelshader 3.0 DualView * depending on system memory	x x x x
<b>Display</b> 12.1-inch TFT WXGA (wide format) /1280 x 800 Max. resolution for external displays <b>at DVI on Port replicator</b>	x 1920 x 1200 / true color / 85 Hz



<b>Accessories</b> (order number) Port Replicator/AC Adapter/EU cable kit AC Adapter 20V/90W 1st Battery 2nd battery Modem adapter set 1: D, UK Modem adapter set 2: SW, NO, FI, DK Modem adapter set 3: CH, A, B, NL, F, I, E, POR <a href="http://www.fujitsu-siemens.com/accessories/">http://www.fujitsu-siemens.com/accessories/</a>	S26391-F696-L100 S26391-F696-L200 S26391-F405-L840 S26391-F405-L841 S26391-F3145-L10 S26391-F3145-L20 S26391-F3145-L30
<b>Spare part availability</b>	5 years