ComX Computers
Product Specification Sheet

0024Z0607

Lexmark C925dte A3 Colour Laser Printer

Product Overview

Lexmark C925dte A3 Colour Laser Printer, 512MB Memory, USB Interface, Ethernet, 31/31 PPM Print Speed, Duplex, 1 x 550 Sheet tray, Usb direct interface, Touch Screen.



Specifications

Features:

Intuitive Colour Touch Screen
The 4.3-inch colour touch screen allows you to operate your printer with ease and confidence through smart and intuitive navigation, easy access to workflow solutions and shortcuts, and the ability to preview your documents and print jobs at the device.

Affordable A3 Colour Printing
Vibrant, professional-quality output on a wide variety of media for more colour printing in-house. Supports media up to 11.7 x 48 inches.

Load Multiple Media types
150-sheet and 250-sheet input trays, a 550-sheet drawer and a multipurpose feeder come standard, allowing you to load up to four media types.

Networking
Robust connectivity makes it easy to integrate into most network environments.

Lexmark Solutions
Reduce unnecessary printing and simplify work processes through solution applications preloaded on your device. Choose additional Lexmark solutions to fit your unique workflow needs.

Advanced Security
Protect your device, data and network with innovative security controls, like authentication and authorisation, and an optional hard disk with disk wiping and encryption.

Specifications:

Size (mm - H x W x D)	555 x 622 x 557
Packaged Size (mm - H x W x D)	1191 x 680 x 749
Weight (kg)	62.3
Packaged Weight (kg)	91.7
UNSPSC Code	43212105
Size, Trays Extended (mm - H x W x D)	555 x 864 x 938
Product Certifications	Energy Star, CAN/CSA-C22.2 60950-1-07, ICES-003 Class A, US FDA, BSMI Class A, CNS 13438, VCCI Class A, FCC Class A, UL 60950-1, EN/IEC 60320-1, NOM-019-SCFI-1998, CE Class A, CB IEC 60950-1, EN 60950-1, EN/IEC 61000-3, EN 55022 Class A, EN 55024, GS (TÜV), SAT, SABS, ZIK, KPSIM, Bel GISS, GOST-R 'Cpt' Mark, N Mark, UL AR, CS, TÜV Rh, ACMA A-tick mark Class A, AS/NZS 60950-1, CCC Class A, CISPIR 22 Class A, MIC Mark, EK-K60950, PSB
Display	Lexmark e-Task 4.3-inch (10.9 cm) colour touch screen with audible feedback
Energy Star Typical Electricity Consumption (TEC)	5.705
Energy Star	Yes
Touch Screen Display	Yes
Ethernet Network	Yes
Direct USB	Yes
A3	Yes
Workgroup Size	Medium-Large Workgroup
Print Technology	Colour LED
Print Resolution, Black	1200 Image Quality; 600 x 600 dpi
Print Resolution, Colour	1200 Image Quality; 600 x 600 dpi
Print Speed (A4, Black)	Up to 31
Print Speed (A4, Colour)	Up to 31
Print Speed (A4, Black) Duplex	Up to 26
Time to First Page (Black)	As fast as 9
Processor	800
Memory, Standard	1280
Memory, Maximum	1280
Printable Area (metric)	5
Noise Level, Idle	39
Print Noise Level, Operating	53
Time to First Page (Colour) as fast as	11
Duplex Print Noise Level, Operating	55
Hard Disk	Option available
Maximum Monthly Duty Cycle	Up to 200000

Recommended Monthly Page Volume	2500 - 10000
Paper Handling Optional	550-Sheet Drawer
Paper Input Capacity, Standard	Up to 1000
Paper Input Capacity, Maximum	Up to 2100
Paper Output Capacity, Standard	Up to 250
Paper Output Capacity, Maximum	Up to 250
Finishing Option	No
Paper Weight Range Supported - Standard Tray (gsm)	60 - 128
Number of Paper Inputs, Standard	4
Number of Paper Inputs, Maximum	6
Duplex (2-sided) Printing	Integrated Duplex
Photoconductor Notes	Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.
Duty Cycle Notes	"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.
Paper Handling Standard	150-Sheet Input Tray
	250-Sheet Output Bin
	Integrated Duplex
	250-Sheet Input Tray
	550-Sheet Drawer
	50-Sheet Multipurpose Feeder

Media Sizes Supported	10 Envelope
	7 3/4 Envelope
	9 Envelope
	A3
	A4
	A5
	B5 Envelope
	C5 Envelope
	DL Envelope
	Executive
	Folio
	JIS-B4
	JIS-B5
	Ledger
	Legal
	Letter
	Statement
	Universal
	Oficio
	A6
Media Types Supported	Card Stock
	Envelopes
	Labels
	Plain Paper
	Transparencies
	Refer to the Card Stock & Label Guide
Supplies Yield	*Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.
	7, 500*-page Colour (CMY) High Yield Toner Cartridges
	8, 500*-page Black High Yield Toner Cartridge
Cartridge(s) Shipping with Product	7, 500*-page Colour (CMY) High Yield Toner Cartridges
	8, 500*-page Black High Yield Toner Cartridge
Apple Macintosh Operating Systems Supported	Apple Mac OS X

Microsoft Windows Operating Systems Supported	Microsoft Windows 2000
	Microsoft Windows XP
	Microsoft Windows Server 2003
	Microsoft Windows XP x64
	Microsoft Windows Server 2003 running Terminal Services
	Microsoft Windows 2000 Server running Terminal Services
	Microsoft Windows Server 2003 x64
	Microsoft Windows Server 2003 x64 running Terminal Services
	Microsoft Windows Vista
	Microsoft Windows Vista x64
	Microsoft Windows Server 2008
	Microsoft Windows Server 2008 x64
	Microsoft Windows Server 2008 running Terminal Services
	Microsoft Windows Server 2008 x64 running Terminal Services
	Microsoft Windows 7
	Microsoft Windows 7 x64
	Microsoft Windows Server 2008 R2
	Microsoft Windows Server 2008 R2 running Terminal Services
Novell Operating Systems Supported	Novell NetWare 6.5 Open Enterprise Server
	Novell NetWare 5.1(SP 6+), 6.0(SP 3+) with Novell Distributed Print Services (NDPS)
	Novell Open Enterprise Server on SUSE Linux Enterprise Server
Linux Operating Systems Supported	Linspire Linux 6.0
	Debian GNU/Linux 5.0
	SUSE Linux Enterprise Server 10, 11
	SUSE Linux Enterprise Desktop 10, 11
	openSUSE 11.0, 11.1
	Red Hat Enterprise Linux WS 4.0, 5.0
	Red Flag Linux Desktop 6.0
	Linpus Linux Desktop 9.6
	Ubuntu 9.04, 9.10, 10.04
	Fedora 12, 13
UNIX Operating Systems Supported	Sun Solaris SPARC 8, 9, 10
	Sun Solaris x86 10
	HP-UX 11.11, 11.23, 11.31
	IBM AIX 5.2, 5.3, 6.1
	Sun openSolaris SPARC 2010.02
	Sun openSolaris X86 2010.02

Citrix MetaFrame	Microsoft Windows Server 2003 running Terminal Services with Citrix Presentation Server 3.0, 4.0, 4.5
	Microsoft Windows Server 2003 and 2003 X64 Edition with Citrix XenApp 5.0
	Microsoft Windows Server 2008 and 2008 X64 Edition with Citrix XenApp 5.0
Standard Ports	USB 2.0 Specification Hi-Speed Certified (Type B)
	Front USB 2.0 Specification Hi-Speed Certified port (Type A)
	Ethernet 10/100/1000 BaseTX (RJ-45)
Optional Local Ports	RS-232C Serial Interface Card
	Parallel 1284-B Interface Card
Optional Network Ports	External MarkNet N7020e Gigabit Ethernet
	Internal MarkNet N8120 Gigabit Ethernet
	Internal MarkNet N8130 Fiber Fast Ethernet
	Internal MarkNet N8250 802.11b/g/n Wireless
Printer Languages (Standard)	PCL 5c Emulation
	PCL 6 Emulation
	PPDS
	PostScript 3 Emulation
	xHTML
	PDF 1.6
	Direct Image
	Microsoft XPS (XML Paper Specification)
	AirPrint
Fonts and Symbol Sets	3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide
	158 scalable PostScript fonts
	2 PCL bitmap fonts
	39 scalable PPDS fonts
	5 PPDS bitmap fonts
	84 scalable PCL fonts
	OCR-A, OCR-B scalable PCL 5e fonts
	For more information, refer to the Technical Reference.
Network Protocol Support	TCP/IP IPv4
	AppleTalk
	TCP/IP IPv6
	TCP
	UDP

Network Printing Methods	LPR/LPD
	Direct IP (Port 9100)
	HTTP
	NDS Queue-based Printing
	NDPS/NEPS (Novell Distributed Print Services, Novell Netware Enterprise Print Services)
	Enhanced IP (Port 9400)
	FTP, TFTP
	IPP 1.1 (Internet Printing Protocol)
	ThinPrint .print integration
Network Security	SNMPv3
	802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS
	IPSec
Network Management Protocols	HTTP
	HTTPs (SSL*/TLS)
	SNMPv3
	WINS
	IGMP
	BOOTP, RARP
	APIPA (AutoIP)
	DHCP
	ICMP
	DNS
	SNMPv2c
	Bonjour
	DDNS
	mDNS
	ARP
	NTP
	Telnet
	Finger
	*This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit.

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: https://www.comx-computers.co.za/0024Z0607-Lexmark-C925dte-A3-Colour-Laser-Printer-p-57235.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-20 04:23:46.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.