ComX Computers
Product Specification Sheet

103006456-6591

Eaton 9130 1500VA 1350Watts Superior Rackmounted/Tower 2U UPS

Product Overview

Eaton 9130 1500VA 1350Watts Superior Rackmounted/Tower 2U UPS, 11-18min



Specifications

Overview:

The Eaton 9130 Rackmount UPS delivers online power quality and scalable battery runtimes for rack servers, voice and data networks, storage systems and other IT equipment. With an efficiency rating of >95%, the 9130 UPS cuts energy costs while packing up to three kVA of power into only 2U of rack space. The 9130 UPS significantly extends battery service life with ABM technology and also has a bright LCD user interface to simplify monitoring.

Features:

- Cuts energy usage and costs with >95% efficiency rating in high efficiency mode
- Conserves valuable rack space with 2U form factor that includes internal batteries and a 4-post rail kit
- Provides more real power (watts) to protect more equipment and leave room for expanding IT systems with a 0.9 power factor
- Simplifies UPS monitoring and management with a bright LCD user interface, intuitive power management software and optional eNotify Remote Monitoring service
- Increases battery service life and system uptime with ABM battery-charging technology and hot-swappable batteries
- Maximizes runtimes with optional extended battery modules

Specifications:

© 2015 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	103006456-6591

General	
Topology	Online, double-conversion
Configuration	Rackmount
Part Number	103006456-6591
Color	Black
Rating (VA/Watts)	1500/1350
Diagnostics	Full system self-test
Efficiency	94% in high-efficiency mode; 90% in online mode
UPS Bypass	Automatic bypass
Dimensions (H x W x D, mm)	86.5 x 438 x 450
Weight (kg)	19
Rail Kit Included	Yes
Remote Emergency Power off (REPO)	Emergency shutdown control through the REPO port
Electrical Input	
Connection	(1) IEC-320-C14
Input Cord	Schuko 10A to IEC 320-10A
Input Voltage Range	180-276 Vac (with load PF of 0.7)
Nominal Voltage	220-240 V
Frequency	50/60 Hz
Frequency Range	45-65 Hz
Nominal Current	7.2A @230V
Breaker Ratings	10A
Electrical Output	
Outlets	(6) IEC-320-C13
On Utility Voltage Regulation	+/-3% of nominal
On Battery Voltage Regulation	+/-3% of nominal
Frequency Regulation	+/-3% Hz online
Load Crest Factor	3 to 1
Battery	
Battery Description	VRLA 12V/9 Ah (internal and External)
Battery Type	Replaceable maintenance free sealed lead acid
Battery Replacement	Hot-swappable internal batteries
Start On Battery	Allows start of UPS without utility input
Communications	
User Interface	Graphical LCD with blue backlight and text in English, French, German, Russian and Spanish
LEDs	Four status-indicating LEDs

Communication Ports	RS-232 and USB HID port as standard
Relay Output	Common alarm standard
Communications Slot	Optional communication slots (BD Slot)
Communications Card Slots	Optional SNMP/Web card for monitoring in SNMP-based networks, monitoring through Web browser interface. Relay card for integration to industrial environment and BMS, remote shutdown for IBM AS/400 systems
Environmental & Standards	
Heat Dissipation (BTU)	Line: 750, Bat: 1011
Audible Noise	
Operating Temperature	0?C to +40?C
Performance - Safety - EMC	CE (per IEC/EN62040-2: Emissions, Category C1; Immunity, Category C2), GS
Storage Temperature	-20?C to +40?C with batteries and -25?C to +55?C without batteries
Relative Humidity	5-90% non-condensing

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/103006456-6591-Eaton-9130-1500VA-1350Watts-Superior-Rackmounted-Tower-2U-UPS-p-116816.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-14 08:22:43.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.