ComX Computers
Product Specification Sheet

103007848-6591

Eaton 9130 3000VA Marine Tower UPS

Product Overview

Eaton 9130 3000VA Marine Tower UPS



Specifications

Overview:

Marine approved UPS by the DNV and ABS, Online double conversion UPS with automatic bypass, 1000VA/900W, 2000VA/1800W, 3000VA/2700W, Tower unit with mounting rails and vibration dampers, multilingual LCD display, hot swappable batteries, power management software, Relay output, USB and Serial port.

Features:

- Provides more real power (watts) to protect more equipment and leave room for expanding IT systems with a 0.9 power factor
- Simplifies UPS monitoring and management with a bright LCD user interface and free intuitive power management software
- Increases battery service life and system uptime with ABM battery-charging technology and hot-swappable batteries
- Extends battery runtime for critical devices with load segments
- Maximizes runtimes with optional extended battery modules

Specifications:

© 2014 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	103007848-6591
General	
Topology	Online, double-conversion

Configuration	Tower
Part Number	103007848-6591 (Marine Filter and Installation Kit are required for the DNV and ABS compliance)
Color	Black
Rating (VA/Watts)	3000/2700
Diagnostics	Full system self-test
Efficiency	94% in high-efficiency mode; 90% in online mode
UPS Bypass	Automatic bypass
Dimensions (H x W x D, mm)	469 x 392 x 445
Weight (kg)	33
Remote Emergency Power off (REPO)	Emergency shutdown control through the REPO port
Electrical Input	
Connection	(1) IEC-320-C20
Input Voltage Range	180-276 Vac (with load PF of 0.7)
Nominal Voltage	220-240V
Frequency	50/60 Hz
Frequency Range	45-65 Hz
Nominal Current	13.0A @230V
Breaker Ratings	16A
Electrical Output	
Output Receptacles	(8) IEC-320-C13
	(1) IEC-320-C19
On Utility Voltage Regulation	+/-3% of nominal
On Battery Voltage Regulation	+/-3% of nominal
Power Factor	0.9
Frequency Regulation	+/-3% Hz online
Load Crest Factor	3 to 1
Battery	
Battery Description	VRLA 12V/9 Ah (internal and External)
Battery Type	Replaceable maintenance free sealed lead acid
Half Load Runtime (in mins)	20
Full Load Runtime (in mins)	9
Battery Replacement	Hot-swappable internal batteries
Start On Battery	Allows start of UPS without utility input
Communications	
User Interface	Graphical LCD with blue backlight and text in English, French, German, Russian and Spanish

LEDs	Four status-indicating LEDs
Communication Ports	RS-232 and USB HID port as standard
Relay Output	Common alarm standard
Communications Card Slots	Optional SNMP/Web card for monitoring in SNMP-based networks, monitoring through Web browser interface. Relay card for integration to industrial environment and BMS, remote shutdown for IBM AS/400 systems
Environmental & Standards	
Heat Dissipation (BTU)	Line: 1257, Bat: 1755
Audible Noise	
Operating Temperature	0?C to +40?C
Performance - Safety - EMC	CE (per IEC/EN62040-2: Emissions, Category C1; Immunity, Category C2), GS, IEC/EN 60945
Storage Temperature	-20?C to +40?C with batteries and -25?C to +55?C without batteries
Relative Humidity	5-90% non-condensing

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: https://www.comx-computers.co.za/103007848-6591-Eaton-9130-3000VA-Marine-Tower-UPS-p-99614.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-15 16:19:31.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.