

1221401

OKI B930N Mono Laser Printer

Product Overview

OKI B930N: Mono Laser 50ppm, 600MHz, 256MB, 1200x1200dpi, PCL6/PS3, 1100sheets, Par/serial, USB, 300k duty, with network



Specifications

Overview:

The B930 could be the only black and white large workgroup printer you'll ever need. Not only is it fast, but it's purpose-built for heavy workloads, too. Now everyone in the office can print 50 pages per minute (ppm), job after job, day after day. For years.

This highly versatile black and white printer can be precisely configured with options to accommodate all your essential printing needs. Of course, your needs could change over time. That's why we created a full range of plug and play expansion modules. And that's the B930. Fast, versatile and entirely dependable. The perfect choice for any busy office.

Features:

- Fast print speed of 50ppm when printing A4 and 28ppm for A3
- Various configurations to suit everybody's needs
- Easy to use mono printer with extra support of in-box utilities
- Built to perform all day, every day

Specifications:

© 2014 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.	
Specifications	
Product Code	1221401
Configurations Available	
Model	B930n - Networked; B930dn - Duplex and networked; B930dtn - Duplex, A4 Tandem-tray and networked; B930dxf - Duplex, A4 Tandem-tray, networked, High Capacity Feeder and finisher

ComX Computers

Product Specification Sheet

Connectivity and Compatibility	
Emulation(s)	PCL6, PCL5e, PostScript 3, SIDM (Epson FX)
OS Compatibility	Windows 2000 / XP Home / XP Professional / XP Professional x64 / Vista (32-bit) / Vista (64-bit) / Server 2003 / Server 2003 for x64 Mac OS X PowerPC 10.2 or greater / OS X Intel 10.4.4 or greater
Optional interface(s)	1GB Base TX Ethernet
Standard interface(s)	10/100 Base TX Ethernet on board with internal web server for printers and network set-up and management. Includes SMTP mail client for alerts.
	Major protocols supported: TCP/IP, Netware 5.x and 6.x, and EtherTalk. TCP/IP: ARP, IPv4, ICMP, UDP, TCP, LPR, HTTP, SMTP, BOOTP, DHCP, SNMPv1, SNMPv2, DNS, WINS, IPX/SPX, and Apple Bonjour protocols
Consumables	
EP-cartridge	60, 000 pages
Toner cartridge	33, 000 pages
Other Specifications	
Voltage requirements	230 VAC +/- 10%
Weight	B930n: approx 44.1kgs; B930dn: approx 48.4kgs; B930dtn: approx 78.4kgs; B930dx: approx 155.4kgs
Notes	Optional accessories: 256MB, 512MB Memory; Duplex (standard on B930dn, B930dtn, B930dx); A4 Tandem-tray (standard on B930dtn, B930dx); High Capacity Feeder (standard on B930dx);
	Finisher unit (standard on B930dx); A3 Two-tray; 1GB Network I/F kit; 60GB, 120GB Hard Disk Drive; 256MB, 512MB, 1GB Compact Flash memory; Maintenance kit (300, 000 pages); Staple refill pack (15, 000 staples)
Noise	Operating: Up to 54dB(A), Stand by: 22dB, Power Save: Background Level
Warranty	Pan European 1 year on-site
Operating conditions	5 degreesC to 32 degreesC
Barcodes 11 types of one dimension with 28 variations	UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved2of5, Code39, Code 128, EAN/UCC-128, CODABAR, ZIP+4POSTNET
Dimensions(WxDxH)	B930n: 498 x 640 x 525mm; B930dn: 577 x 640 x 525mm; B930dtn: 851 x 640 x 525mm; B930dx: 1050 x 1679 x 639mm
Frequency	50 or 60Hz +/- 2%
Humidity	15% to 85% RH non-condensing
Paper Handling	
Paper types	Standard trays and MPT: A3, A4, A5, A6, B5, Letter, Legal 13 & 14, Executive, Statement; High Capacity Feeder: A4, Letter, B5, Executive; Tandem-tray: A4, Letter, B5, Executive; Two-tray: A3, A4, A5, B5, Letter, Legal 13 & 14, Executive, Statement
Paper output 500 sheets face down	
Duplex printing	Available
Standard paper input	1, 000 sheets of 80gsm
Envelope types	Com-9, DL, C5, Monarch

ComX Computers

Product Specification Sheet

Optional paper input	Tandem-tray (A4 2, 000 sheets capacity); Two-tray (A3 1, 000 sheets capacity); High Capacity Feeder (A4 2, 000 sheets capacity)
Manual feeder	100 sheets of 80gsm
Custom paper size	Multi-purpose tray: Width 89 - 297mm x Length 98.4 - 432mm; Standard trays: Width 140 - 297mm, Length 182 - 432mm
Performance	
Time to first page	3 seconds (warm start)
Memory(standard)	256MB
Duty cycle(max.pages/month) 300, 000 pages/month	
Memory(maximum)	768MB
Resolution	1200 x 1200dpi
Fonts	99 scalable PCL and 136 PS fonts, 47 bitmap symbol sets
Print speed mono A3	28ppm
Print speed mono A4	50ppm
Processing print jobs	600MHz

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx-computers.co.za/1221401-OKI-B930N-Mono-Laser-Printer-p-105283.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-29 18:37:22.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.