ComX Computers
Product Specification Sheet

22Z0099

Lexmark C950de A3 Colour Lazer Printer

Product Overview

Lexmark C950de Colour Laser Printer Functions: Colour Printing, Colour LED, Lexmark e-Task 10.9 cm (4.3-inch) Colour touch screen - A3: Yes - Duplex: Integrated Duplex - HD: Option available - Direct USB: Yes - Print Speed, A4 black: 50 ppm



Specifications

Features:

Outstanding A3 Color Output
PANTONE calibration helps ensure consistent color tones and Named Color Replacement makes color matching easy.

Exceptional Media Handling
Ultra-reliable paper feeding lets you load up to six different media types, including banner support up to 47.24-inches and weights up to 300 gsm.

Advanced Finishing Options
Easily create professional output in-house with flexible finishing options, including multi-position stapling, hole punch, expanded output stacking, and booklet capability.

Flexible Input Capacity
Flexible input capacity enables you to choose the configuration that best fits your needs, up to a maximum of 5,140 sheets.

Intuitive Color Touch Screen
The intuitive 4.3-inch color touch screen allows you to operate your printer with ease through intuitive navigation and easy access to workflow solutions and shortcuts.

Built for Business
Simplify device monitoring and administration through the Lexmark Universal Print Driver, and Lexmark MarkVision Enterprise.

Specifications:

© 2016 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	22Z0099
Print Technology	Color LED
Print Resolution, Black	1200 x 1200 dpi
	2400 Image Quality
Print Resolution, Color	1200 x 1200 dpi
	2400 Image Quality
Time to First Page (Black) As fast as	5.2 seconds
Time to First Page (Color) As fast as	7.7 seconds
Print Speed (Letter, Black): Up to	50 ppm
Print Speed (Letter, Color): Up to	45 ppm
Print Speed (A4, Color): Up to	45 ppm
Print Speed (Letter, Black) Duplex: Up to	50 spm
Print Speed (Letter, Color) Duplex: Up to	45 spm
Print Speed (A4, Black) Duplex: Up to	50 spm
Print Speed (A4, Color) Duplex: Up to	45 spm
Recommended Monthly Page Volume	4000 - 33000 pages
Maximum Monthly Duty Cycle: Up to	225000 pages per month
Duty Cycle Notes	"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.
	"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.
Noise Level, Idle	22 dBA
Print Noise Level, Operating	53 dBA
Duplex Print Noise Level, Operating	54 dBA
Processor Speed	1.2 GHz
Memory, Standard	1024 MB

Memory, Maximum	2048 MB
Hard Disk	Option available
Printable Area	0.158 inches of the top, bottom, right and left edges (within)
Printable Area (metric)	4.0 mm of the top, bottom, right and left edges (within)
Supplies Yield	*Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.
	22, 000*-page color (CMY) Toner Cartridges
	32, 000*-page Black Toner Cartridge
Photoconductor Estimated Yield: Up to	115000 pages, based on 3 average letter/A4-size pages per print job
Cartridge(s) Shipping with Product	11, 000*-page Color (CMY) Starter Toner Cartridges
	16, 000*-page Black Starter Toner Cartridge
Photoconductor Notes	Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.
Paper Handling Standard	500-Sheet Output Bin
	Integrated Duplex
	100-Sheet Multipurpose Feeder
	520-Sheet Input Tray
Paper Handling Optional	2, 000-Sheet High-Capacity Feeder
	3, 500-Sheet Finisher
	3 x 520-Sheet Drawer Stand
	Booklet Finisher
	2, 520-Sheet Tandem Tray Module
	520-Sheet Drawer Stand
Number of Paper Inputs, Standard	2
Number of Paper Inputs, Maximum	6
Paper Input Capacity, Standard: Up to	620 pages 20 lb or 75 gsm bond
Paper Input Capacity, Maximum: Up to	5140 pages 20 lb or 75 gsm bond
Paper Output Capacity, Standard: Up to	500 pages 20 lb or 75 gsm bond
Paper Output Capacity, Maximum: Up to	3750 pages 20 lb or 75 gsm bond
Envelope Capacity	10
Finishing Option	Yes
Duplex (2-sided) Printing	Integrated Duplex

Media Types Supported	Card Stock
	Envelopes
	Glossy Paper
	Labels
	Plain Paper
	Transparencies
	Refer to the Card Stock & Label Guide
Media Sizes Supported	10 Envelope
	7 3/4 Envelope
	A3
	A4
	A5
	C5 Envelope
	DL Envelope
	Executive
	Folio
	JIS-B4
	JIS-B5
	Ledger
	Legal
	Letter
	Statement
	Universal
	Oficio
	A6

Network Management Protocols	HTTP
	HTTPs (SSL*/TLS)
	SNMPv3
	WINS
	IGMP
	BOOTP, RARP
	APIPA (AutoIP)
	DHCP
	ICMP
	DNS
	SNMPv2c
	Bonjour
	DDNS
	mDNS
	ARP
	NTP
	Telnet
	Finger
	*This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit.
Network Printing Methods	LPR/LPD
	Direct IP (Port 9100)
	HTTP
	NDPS/NEPS (Novell Distributed Print Services, Novell Netware Enterprise Print Services)
	Enhanced IP (Port 9400)
	FTP, TFTP
	IPP 1.1 (Internet Printing Protocol)
	ThinPrint .print integration
Network Protocol Support	TCP/IP IPv4
	AppleTalk
	TCP/IP IPv6
	TCP
	UDP
Network Security	SNMPv3
	802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS
	IPSec

Microsoft Windows Operating Systems Supported	Microsoft Windows XP
	Microsoft Windows Server 2003
	Microsoft Windows XP x64
	Microsoft Windows Server 2003 running Terminal Services
	Microsoft Windows Server 2003 x64
	Microsoft Windows Server 2003 x64 running Terminal Services
	Microsoft Windows Vista
	Microsoft Windows Vista x64
	Microsoft Windows Server 2008
	Microsoft Windows Server 2008 x64
	Microsoft Windows Server 2008 running Terminal Services
	Microsoft Windows Server 2008 x64 running Terminal Services
	Microsoft Windows 7
	Microsoft Windows 7 x64
	Microsoft Windows Server 2008 R2
	Microsoft Windows Server 2008 R2 running Terminal Services
Apple Macintosh Operating Systems Supported	Apple Mac OS X
Citrix MetaFrame	Microsoft Windows Server 2003 running Terminal Services with Citrix Presentation Server 3.0, 4.0, 4.5
	Microsoft Windows Server 2003 and 2003 X64 Edition with Citrix XenApp 5.0
	Microsoft Windows Server 2008 and 2008 X64 Edition with Citrix XenApp 5.0
Linux Operating Systems Supported	Debian GNU/Linux 5.0
	SUSE Linux Enterprise Server 10, 11
	SUSE Linux Enterprise Desktop 10, 11
	Red Hat Enterprise Linux WS 4.0, 5.0
	Red Flag Linux Desktop 6.0
	Linpus Linux Desktop 9.6
	Fedora 12, 13, 14
	Ubuntu 9.04, 9.10, 10.04, 10.10
	openSUSE 11.2, 11.3, 11.4
Novell Operating Systems Supported	Novell NetWare 6.5 Open Enterprise Server
	Novell NetWare 5.1(SP 6+), 6.0(SP 3+) with Novell Distributed Print Services (NDPS)
	Novell Open Enterprise Server on SUSE Linux Enterprise Server

UNIX Operating Systems Supported	Sun Solaris SPARC 8, 9, 10
	Sun Solaris x86 10
	HP-UX 11.11, 11.23, 11.31
	IBM AIX 5.2, 5.3, 6.1
Standard Ports	USB 2.0 Specification Hi-Speed Certified (Type B)
	Front USB 2.0 Specification Hi-Speed Certified Port (Type A)
	Rear USB 2.0 Specification Hi-Speed Certified Port (Type A)
	Ethernet 10/100/1000 BaseTX (RJ-45)
Optional Local Ports	Internal RS-232C serial
	Internal 1284-B Bidirectional Parallel
Optional Network Ports	Internal MarkNet N8130 Fiber Fast Ethernet
	Internal MarkNet N8250 802.11b/g/n Wireless
Fonts and Symbol Sets	3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide
	158 scalable PostScript fonts
	2 PCL bitmap fonts
	39 scalable PPDS fonts
	5 PPDS bitmap fonts
	84 scalable PCL fonts
	OCR-A, OCR-B scalable PCL 5e fonts
	For more information, refer to the Technical Reference.
Printer Languages (Standard)	PCL 5c Emulation
	PCL 6 Emulation
	Personal Printer Data Stream (PPDS)
	PostScript 3 Emulation
	xHTML
	PDF 1.6
	Direct Image
	Microsoft XPS (XML Paper Specification)
	AirPrint
UNSPSC Code	43212110
Display	Lexmark e-Task 4.3-inch (10.9 cm) color touch screen with audible feedback
Energy Star	Yes
Energy Star Typical Electricity Consumption (TEC)	7.24 kilowatt-hours per week
Size (in. - H x W x D)	22.24 x 25.20 x 26.97 in.
Size (mm - H x W x D)	565 x 640 x 685 mm
Weight (kg)	95.0 kg

Packaged Size (in. - H x W x D)	27.83 x 31.81 x 29.45 in.
Packaged Size (mm - H x W x D)	707 x 808 x 748 mm
Packaged Weight (lb.)	229.3 lb.
Packaged Weight (kg)	104.0 kg
Size, Trays Extended (in. - H x W x D)	22.24 x 25.20 x 43.63 in.
Size, Trays Extended (mm - H x W x D)	565 x 640 x 1108 mm
Product Certifications	Energy Star, CAN/CSA-C22.2 60950-1-07, ICES-003 Class A, BSMI Class A, CNS 13438 and 14336, VCCI Class A, FCC Class A, UL 60950-1, EN/IEC 60320-1, NOM-019-SCFI-1998, CB IEC 60950-1, EN 60950-1, EN/IEC 61000-3, EN 55022 Class A, EN 55024, GS (TÜV), SAT, SABS, ZIK, KPSIM, Bel GISS, GOST-R 'Cpt' Mark, N Mark, IRAM, CS, TÜV Rh, ACMA A-tick mark Class A, AS/NZS 60950-1, CCC Class A, GB4943, CISPIR 22 Class A, MIC Mark, EK-K60950, PSB-SS 337
Country of Origin	China (PR)
Touch Screen Display	Yes
Ethernet Network	Yes
Direct USB	Yes
Harmonized Tariff Code	8443.32.1030

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: https://www.comx-computers.co.za/22Z0099-Lexmark-C950de-A3-Colour-Lazer-Printer-p-146504.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-19 04:44:10.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.