

3084048

Lexmark MS610dn A4 Mono Laser Printer

Product Overview

Lexmark MS610dn A4 Mono Laser Printer Functions: Monochrome Laser , 6 cm (2.4 inch) Colour LCD display - Processor: Dual Core, 800 MHz - Duplex: Integrated Duplex - Direct USB: Yes - Print Speed, A4 black: 47 ppm - Time for first page: 6.5 seconds - Memory: 256 MB - Monthly Duty Cycle: 175000 pages per month - Recommend monthly volume: 3000 - 16000 pages - Touch Screen: No - Paper Input Capacity, Standard: Up to: 650 pages 75 gsm bond



Specifications

Overview:

The Lexmark MS610dn network-ready laser printer with internal 2-sided printing, 256MB of standard memory, 650-sheet input and a print speed of up to 50 ppm quickly and easily performs tasks.

Features:

Print Complex Documents Fast

Print documents with graphics and images effortlessly with up to 1.2 GB of upgradable memory, powerful 800 MHz dual-core processor and Gigabit Ethernet.

Get Work Done Quickly

Print up to 50 pages per minute-plus get your first page in as little as 6.5 seconds.

Run Jobs without Interruption

With an input capacity of up to 2,300 sheets and ultra high yield toner cartridge options, you won't have to add paper or change cartridges as often.

Innovative Toner That Optimizes Performance

Get greater system performance with Lexmark's Unison™ Toner, which delivers consistent image quality from first to last print.

Print Anytime and Anywhere

With this system, you can print from desktops as well as mobile devices that can run applications.

Specifications:

ComX Computers

Product Specification Sheet

Size (in. - H x W x D)	12.1 x 15.7 x 15.0 in.
Packaged Size (in. - H x W x D)	16.6 x 17.0 x 18.6 in.
Weight (lb.)	34.6 lb.
Packaged Weight (lb.)	38.75 lb.
UNSPSC Code	43212105
Product Certifications	Energy Star V1.2, Blue Angel (RAL-UZ-122), CAN/CSA-C22.2 60950-1, CSA E60825-1, ICES-003 Class B, BSMI Class B, CNS 13438, VCCI Class B, US FDA, FCC Class B, UL 60950-1, IEC 320-1, EN/IEC 60320-1, CE Class B, CB IEC 60950-1, EN 62311, EN 60950-1, EN/IEC 61000-3, EN 55022 Class B, EN 55024, EN/IEC 60825-1, GS (TÜV), SEMKO, UL AR, CS, TÜV Rh, SMA C-tick mark Class B, CCC Class B, CISPIR 22 Class B, EK Mark, N Mark, ECMA-370, TED
Specified Operating Environment	Temperature: 16 to 32 degreesC (60 to 90 degreesF)
	Humidity: 8 to 80% Relative Humidity
	Altitude: 0 - 2896 Meters (9, 500 Feet)
Country of Origin	China (PR)
Display	2.4-inch (6 cm) color LCD display
ENERGY STAR Typical Electricity Consumption (TEC)	2.60 kilowatt-hours per week
Touch Screen Display	No
Ethernet Network	Yes
Direct USB	Yes
Workgroup Size	Medium Workgroup
Print Technology	Monochrome Laser
Print Resolution, Black	1200 Image Quality
	1200 x 1200 dpi
	2400 Image Quality
	600 x 600 dpi
Print Speed (Letter, Black): Up to	50 ppm
Print Speed (Letter, Black) Duplex: Up to	22 spm
Time to First Page (Black) As fast as	6.5 seconds
Processor	Dual Core, 800 MHz
Memory, Standard	256 MB
Memory, Maximum	1280 MB
Printable Area	0.16 inches of the top, bottom, right and left edges (within)
Noise Level, Idle	15 dBA
Print Noise Level, Operating	55 dBA
Duplex Print Noise Level, Operating	54 dBA

ComX Computers

Product Specification Sheet

Hard Disk	Not Available
Maximum Monthly Duty Cycle: Up to	100000 pages per month
Recommended Monthly Page Volume	3000 - 16000 pages
Duty Cycle Notes	"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.
	"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.
ISO Speeds	Print and copy speeds measured in accordance with ISO/IEC 24734, excludes first set of test documents. For more information see: www.lexmark.com/ISOspeeds .
Paper Input Capacity, Standard: Up to	650 pages 20 lb or 75 gsm bond
Paper Input Capacity, Maximum: Up to	2300 pages 20 lb or 75 gsm bond
Paper Output Capacity, Standard: Up to	250 pages 20 lb or 75 gsm bond
Paper Output Capacity, Maximum: Up to	250 pages 20 lb or 75 gsm bond
Finishing Option	No
Media Sizes Supported	10 Envelope
	7 3/4 Envelope
	9 Envelope
	A4
	A5
	DL Envelope
	Executive
	Folio
	JIS-B5
	Legal
	Letter
	Statement
	Universal
	Oficio
	A6

ComX Computers

Product Specification Sheet

Media Types Supported	Card Stock
	Envelopes
	Paper Labels
	Plain Paper
	Transparencies
	Refer to the Card Stock & Label Guide
Paper Weight Range Supported - Standard Tray (lb.)	16 - 32 lb.
Number of Paper Inputs, Standard	2
Number of Paper Inputs, Maximum	5
Duplex (2-sided) Printing	Integrated Duplex
Optional Paper Handling	250-Sheet Tray
	550-Sheet Tray
Included Paper Handling	550-Sheet Input
	100-Sheet Multipurpose Feeder
	Integrated Duplex
	250-Sheet Output Bin
Cartridge(s) Shipping with Product	6, 000*-page Starter Return Program Toner Cartridge
Imaging Unit Estimated Yield: Up to	60000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage
Laser Cartridge Yields	1, 500*-page Cartridge
	5, 000*-page Black High Yield Cartridge
	10, 000*-page Extra High Yield Cartridge
	20, 000*-page Ultra High Yield Cartridge
	*Average standard page yield value declared in accordance with ISO/IEC 19752.
Replacement Cartridges	Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.
Apple Macintosh Operating Systems Supported	Apple Mac OS X (10.5, 10.6, 10.7, 10.8)

ComX Computers

Product Specification Sheet

Microsoft Windows Operating Systems Supported	Microsoft Windows XP
	Microsoft Windows Server 2003
	Microsoft Windows XP x64
	Microsoft Windows Server 2003 running Terminal Services
	Microsoft Windows Server 2003 x64
	Microsoft Windows Server 2003 x64 running Terminal Services
	Microsoft Windows Vista
	Microsoft Windows Vista x64
	Microsoft Windows Server 2008
	Microsoft Windows Server 2008 x64
	Microsoft Windows Server 2008 running Terminal Services
	Microsoft Windows Server 2008 x64 running Terminal Services
	Microsoft Windows 7
	Microsoft Windows 7 x64
	Microsoft Windows Server 2008 R2
	Microsoft Windows Server 2008 R2 running Terminal Services
	Microsoft Windows 8
	Microsoft Windows 8 x64
	Microsoft Windows Server 2012
Novell Operating Systems Supported	Novell NetWare 6.5 Open Enterprise Server
	Novell NetWare 5.1(SP 6+), 6.0(SP 3+) with Novell Distributed Print Services (NDPS)
	Novell Open Enterprise Server on SUSE Linux Enterprise Server
Linux Operating Systems Supported	SUSE Linux Enterprise Server 10, 11
	SUSE Linux Enterprise Desktop 10, 11
	Red Flag Linux Desktop 6.0
	Linpus Linux Desktop 9.6
	Debian GNU/Linux 5.0, 6.0
	Red Hat Enterprise Linux WS 4.0, 5.0, 6.0
	Ubuntu 11.04, 11.10, 12.04
	openSUSE 11.3, 11.4, 12.1
	PCLinuxOS 2011.9
	Mint 9, 10, 11, 12
	Fedora 14, 15, 16, 17
UNIX Operating Systems Supported	Sun Solaris SPARC 9, 10
	HP-UX 11.11, 11.23, 11.31
	Sun Solaris x86 10, 11
	IBM AIX 5.3, 6.1, 7.1

ComX Computers

Product Specification Sheet

Citrix MetaFrame	Microsoft Windows Server 2003 running Terminal Services with Citrix Presentation Server 3.0, 4.0, 4.5
	Microsoft Windows Server 2003 x64 running Terminal Services with Citrix Presentation Server 4.0 x64, 4.5 x64
	Microsoft Windows Server 2003 and 2003 X64 Edition with Citrix XenApp 5.0
	Microsoft Windows Server 2008 and 2008 X64 Edition with Citrix XenApp 5.0
	Microsoft Windows Server 2008 R2 with Citrix XenApp 6.0, 6.5
Standard Ports	USB 2.0 Specification Hi-Speed Certified (Type B)
	Gigabit Ethernet (10/100/1000)
	Front USB 2.0 Specification Hi-Speed Certified Port (Type A)
Optional Network Ports	MarkNet N8352 802.11b/g/n Wireless
Printer Languages (Standard)	PCL 5e Emulation
	PCL 6 Emulation
	Personal Printer Data Stream (PPDS)
	PostScript 3 Emulation
	Direct Image
	Microsoft XPS (XML Paper Specification)
	PDF 1.7 emulation
Fonts and Symbol Sets	3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide
	2 PCL bitmap fonts
	39 scalable PPDS fonts
	5 PPDS bitmap fonts
	84 scalable PCL fonts
	OCR-A, OCR-B scalable PCL 5e fonts
	For more information, refer to the Technical Reference.
	91 scalable PostScript fonts
Network Protocol Support	TCP/IP IPv4
	AppleTalk
	TCP/IP IPv6
	TCP
	UDP
Network Printing Methods	LPR/LPD
	Direct IP (Port 9100)
	Enhanced IP (Port 9400)
	FTP, TFTP
	ThinPrint .print integration
	IPP 1.0, 1.1, 2.0 (Internet Printing Protocol)

ComX Computers

Product Specification Sheet

Network Security	SNMPv3
	802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS
Network Management Protocols	HTTP
	HTTPs (SSL*/TLS)
	SNMPv1, SNMPv2c
	SNMPv3
	WINS
	IGMP
	APIPA (AutoIP)
	DHCP
	ICMP
	DNS
	Bonjour
	DDNS
	mDNS
	ARP
	NTP
	Telnet
	Finger
	*This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit.

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx-computers.co.za/3084048-Lexmark-MS610dn-A4-Mono-Laser-Printer-p-145603.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-28 15:50:14.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.