

5E1200UI

Eaton 5e Gen2 UPS 1200VA 660W USB IEC

Product Overview

Eaton 5e Gen2 UPS 1200VA 660W USB IEC, C14 Input, 6x C13 Outputs, Tower, Sealed Lead-Acid Battery Type, Line-interactive



Specifications

Overview:

Eaton 5E Gen2 UPS

The Eaton 5E Gen2 UPS combines proven high performance and quality with affordable pricing to offer cost-effective, reliable protection against power outages and bad power quality. Suitable for home use or for equipment in small business and professional environments, this latest version of our 5E line interactive UPS now also offers national outlets flexibility plus the convenience of permanently recharged batteries (even when off) and the ability to start without mains power (cold start).

CE certification by the external TUV agency guarantees compliance with the latest international safety standards.

Features:

Easy application connection and protection

A perfect fit for any local plug type thanks to national outlet formats (4 or 6 IEC and 2 or 4 for FR, DIN/IT, BS). Eaton's 5E Gen2 UPS offers single-product simplicity in multiple residential and commercial environments.

Greater tolerance of grid fluctuations

ComX Computers

Product Specification Sheet

All kinds of influences can upset grid voltage at any time. Features double-boost line interactive topology (AVR) for wider input voltage window (under and overvoltage: 140 - 300 V) to save battery power in the event of power outage.

Silent operation for a better customer experience

A key consideration in residential settings to ensure peace of mind as noisy equipment can distract - as well as add to stress levels. Thanks to a fanless design on all models up to 1200 VA, the 5E Gen2 UPS guarantees silent operation.

Specifications:

© 2024 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.	
Specifications	
Product Code	5E1200UI
GENERAL SPECIFICATIONS	
PRODUCT NAME	Eaton 5E Gen2 UPS
CATALOG NUMBER	5E1200UI
EAN	3553340704277
PRODUCT LENGTH/DEPTH	330 mm
PRODUCT HEIGHT	180 mm
PRODUCT WIDTH	133 mm
PRODUCT WEIGHT	8.13 kg
COMPLIANCES	CB
	LVD Directive
	EMC Directive
	RoHS Directive
	Packaging Directive
	WEEE Directive
	Batteries Directive
CERTIFICATIONS	IEC/EN 62040-1
	IEC/EN 62040-2
	CE
	EAC
	UKCA
	Cm
	Ukr
	IEC/EN 62040-3
PRODUCT SPECIFICATIONS	
SECONDARY FREQUENCY - MAX	60 Hz
WATTAGE	660 W
FORM FACTOR	Tower

ComX Computers

Product Specification Sheet

INCLUDES NETWORK CARD	No
INPUT CONNECTION	C14
INPUT VOLTAGE - MIN	140 V
OUTPUT VOLTAGE - MAX	257 V
SECONDARY FREQUENCY - MIN	50 Hz
SOFTWARE COMPATIBILITY	Eaton UPS Companion (enables safe system shutdown, energy usage metering and configuration of UPS settings)
BATTERY TYPE	Sealed, lead-acid
EFFICIENCY	95
SPECIAL FEATURES	Automatic Voltage Regulation (AVR)
	Saves space with a compact tower design
	HID-compliant USB port, for automatic integration with major operating systems (Windows/Mac OS/Linux)
CONSTRUCTION TYPE	Free standing model
OUTPUT VOLTAGE - MIN	195 V
COLOR	Black
EXTENDED BATTERY CAPABILITY	No
OUTPUT VOLTAGE RANGE	195-257 V
TOPOLOGY	Line-interactive
SURGE PROTECTION	Yes
INPUT NOMINAL VOLTAGE	230V default (220/230/240V)
INPUT FREQUENCY RANGE	45-63 Hz
INTERNAL BYPASS	No
INPUT VOLTAGE - MAX	300 V
VOLTAGE TYPE	AC
PHASE (OUTPUT)	1
BATTERY MANAGEMENT	Automatic battery test, deep-discharge protection, cold-start capable
AUTO SHUTDOWN FUNCTION	Yes
NUMBER OF OUTPUTS C13	6
OPERATING TEMPERATURE - MIN	0 degreesC
VA RATING	1200 VA
POTENTIAL FREE SWITCH CONTACT	No
RECEPTACLE	(6) C13
PHASE (INPUT)	1
PACKAGE CONTENTS	(2) IEC-IEC output cables
	Quick start
	Safety instructions

ComX Computers

Product Specification Sheet

FEED TYPE	1
USER INTERFACE	LEDs
BATTERY QUANTITY	2
OPERATING TEMPERATURE - MAX	40 degreesC
VOLTAGE	230V
HOT SWAP POWER	No
TEMPERATURE RANGE	0 degrees to 40 degreesC (32 degrees to 104 degreesF)
ETHERNET INTERFACE	No
COMMUNICATION	USB port (HID compliant)
RELATIVE HUMIDITY	0-90% non-condensing
OUTPUT APPARENT POWER	1200 VA
RACK MOUNTING KIT	No
OUTPUT FREQUENCY	50/60 Hz
TYPE OF INTERFACE	USB
PRIMARY FREQUENCY - MIN	45 Hz
BATTERY RATING	12 V / 7 Ah
TYPE	UPS
OUTPUT NOMINAL VOLTAGE	230V
EXPANSION SLOTS	No
INPUT VOLTAGE RANGE	140-300 V
NOMINAL FREQUENCY	50/60 Hz
PRIMARY FREQUENCY - MAX	63 Hz

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx-computers.co.za/5E1200UI-Eaton-5e-Gen2-UPS-1200VA-660W-USB-IEC-Buy-p-296783.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-14 11:28:46.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.