ComX Computers
Product Specification Sheet

5P650iR

Eaton 50 650i VA Rack 1U Line-Interactive High Frequency UPS

Product Overview

Eaton 50 650i VA Rack 1U Line-Interactive High Frequency UPS



Specifications

Specifications:

© 2024 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	5P650iR
General	
Topology	Line-Interactive High Frequency (Pure Sinewave, Booster + Fader)
Configuration	Rack 1U
Part Number	5P650iR
Rating (VA/Watts)	650/420
Dimensions (H x W x D, mm)	43.2 x 438 x 364
Weight (kg)	8.6
Warranty	3 years on electronics, 2 years on batteries
Contents	5P UPS

(Ships with the following items)	Eaton Intelligent Power Software CD
	USB cable
	Serial cable
	Safety guide
	Quick start guide
	CD with 10-language user manual
Electrical Input	
Connection	(1) IEC-320-C14
Input Voltage Without Using Batteries	160V-294V (adjustable to 150V-294V)
Input frequency Range Without Using Batteries	47 to 70Hz (50 Hz system), 56.5 to 70Hz (60 Hz system), 40Hz in low-sensitivity mode
Electrical Output	
Voltages	230 V (+6/-10 %) (Adjustable to 200V / 220V / 230V / 240V)
Output Receptacles	(4) IEC-320-C13
Remotely controlled sockets	2 groups of C13 (10 A) output receptacles, grouped 1+1
Output Frequency	50/60 Hz +/- 0.1 % (autosensing)
Battery	
Battery Management	ABM & temperature compensated charging method (user selectable), automatic battery test, deep discharge protection
Cold start (No mains power)	Yes
Communications	
User Interface	3 LEDS + Multilingual LCD : access to measures, alarm messages and customization
Communication Ports	1 USB port + 1 RS232 serial port and relay contacts (USB and RS232 ports cannot be used simultaneously), 1 mini-terminal block for remote ON/OFF and Remote Power Off
Communications Card Slots	1 slot for Network-MS card, ModBus-MS or Relay-MS cards
Environmental & Standards	
Audible Noise	< 40 dBA
Operating Temperature	0 to 35 degreesC
Safety markings	IEC/EN 62040-1
EMC Markings	IEC/EN 62040-2 class B (EMC), IEC/EN 62040-3 (performance), C-Tick
Approvals	CE, CB report
Quality	Designed, manufactured and marketed under ISO9001 & ISO14001 quality system

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/5P650iR-Eaton-50-650i-VA-Rack-1U-Line-Interactive-High-Frequency-UPS-p-306263.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-10 10:22:45.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.