ComX Computers
Product Specification Sheet

5PX1500IRT

Eaton 5PX 1500VA Tower Rack 2U Line-Interactive High Frequency UPS

Product Overview

Eaton 5PX 1500VA Tower Rack 2U Line-Interactive High Frequency UPS



Specifications

Overview:

The Eaton 5PX Rack/Tower UPS provides line-interactive backup power and scalable runtimes for servers, storage systems, VoIP gear and network equipment. With a next-generation intuitive LCD display, energy consumption metering down to the outlet group level, and up to 99% efficiency, the 5PX is the perfect UPS to protect modern IT equipment.

Features:

- Energy consumption metering down to the outlet group level
- Intuitive LCD screen displays all the information you need in one glance
- 5PX can provide up to 99% efficiency, reducing cooling and utility costs
- Delivered with Eaton's Intelligent Power Software compatible with all major OS including virtu-alization software
- 0.9 power factor to protect more servers from one UPS

Specifications:

© 2014 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	5PX1500IRT
General	
Topology	Line-Interactive High Frequency (Pure Sinewave, Booster + Fader)
Configuration	Tower/Rack 2U

Part Number	5PX1500iRT
Rating (VA/Watts)	1500/1350
Dimensions (H x W x D, mm)	86.2 x 441 x 522
Weight (kg)	28
Electrical Input	
Connection	(1) IEC-320-C14
Input Voltage Without Using Batteries	160V-294V (adjustable to 150V-294V)
Input frequency Range Without Using Batteries	47 to 70 Hz (50 Hz system), 56.5 to 70 Hz (60 Hz system), 40 Hz in low-sensitivity mode
Electrical Output	
Voltages	230 V (+6/-10 %) (Adjustable to 200V / 208V / 220V / 230V / 240V)
Outlets	(8) IEC-320-C13
Remotely controlled sockets	2 groups of 2 x IEC C13 (10 A)
Output Frequency	50/60 Hz +/- 0.1 % (autosensing)
Battery	
Battery Management	ABM & Temperature compensated charging method (user selectable), Automatic battery test, deep discharge protection, automatic recognition of external battery units
Communications	
Communication Ports	1 USB port + 1 RS232 serial port and relay contacts (USB and RS232 ports cannot be used simultaneously) + 1 mini terminal block for remote ON/OFF and Remote Power Off
Communications Card Slots	1 slot for NMC Minislot card or NMC ModBus/JBus or MC Contacts/Serial
Environmental & Standards	
Audible Noise	< 45 dBA
Operating Temperature	0 to 40 degreesC
Performance - Safety - EMC	IEC/EN 62040-1-1 (Safety), IEC/EN 62040-2 (EMC), IEC/EN 62040-3 (Performance)
Approvals	CE, CB report, TÜV

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/5PX1500IRT-Eaton-5PX-1500VA-Tower-Rack-2U-Line-Interactive-High-Frequency-UPS-p-99271.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-10 10:23:25.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken

to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.