**ComX Computers**
Product Specification Sheet

# 68401

Eaton EX 2200VA Tower/Rack 2U (Rack kit included) UPS

## Product Overview

Eaton EX 2200VA Tower/Rack 2U (Rack kit included) UPS




## Specifications

**Overview:**

The Eaton EX Uninterruptible Power System offers high-performance power protection. With the ability to be rack mounted or a standalone tower, this UPS is ideal for mid-range servers, networks, IT equipment, and medical and storage devices. With a low cost of ownership and a broad range of features, the EX UPS is one of the best in its class. EX UPS delivers clean, continuous backup power.

**Features:**

- Double Conversion UPS technology for 100% compatibility with any application, environment or genset and high output to protect equipment with PFC power supplies
- Wide input voltage window to conserve battery time for blackouts only
- Automatic by-pass for high availability
- Extended runtime capabilities with multiple, hot-swappable battery modules (optional)
- Remote reboot of locked equipment, sequential start-up through individually switchable outlets
- Works with the Intelligent Power Software Suite, which offers free monitoring, management and shutdown software ideal for protecting physical and virtual machines

**Specifications:**

© 2014 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

| Specifications | |
|---|---|
| **Product Code** | 68401 |

| | |
|---|---|
| **General** | |
| **Topology** | On-line double conversion with automatic by-pass and power factor correction |
| **Configuration** | Rack/Tower |
| **Style Number** | 68401 |
| **Color** | metallic grey |
| **Rating (VA/Watts)** | 2200/1980 |
| **Dimensions (H x W x D, inches)** | 3.39 x 17.32 x 25.2 |
| **Weight (lbs)** | 68.3 |
| **Warranty** | Carry-in warranty |
| **Hot-swappable Power** | Yes (with optional HotSwap MBP) |
| **Rail Kit Included** | Yes |
| **Contents** | 1 ready-to-go UPS |
| **(Ships with the following items)** | Power Management Software Suite CD |
| | USB Cable |
| | Serial Cable DB9/DB9 |
| | (2) brackets for 19" rack or wall-mounting |
| | Hardware mounting kit |
| | Safety guide |
| | Quick Start |
| | 4-language user manual |
| **Electrical Input** | |
| **Connection** | (1) IEC-320-C20 |
| **Input Voltage Range** | 100/120/140/160 V to 248V (Lower limits for |
| **Nominal Voltage** | 230 VAC |
| **Frequency** | 50/60 Hz |
| **Input frequency Range Without Using Batteries** | 40 to 70 Hz |
| **Electrical Output** | |
| **Output Receptacles** | (8) IEC-320-C13 |
| | (1) IEC-320-C19 |
| **Power Factor** | 0.9 |
| **Battery** | |
| **Optional Extended Battery Module** | 68405 |
| **Battery Management** | Programmable battery test, EXB auto recognition, automatic runtime adjustment, protection against deep discharge |
| **Battery Type** | Maintenance-free, sealed Lead-Acid battery |
| **Communications** | |

| | |
|---|---|
| **User Interface** | (3) LEDs adjustable multilingual display: display of measurements, access to control and setup menus |
| **Communication Ports** | (1) USB port, (1) RS232 serial port and relay contacts, (1) mini terminal block for remote On/Off and emergency stop |
| **Communications Slot** | 1 Minislot for Network Management Card |
| **Environmental & Standards** | |
| **Audible Noise** | 45 dBA |
| **Operating Temperature** | 32 degreesF to 104 degreesF (0 degreesC to 40 degreesC) continuous |
| **Performance - Safety - EMC** | IEC/EN 62 040-3 (VFI-SS-113), IEC/EN 62 040-1-1, IEC/EN 60 950-1 (RD), IEC/EN 62 040-2 C1 Class |
| **Approvals** | CE, TüV GS, CB report, UL 1778 cUL CSA 22.2 |

## Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

**Product page:**
**https://www.comx-computers.co.za/68401-Eaton-EX-2200VA-Tower-Rack-2U-Rack-kit-included-UPS-p-99446.php**

*Images and specifications are provided for reference and are subject to change without notice. E&OE.*

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-11 17:35:30.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.