ComX Computers
Product Specification Sheet

9E3000IR

Eaton 9e 3000i 3000VA 2400W Online Rack 2U UPS

Product Overview

Eaton 9e 3000i 3000VA 2400W Online Rack 2U UPS, LCD Display, Online/Double-conversion, C14 Input connection, 6x C13 & 1x C19 Output Ports, Pure Sine Wave, 230V AC Voltage, 6x 12V 9Ah sealed Lead-Acid batteries







Specifications

Overview:

9E3000IR

Eaton 9E UPS, 3000 VA, 2700 W, Input: C20, Outputs: (6) C13, (1) C19, Rack, 2U

Specifications:

© 2024 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	9E3000IR
GENERAL SPECIFICATIONS	

PRODUCT NAME	Eaton 9E UPS
CATALOG NUMBER	9E3000IR
EAN	3553340710353
PRODUCT LENGTH/DEPTH	608 mm
PRODUCT HEIGHT	86.5 mm
PRODUCT WIDTH	438 mm
PRODUCT WEIGHT	31.3 kg
COMPLIANCES	CE Marked
	TUV
CERTIFICATIONS	IEC/EN 62040-1
	IEC/EN 62040-2
	CE
PRODUCT SPECIFICATIONS	
SPECIAL FEATURES	Double conversion topology
	Constantly monitors power conditions and regulates voltage and frequency
	Provides more real power (watts) to protect more equipment with a 0.9 power factor
	Internal bypass allows service continuity in case of UPS fault
	LCD display
	Long backup time with up to 4 optional EBM
TYPE	UPS
TOPOLOGY	Online/Double-conversion
FORM FACTOR	Rack
RACK SIZE	2U
CONSTRUCTION TYPE	482.6 mm (19 inch) device
COLOR	Black
VA RATING	3000 VA
WATTAGE	2700 W
RACK MOUNTING KIT	Yes
PACKAGE CONTENTS	UPS
	(2) IEC-IEC output cables
	USB cable
	Rack-mounting kit (rails and brackets)
	Safety instructions
	Quickstart guide
INTERNAL BYPASS	Yes
HOT SWAP POWER	No
AUTO SHUTDOWN FUNCTION	Yes

PRIMARY FREQUENCY - MAX	70 Hz
PRIMARY FREQUENCY - MIN	40 Hz
INPUT CONNECTION	C14
INPUT CORD LENGTH	1.8m
INPUT NOMINAL VOLTAGE	230V default (220/230/240V)
NOMINAL FREQUENCY	50/60 Hz
INPUT FREQUENCY RANGE	40-70 Hz
INPUT POWER FACTOR	>.99
RECEPTACLE	(6) C13 + (1) C19
NUMBER OF OUTPUTS C13	6
NUMBER OF OUTPUTS C19	1
OUTPUT WAVEFORM	Sine wave
VOLTAGE	230V
OUTPUT NOMINAL VOLTAGE	230V default (220/230/240V)
FEED TYPE	1
VOLTAGE TYPE	AC
RUNTIME GRAPH	
BATTERY MANAGEMENT	Temperature compensated charging method
	Automatic battery test
	Deep discharge protection
BATTERY REPLACEMENT	Replacable batteries
BATTERY RATING	12 V / 9 Ah
BATTERY TYPE	Sealed, lead-acid
EXTENDED BATTERY CAPABILITY	Yes
RUNTIME AT HALF LOAD	10.5 min
COMMUNICATION	USB port (HID compliant)
	Serial port (RS232)
	Mini-terminal block for remote power off
EXPANSION SLOTS	One slot for optional communication card
ETHERNET INTERFACE	No
INCLUDES NETWORK CARD	No
SOFTWARE COMPATIBILITY	Eaton Intelligent Power Manager, Eaton Intelligent Power Protector
USER INTERFACE	Multilingual LCD display
TYPE OF INTERFACE	Other
POTENTIAL FREE SWITCH CONTACT	Yes
ALTITUDE	3000 m

BTU RATING	Online: 818
NOISE LEVEL	
RELATIVE HUMIDITY	0-96% non-condensing
TEMPERATURE RANGE	0 degrees to 40 degreesC (32 degrees to 104 degreesF)
INPUT VOLTAGE - MAX	276 V
INPUT VOLTAGE - MIN	140 V
OUTPUT VOLTAGE - MAX	240 V
OUTPUT VOLTAGE - MIN	220 V
SECONDARY FREQUENCY - MAX	60 Hz
SECONDARY FREQUENCY - MIN	50 Hz
BATTERY QUANTITY	6
EFFICIENCY	91
EFFICIENCY (ECO-MODE)	97
MAX NUMBER OF BATTERY PACKS	4
OUTPUT FREQUENCY	50/60 Hz
OUTPUT POWER FACTOR	0.9
OUTPUT VOLTAGE RANGE	220/230/240 V +/- 2%
PHASE (INPUT)	1
PHASE (OUTPUT)	1
RUNTIME AT FULL LOAD	3.5 min
VOLTAGE DISTORTION OUTPUT (LINEAR LOAD) - MAX	3

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/9E3000IR-Eaton-9e-3000i-3000VA-2400W-Online-Rack-2U-UPS-p-303947.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-15 02:26:36.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.