ComX Computers
Product Specification Sheet

9VJ40AA

HP EliteDisplay E24i G4 23.8" IPS WUXGA 1920x1200 LED backlit Monitor, HDMI, DP, VGA

Product Overview

HP 9VJ40AA EliteDisplay E24i G4 23.8" IPS WUXGA 1920x1200 LED backlit Monitor, 16:10 Aspect Ratio, 250 nits brightness (typical), 1000:1 static contrast ratio (typical), 5ms On/Off response times, Low Blue light mode, Anti-Glare, 1x VGA, 1x USB Type-B, 1x HDMI 1.4, 1x DisplayPort 1.2, 4x USB Type-A 3.2 Gen 1, 100 mm x 100 mm VESA Mount







Specifications

Specifications:

© 2022 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	9VJ40AA
Panel	
Product number	9VJ40AA
Display panel type	IPS

Viewable image area (diagonal)	24"
Panel active area (W x H)	51.84 x 32.4 cm
Resolution	WUXGA (1920 x 1200)
Aspect ratio	16:10
Brightness (typical)	250 nits
Contrast ratio (typical)	1000:1 static
Response times	5ms GtG (with overdrive)
Pixel pitch	0.27 mm
Display features	Low blue light mode, Anti-glare
Onscreen controls	
User controls	Brightness, Exit, Information, Management, Power control, Input control, Menu control, Image, Color
Resolutions supported	
Signal interface/performance	1024 x 768, 1280 x 1024, 1280 x 720, 1280 x 800, 1440 x 900, 1600 x 900, 1680 x 1050, 1920 x 1080, 1920 x 1200, 640 x 480, 720 x 400, 800 x 600
Video/other inputs/cables	
Interface	HDMI, VGA, USB hub, DisplayPort
Display Input Type	1 VGA, 1 USB Type-B, 1 HDMI 1.4, 1 DisplayPort 1.2, 4 USB-A 3.2 Gen 1
Ergonomics	
VESA mount	100 mm x 100 mm
Physical security	Security lock-ready
Power	
Input voltage	Input voltage 100 to 240 VAC
Power consumption	53 W (maximum), 36 W (typical), 0.5 W (standby)
Physical specifications	
Dimensions With Stand (W x D x H)	53.2 x 20.69 x 50.96 cm
Dimensions (W x D x H)	53.2 x 4.7 x 35.27 cm
Minimum dimensions (W x D x H)	20.94 x 1.85 x 13.88 in
Product dimensions with stand (W x D x H)	20.94 x 8.15 x 20.06 in
Weight	13.36 lb
What's in the box	
What's in the box	Monitor, DisplayPort 1.2 cable, HDMI cable, USB Type-A to B cable, QSP, AC power cable
Environmental	
Operating temperature range (deg C)	5 to 35 degreesC
Operating temperature range (deg F)	41 to 95 degreesF

Operating humidity range	20 to 80% non-condensing
Certifications and compliances	BIS, BSMI, CB, CCC, CE, CECP, CEL, EAC, ENERGY STAR, FCC, ISO 9241-307, KC/KCC, NOM, PSB, SEPA, TCO Certified, TCO Certified Edge, TUV LBL, TUV-S, VCCI, WEEE, ISC, California Energy Commission (CEC), WW application, ICE, TGM, TUV-GS

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/9VJ40AA-HP-EliteDisplay-E24i-G4-23-8-IPS-WUXGA-1920x1200-LED-backlit-Monitor-HDMI-p-262534.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-14 22:07:38.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.