ComX Computers
Product Specification Sheet

A7522122

Dell Smart-UPS 1500VA LCD 230V Line interactive

Product Overview

Dell A7522122 Smart-UPS 1500VA LCD 230V Line interactive, 1x power IEC 60320 C14 Input Connectors, 8x power IEC 60320 C13 Power Output Connectors





Specifications

Overview:

Dell SMART-UPS 1500VA LCD 230V-1000-watt-UPS #DLT1500I

Manufacturer Part# : DLT1500I
Dell Part# : A7522122

Features:

- High online efficiency Reduces utility costs, generates less heat.
- Intuitive LCD interface Provides clear and accurate information in multiple languages with the ability to configure the UPS locally with easy to use navigation keys.
- Single switched outlet group Single outlet group that may be controlled separately from the UPS for discrete reboot of hung devices, sequenced on/off and non-critical load shedding.
- SmartSlot Customize UPS capabilities with management cards.
- Cold-start capable Provides temporary battery power when the utility power is out.
- Temperature-compensated battery charging Prolongs battery life by regulating the charge voltage according to battery temperature.
- Predictive replace battery date Dynamically provides the month and year when battery replacement is recommended to aide in long term maintenance planning.
- Energy meter Provides actual kilowatt hours of usage for energy conscious users.
- Pure sine wave output on battery Simulates utility power to provide the highest degree of compatibility for active PFC (power factor corrected) servers and sensitive electronics.
- Green mode Patent-pending operating mode that bypasses unused electrical components in good power conditions to achieve very high operating efficiency without sacrificing any protection.

Availability

- Boost and Trim Automatic Voltage Regulation (AVR) Gives higher application availability by correcting low and high voltage conditions without using the battery (not available on all models).
- Intelligent battery management Maximizes battery performance, life, and reliability through intelligent, precision charging.
- Power conditioning Protects connected loads from surges, spikes, lightning, and other power disturbances.
- Temperature-compensated battery charging Prolongs battery life by regulating the charge voltage according to battery temperature.
- Automatic restart of loads after UPS shutdown Automatically starts up the connected equipment upon the return of utility power.
- Automatic self-test Periodic battery self-test ensures early detection of a battery that needs to be replaced.
- Disconnected battery notification Warns when a battery is not available to provide backup power.

Manageability

- Network manageable Provides remote power management of the UPS over the network.
- Audible alarms Actively let you know if the unit is on battery, if the battery is low or if there is an overload condition.
- LED status indicators Quickly understand unit and power status with visual indicators.
- Serial connectivity Provides management of the UPS via a serial port.
- USB connectivity Provides management of the UPS via a USB port (not available on all models).
- Disconnected battery notification Warns when a battery is not available to provide backup power.

Serviceability

- User-replaceable batteries Increases availability by allowing a trained user to perform upgrades and replacements of the batteries reducing Mean Time to Repair (MTTR)
- Hot-swappable batteries Ensures clean, uninterrupted power to protected equipment while batteries are being replaced
- Predictive failure notification Provides early-warning fault analysis ensuring proactive component replacement.
- Resettable circuit breakers Enables a quick recovery from overload events.
- Battery failure notification Provides early-warning fault analysis on batteries enabling timely preventive maintenance

Adaptability

- Adjustable voltage-transfer points Maximizes useful battery life by widening the input voltage window or tightening the output voltage regulation.
- Adjustable voltage sensitivity Provides the ability to adapt the UPS for optimal performance in specific power environments or generator applications.

Safety

- Safety-agency approved Ensures the product has been tested and approved to work safely with the connected service provider equipment and within the specified environment.

Specifications:

© 2018 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	A7522122
General	
Device Type	UPS - external
Colour	Black
Power Device	

UPS Technology	Line interactive
Input Voltage	AC 230 V
Input Voltage Range	AC 151 - 302 V
Frequency Provided	50/60 Hz
Frequency Required	50/60 Hz
Input Connectors	1 x power IEC 60320 C14
Power Output Connectors Details	8 x power IEC 60320 C13
Output Voltage	AC 230 V 50/60 Hz
Power Capacity	1000 Watt / 1500 VA
Output Waveform	Sinewave
Surge Energy Rating	459 Joules
Battery	
Technology	Lead Acid
Run Time (Up To)	7 min at full load
	12 min at 700 Watts
	23 min at 500 Watts
	84 min at 200 Watts
Recharge Time	3 hour(s)
Features	Maintenance free, sealed, leak-proof
Networking	
Remote Management Interface	RS-232, USB
Expansion / Connectivity	
Interfaces	1 x management (USB) - 4 pin USB Type B
	1 x management (RS-232) - RJ-45
Expansion Slots	1 (total) / 1 (free) x SmartSlot
Miscellaneous	
Cables Included	Power cable - external - 1.83 m
Features	Audible alarm, LCD display
Compliant Standards	C-Tick, GOST, VDE, RoHS, EN 60950-1, REACH, EN 62040-2, EN 62040-1:2008
Environmental Parameters	
Min Operating Temperature	0 degreesC
Max Operating Temperature	40 degreesC
Humidity Range Operating	0 - 95%
Sound Emission	45 dBA
Dimensions & Weight	
Width	17.1 cm
Depth	43.9 cm

Height	21.9 cm
Weight	24.09 kg
Dimensions & Weight (Shipping)	
Shipping Width	32.8 cm
Shipping Depth	59.5 cm
Shipping Height	37.6 cm
Shipping Weight	27.23 kg

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/A7522122-Dell-Smart-UPS-1500VA-LCD-230V-Line-interactive-p-197345.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-09 09:42:38.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.