

AR3307

APC NetShelter 48U 600mm x 1200mm Server Enclosure with roof and sides - Black

Product Overview

NetShelter SX 48U / 600mm / 1200mm Enclosure with Roof and Sides - Black



Specifications

Overview:

Feature-rich enclosures optimized for easy installation, managing cables, integrating power distribution, and maximizing airflow.

Features:

- Guaranteed Compatibility

Vendor-neutral mounting for guaranteed compatibility with all EIA-310 compliant 19" equipment. The APC "Fits Like a Glove" money back guarantee provides peace of mind that all of your EIA-310-E compliant rack-mount equipment will physically fit in a NetShelter enclosure.

- Facilitates overhead cable management

Overhead cable troughs and partitions install toollessly on the roof of the enclosure eliminating the need for ceiling mounted or underfloor mounted cable trays. Cable troughs and partitions are designed to manage both power and data cables while maintaining separation.

- Integrated with APC InfraStruXure products

APC cooling, power distribution, and cable management products work seamlessly with the enclosures to provide a complete infrastructure support system.

Convenience

- Cable Access

Large cable access slots in the roof provides access for overhead cable egress. The bottom design allows for unobstructed cable access through a raised floor.

- Simple Selection

No need to spend hours choosing from and compiling dozens of part numbers to create a single enclosure. APC has made it easy by handling the details and providing complete enclosures with single part numbers.

- Ventilated

Perforated front and rear doors provide ample ventilation for rack-mount equipment.

ComX Computers

Product Specification Sheet

- Quick release doors

Front door can be moved to the opposite side or interchanged with rear doors. Doors are easily removed with simple lift-off design.

- Half-height side panels

Half-height quick release side panels reduce size and weight for easy handling and access to equipment. Side panels are lockable utilizing a single key with the doors.

Agility

- Rear Cable Management channels

Integrated and adjustable rear channel provides zero U mounting locations for toolless accessories. Each channel has two mounting bays to support a combination of up to four accessories such as PDUs and vertical cable organizers.

- Adjustable mounting rails

The vertical mounting rails can be adjusted in 1/4 in (6.4 mm) increments covering virtually any mounting requirement for IT equipment. U positions are numbered front and back for rapid installation of equipment.

- Split rear doors

Split rear doors improve access and serviceability to rear of rack mounted equipment. The split rear doors help to maximize floor space. Only 11 inches (279 mm) of clearance is required behind the enclosures to allow for door swing.

- Castors and adjustable leveling feet

Enclosures are shipped standard with both leveling feet and castors. Leveling feet can be quickly adjusted through the use of a screwdriver or drill, eliminating the need to reach underneath with a wrench.

- Joining capability

Enclosures include pre-installed joining hardware to join enclosures in a row and provide additional stability to the enclosure.

Safety

- Structural Stability

A proven frame design, heavy-gauge mounting rails, and heavy-duty casters provide for 3000 lb (1364 kg) static and 2250 lb (1023 kg) dynamic load ratings.

- Integrated electrical grounding

The roof, side panels and front and rear doors are grounded to the frame of the enclosure. Eight additional electrical grounding inserts are located on the frame for external grounding.

Specifications:

© 2015 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	AR3307
--------------	--------

Physical

Net Weight	149.55 KG
Maximum Height	2258.00 mm
Maximum Width	600.00 mm
Maximum Depth	1200.00 mm
Weight Capacity (static load)	1363.64 KG
Weight Capacity (dynamic load)	1022.73 KG

ComX Computers

Product Specification Sheet

Minimum Mounting Depth	191.00 mm
Maximum Mounting Depth	1060.00 mm
Rack Height	48U
Rack Width	19"
Color	Black
Vertical Posts	16 gauge
Front Door	16 gauge
Rear Door	18 gauge
Roof	18 gauge
EIA Mounting Rails	14 gauge
Side Panels	18 gauge
Conformance	
Regulatory Approvals	UL 60950
Standards	EIA-310-E
Environmental Compliance	RoHS, China RoHS, REACH: Contains No SVHCs

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/AR3307-APC-NetShelter-48U-600mm-x-1200mm-Server-Enclosure-Buy-p-111201.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-11 08:22:42.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.