

B098-048

Eaton Tripp Lite series 48-Port Console Server

Product Overview

Eaton Tripp Lite series 48-Port Console Server, USB Ports (2) - Dual GbE NIC, 16 Gb Flash, SD Card, Desktop/1U Rack, TAA, Order on Request



Specifications

Overview:

48-port serial console server lets you remotely access and control serial-based networking equipment through one highly secure gateway.

- Manage routers, UPS systems and other serial-based equipment from anywhere 24/7
- Validated to meet FIPS 140-2 standards to ensure utmost protection of private data
- Dual Gigabit Ethernet ports for primary network connection and automatic failover
- Designed for standard Cat5e/6 patch cable when connecting to Cisco devices

Features:

Access All Your Serial and Network Devices from Anywhere in the World at Any Time

This USB console server provides secure in-band (primary network) and out-of-band (alternate channel) remote access to serial- and network-connected routers, network switches, firewalls, PBX systems, UPS systems, PDUs and other devices. It offers reliable network connectivity with dual Gigabit primary and failover Ethernet ports, dual SFP ports for fiber optic network connections, and dual power supplies. You can use it in a wide variety of applications, including wiring closets, branch offices, kiosks, point-of-sale and other remote sites where a quick identification and resolution of network issues is imperative. You'll be able to manage a critical equipment outage quickly and remotely without making a costly and time-consuming physical visit to the site.

Simple and Flexible Accessibility

The 48 RJ45 console ports are configured to use standard Cat5e/6 patch cable when connecting to Cisco devices. They integrate with industry-standard directory servers using TACACS+, RADIUS, LDAP and Kerberos authentication. Provides 16 Gb of internal NAND flash memory, which can be used for log storage and file storage, and is expandable with an SD card.

Connect the Built-In V.92 Modem for Out-of-Band (OOB) Access

For OOB access, connect an RJ11 cable between the front-facing RJ11 port and a functioning landline port to allow the V.92 modem to dial out.

Router/Gateway

Each gateway can port forward to an unlimited number of locally networked hosts (computers, routers). This rack console also includes a built-in stateful firewall and embedded DHCP server to host a separate management LAN for critical traffic.

The Utmost in Security to Keep Your Sensitive Data Private

The B098-048 supports the following security features and standards: PCI DSS 3.2, FIPS 140-2, SSL and SSH, stateful firewall, OpenVPN and IPsec VPN support. The embedded FIPS 140-2 OpenSSL cryptographic module is validated to meet FIPS 140-2 standards and has received Certificate #2473.

PowerMan PDU and UPS Support

This USB console server uses PowerMan for PDU and RPC management and Network UPS Tools for UPS system monitoring and management. It provides support for a range of power products, so you can remotely manage power to your connected equipment.

USB Console

Two USB 3.0 console ports, supporting speeds up to 5Gbps, allow connection to newer devices with USB console ports, such as wide variety of PDUs and UPS systems with WEBCARDLX and LX Platform remote management cards.

Compact Design for Convenient Mounting

The heavy-duty steel housing comes with mounting brackets for 1U installation in an EIA-standard 19-inch rack. Its fanless form factor also allows desktop deployment on included rubber feet that help prevent the unit from sliding.

TAA-Compliant for GSA Schedule Purchases

The B098-048 is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

- B098-048 48-Port Serial Console Server

ComX Computers

Product Specification Sheet

- (2) C13 to NEMA 5-15P power cords, 6 ft.
- (2) Cat5 patch cables, 6 ft.
- Straight-through serial adapter, DB9 to RJ45 (F/F)
- Crossover serial adapter, DB9 to RJ45 (F/F)
- Modular serial adapter, DB9 to RJ45 (M/F)
- Cisco rolled straight-through serial adapter, DB9 to RJ45 (F/F)
- Cisco rolled crossover serial adapter, DB9 to RJ45 (F/F)
- Cisco rolled modular serial adapter, DB9 to RJ45 (M/F)
- Cisco straight pinout (x2) loopback, black
- Cisco rollover pinout (x1) loopback, red
- Rack-mounting hardware
- Quick Start Guide

Specifications:

© 2024 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	B098-048
--------------	----------

OVERVIEW

UPC Code	37332218063
----------	-------------

Multi-User	Yes
------------	-----

INPUT

Voltage Compatibility (VAC)	100 , 110 , 120 , 125 , 127 , 200 , 208 , 220 , 230 , 240
-----------------------------	---

Power Input Receptacle	IEC-320-C14
------------------------	-------------

Redundancy - Dual Power Inputs	Yes
--------------------------------	-----

POWER

Power Consumption (Watts)	15
---------------------------	----

CONNECTIONS

Number of Ports	48
-----------------	----

Side A - Connector 1	(2) USB A (FEMALE)
----------------------	--------------------

Side A - Connector 2	RJ11 (FEMALE)
----------------------	---------------

Side A - Connector 3	RJ45 (FEMALE)
----------------------	---------------

Side A - Connector 4	SD (FEMALE)
----------------------	-------------

Side B - Connector 1	(48) RJ45 (FEMALE)
----------------------	--------------------

Side B - Connector 2	(2) SFP (FEMALE)
----------------------	------------------

Side B - Connector 3	(2) RJ45 (FEMALE)
----------------------	-------------------

USER INTERFACE, ALERTS & CONTROLS

LED Indicators	9 LED's for Power, Heartbeat-Firmware Running, Serial Connectivity, Network Ports
----------------	---

PHYSICAL

ComX Computers

Product Specification Sheet

Color	Black
Material of Construction	Metal
Rackmountable	Yes
Shipping Dimensions (hwd / in.)	3.30 x 16.10 x 19.30
Shipping Weight (lbs.)	10.4
Unit Dimensions (hwd / in.)	17.000 x 10.000 x 1.750
Unit Packaging Type	Box
Unit Weight (lbs.)	10
ENVIRONMENTAL	
Operating Temperature Range	41 degrees to 122 degreesF (5 degrees to 50 degreesC)
Storage Temperature Range	-22 degrees to 140 degreesF (-30 degrees to 60 degreesC)
Relative Humidity	5% to 90% RH, Non-Condensing
BTUs	51.2 BTU/Hr
COMMUNICATIONS	
IP Remote Access	Yes
Network Compatibility	1 Gbps (Gigabit)
IEEE Standards Supported	802.3 , 802.3ab , 802.3ad
FEATURES & SPECIFICATIONS	
USB Specification	USB 3.0 (up to 5 Gbps) , USB 3.1 Gen 1 (up to 5 Gbps)
Port Selection	CLI , GUI
Driver Required	No
Authentication Supported	RADIUS , LDAP , TACACS
Common Access Card (CAC) Support	No
STANDARDS & COMPLIANCE	
Product Compliance	Trade Agreements Act (TAA)

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/B098-048-Eaton-Tripp-Lite-series-48-Port-Console-Server-Buy-p-312334.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-11 15:09:31.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

ComX Computers

Product Specification Sheet

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.