CAM-IPV57-41UDR-Z

Sunell IPV57-41UDR-Z 4MP Motorized Vandal Network IR Dome Camera

Product Overview

Sunell IPV57-41UDR-Z 4MP Motorized Vandal Network IR Dome Camera, 1/3" Progressive Scan CMOS, Motorized lens, 2.7~12mm, 25fps/ 30fps@4MP (2592x1520), Triple Streams, Smart IR Up to 30m, Low bitrate, Excellent low light performance, WDR, 3D DNR, ROI, Defog, HLC, Corridor mode, DIS, IP67, IK10



Specifications

Overview:

Pro series products by upgrading H.265 encoding technology, bringing high efficient video compression . It saves bandwidth and storage, energy-saving design to enhance the monitoring system . Meanwhile, the series offers features such as starlight, Smart IR technology, intelligent image analysis techniques. It provides excellent image quality and intelligent and efficient event reminders. This series provides IP67 weatherproof and IK10 vandal-proof protection feature.

Features:

Wide Dynamic Range
Embedded with industry leading wide dynamic range (WDR) technology, vivid pictures are achieved even in the most intense contrast lighting conditions. For applications with both bright and low lighting conditions that change quickly, true WDR (120dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

Intelligent Video System (IVS)
With built-in intelligent video analytics, the camera has the ability to detect and analyze moving objects for improved video surveillance. The camera provides optional standard intelligence at the edge allowing detection of Perimeter, Single Virtual Fences, Double Virtual Fences Loiter, Multi Loiter, Object Left, Object Removed, Abnormal Speed, Converse, Illegal Parking, Signal Bad.

Environmental
With a temperature range of -30 degreesC to +60 degreesC (-22 degreesF to +140 degreesF), the camera is designed for extreme temperature environments. Subjected and certified to rigorous dust and water immersion tests, the IP67 rating makes it suitable for demanding outdoor applications.

Smart Encode(H.265+)
Deliver high quality video without straining the network, Smart Encode H.265+ is the optimized implementation of H.265. The

Smart H.265+ encoding technology includes a scene adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction, providing saving of up to 70% of bandwidth and storage when compared with standard H.265.

HEVC (H.265)
H.265 ITU-T VCEG is a new video coding standard. H.265 Following standard developed around the existing video coding standard H.264 , some retain the original technology , while some of the relevant technology to improve the new technology uses advanced technology to improve the relationship between the code stream , encoding quality , and the delay between algorithm complexity , optimize settings specific contents include : Improve compression efficiency , improve the robustness and error recovery capabilities, real-time to reduce the delay, reduce channel acquisition time and a random access delay , reduce complexity.

Specifications:

© 2019 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	CAM-IPV57-41UDR-Z
Camera	
Image Sensor	1/3" Progressive Scan CMOS
Effective Pixels	2592(H)x1520(V)
Scanning System	Progressive
Electronic Shutter	1/5-1/20000s
Min. illumination	Color:0.05Lux@(F1.2, AGC ON)
	B/W:0Lux@(IR LED ON)
S/N Ratio	55dB
IR Range	Up to 30m
IR On/Off Control	Auto/ Manual
IR LEDs	15pcs
Pan/Tilt/Rotation Range	Pan:0 degrees~355 degrees, Tilt:0 degrees~80 degrees, Rotation:0 degrees~355 degrees
Lens	
Lens Type	Motorized
Iris	Auto Iris
Focal Length	2.7~12mm
F Number	F1.3
Angle of View	100 degrees~ 30 degrees
Focus Control	Motorized
Close Focus Distance	0.2m
Video	
Compression	H.265, H.264, MJPEG

Max. Resolution	4MP(2592x1520)
Streaming Capability	3 Streams
Stream /	Stream1: 2592x1520/2560x1440/2304x1296/ 1920x1080/1280x720 @25/30fps
Frame Rate	Stream2: D1/VGA/640x360/CIF/QVGA @25/30fps
	Stream3: VGA/CIF/QVGA @25/30fps
Bit Rate Control	CBR/VBR
Bit Rate	Stream1: 500kbps~12000kbps
	Stream2: 100kbps~6000kbps
	Stream3: 100kbps~3000kbps
Day/Night	ICR
Image Enhancement	HLC / Defog / WDR (120dB)
White Balance	Support
Gain Control	Auto/Manual
Noise Reduction	2D/3D DNR
Electronic Image Stabilization(EIS)	Support
Smart IR	Support
Mirror	Support
Region of Interest	Support
Motion Detection	Support
Privacy Masking	Support
Audio	
Compression	G.711, RAW_PCM
Bit Rate	64kbps (G.711), 128kps (RAW_PCM)
Network	
Protocols	IPv4/IPv6, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTP, PPPoE, SMTP, DNS, UPnP, FTP, APR, SNMP
Interoperability	ONVIF
Streaming Method	Unicast
Max. User Access	10 Users
Web Viewer	
Management Software	IMS 3.0
Smart Phone	IOS, Android
Intelligence	
IVS	Perimeter, Single Virtual Fences, Double Virtual Fences, Loiter, Multi Loiter, Object Left, Object Removed, Abnormal Speed, Converse, Illegal Parking, Signal Bad
Interface	
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector

Audio Interface	1ch Audio In, 1ch Audio Out
Alarm	1ch Alarm In, 1ch Alarm Out
RS485	Support
BNC Output	Support
Reset Button	Support
Edge Storage	Micro SD, Max 128GB
Electrical	
Power Supply	DC12V/POE/AC24V
Power Consumption	3.5W(IR LED OFF), 7W(IR LED ON)
Operating Temperature	Starting Temperature: -30 degreesC ~ 60 degreesC (-22 degreesF ~ 140 degreesF)
	Working Temperature: -40 degreesC ~ 60 degreesC (-40 degreesF ~ 140 degreesF)
Operating Humidity	Less than 90% RH
Ingress Protection	IP67, IK10
Certifications	CE / FCC
Casing	Metal
Dimensions	Ø130x112mm
Net Weight	900g

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/CAM-IPV57-41UDR-Z-Sunell-IPV57-41UDR-Z-4MP-Motorized-Vandal-Network-IR-Dome-Camera-p-214836.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-15 17:47:26.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.