CH-GC500G

Gigabyte C500 Aorus Glass eATX Tempered Glass Tower case - Black

Product Overview

Gigabyte C500 Aorus Glass eATX Tempered Glass Tower case - Black, 2x 3.5"/2.5" Drive bays, 2x 2.5" Drive bays, I/O panel - 1x USB 3.1 Gen2 Type-C / 2x USB 3.0 / audio in & out, 190mm CPU height, 420mm GPU length, 220mm PSU length, RGB Lighting, C500G





Specifications

Overview:

- Optimized Airflow design
- Support Motherboards up to E-ATX
- Up to 420mm Liquid Cooling Compatible
- Support Vertical GPU Installation
- Modular Easy Installation
- Full-Size Tempered Glass Side Panel
- With USB 3.0 x2 and USB 3.1 Gen2 Type-C x1 on I/O panel
- RGB Fusion 2.0
- Pre-installed 4 fans with ARGB & PWM Connector Hub

Features:

OPTIMIZED AIRFLOW DESIGN
The AORUS C500 GLASS comes with the large mesh front and the vented top panel, delivering generous airflow with premium aesthetics.

MAX COOLING POTENTIAL
The large interior offers extra space that allows users to add 3 more 120mm fans on top of the space that houses the triple 120mm fans in both the front and roof position along with a radiator.

MAX COMPATIABILITY
The AORUS C500 GLASS is compatible with every single AORUS component and has room to hold up to E-ATX motherboards and radiators up to 420mm, providing users with the upmost flexibility.

CABLE MANAGEMENT LIKE A PRO

A series of grooves and cutouts are located behind the board and along the case edges for smart and tidy cable management, which can shorten your building time.

EASY-ACCESS SWING DOOR FRONT PANEL
The swing door design allows easy front access without having to remove the entire panel, which avoids the risk of detaching any cables by accident.

PSU INSTALLATION MADE EASY
The PSU can be mounted on the mounting plate without removing any screw, making it convenient for users to assemble. This design is also more flexible to install and remove components when upgrading equipment.

HIDDEN POWER. SUCCINCT BEAUTY.
The PSU shroud is designed to shield messy and intertwined power cables while isolating the heat generated from the PSU.

EASY MAINTENANCE
The filters keep your PC from accumulating dust, while maintaining optimal cooling performance. The top and front magnetic filters, along with the removable filter at the bottom, make maintenance easy.

TEMPERED GLASS PANEL WITH ANTI-DROPPING DESIGN
The 4mm tempered glass side panel is thoughtfully designed to be removed by tilting out the top first to prevent accidental drops. The non-drilled design further improves the glass panel's strength and safety.

REAL 11 CORE CABLE.
The 2 USB 3.0 ports use the 11-core USB cables to ensure stable signal integrity. The front I/O also offers versatile connectivity, including a USB 3.1 Gen-2 Type-C port and an audio port.

RGB FUSION 2.0
With 16.7M customizable color options and numerous lighting effects, you can choose lighting effects or synchronize with other AORUS devices.

*The type of RGB lighting effect depends on the MB support.

- WAVE
- CYCLE
- PULSE
- FLASH
- DOUBLE FLASH
- STATIC

ARGB & PWM CONNECTOR HUB
The built-in ARGB and PWM connector hub is equipped with 5x 5V 3-pin and 5x PWM connectors, enabling users to expand their RGB light stripes, create a superb cooling system as well as a fantastic and gorgeous rig.

Specifications:

© 2022 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	CH-GC500G
Case Form Factor	Mid Tower

M/B Type	Mini ITX / Micro ATX / ATX / E-ATX
Color	Black
Materials	Steel, Plastic, Glass
Dimensions	H=548 W=250 D=482 mm (Within +/- 1% error)
Expansion slots	8 + 3 (Requires PCIE Riser Cable)
5.25" Drive Bays	None
3.5"/2.5" Drive Bays	2
2.5" Drive Bays	2
I/O Panel	USB 3.1 Gen2 Type-C x1 / USB 3.0 x2 / Audio In & Out
	(supports AC97 /HD Audio)
Pre-installed Fan	Front : 120mm x3 (ARGB & PWM)
	Rear : 120mm x1 (ARGB & PWM)
Fan Support	Front : 120mm x3 / 140mm x3
	Top : 120mm x3 / 140mm x2
	Rear : 120mm x1 / 140mm x1
Radiator Support	Front : Max 420mm
	Top : Max 360mm
	Rear : 140mm
Power Supply Type	Standard ATX (Not included)
Maximum Compatibility	CPU Height : 190mm
	GPU Length : 420mm
	PSU Length : 220mm
Vertical GPU Mount	Yes (Default: 73mm total clearance / VGA holder bracket: 160mm total clearance)
Dust Filters	Top, Front, Bottom
RGB Lighting	Yes (Support RGB Fusion 2.0)
Weight	N.W. 13.4 Kg
Package Dimensions	H=594 W=336 D=584 mm
Accessories	1. Manual
	2. Accessories kit

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/CH-GC500G-Gigabyte-C500-Aorus-Glass-eATX-Tempered-Glass-Tower-case-Black-p-272778.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-21 21:44:22.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.