

CL-F149-PL12SW-A

Thermaltake CT120 ARGB Sync PC cooling fan - 2 fan pack

Product Overview

Thermaltake CT120 ARGB Sync PC cooling fan - 2 fan pack, 120 x 120 x 25 mm fan dimension, 57.05 CFM Max Air Flow, Hydraulic bearing, 4 pin PWM connector, 3 pin-argb connector



Specifications

Overview:

CT120 ARGB Sync PC Cooling Fan (2-Fan Pack)

CL-F149-PL12SW-A

CT120 ARGB Sync PC Cooling Fans are Thermaltakes new generation PWM fans designed to fit all PC usage scenarios. The CT Series Fans have a fan speed of 2000 RPM and are made with specially tuned fan blades that can push the air further. The new Cable-Integrated Daisy-Chain Design provides more flexibility in cable management, and its 9 addressable LEDs can be controlled through motherboard sync software for spectacular lighting effects.

Features:

Unify Your Look with Our New Chassis

Have you ever felt troublesome seeing nice pre-installed fans in the chassis and found out they don't come in individual packages?

CT Series Fans allow you to pair up your fans without switching out any pre-installed fans granting freedom to unify your display within your chassis. The new Ceres 500 mid-tower chassis is now available, and more chassis pre-installed with the CT Series fans are on their way!

Detailed Craftsmanship Pushes Through Limits

After numerous research, tests, and modifications, we finally tuned our CT series fan blades to meet our expectations and beyond their limits. These seven fan blade structured fans can provide a 2.23 mm-H₂O air pressure and an airflow of 57.05 CFM while maintaining its noise level at 25.8 db-A, allowing you to enjoy these well-balanced performance fans under a friendly budget.

Less Cable, More Friendly

The new cable-integrated daisy-chain design allows the fans to be directly connected, so it minimizes demands of 4-pin PWM and 3-pin ARGB ports on your motherboard and shortens the cable length between the fans. We've also included two 900mm PWM cables and two 900mm ARGB cables for you to easily manage your cables while assembling your build.

Solid Structure for Better Performance

The new CT Series fan frames are crafted to be steady and robust so the fan won't deform easily. We have also modified the exterior design to allow the fans to fit the chassis or radiator even better, so there won't be gaps for air to slip through.

A little Surprise for Extra Security

CT Series Fans are equipped with four round undetachable anti-vibration rubber pads on each of the fans corners. They are designed to be stable and dampen the fans vibration, allowing the fans to spin at a higher speed under certain noise levels.

Keeping Your Cables in Place

You might have experienced easily detached 5V ARGB cables when you assemble your builds. Worry not; this 5V ARGB Connector Clip can guarantee that the cables are correctly connected and won't get loose in unexpected conditions.

Spectacular Lighting Effects

Featuring 9 addressable LEDs for users to build up spectacular lighting effects through motherboard sync software, providing great coverage of 16.8 million uniformity colors. You can create stunning lighting effects through your motherboard software to customize your ideal lighting effects. The CT Series ARGB Fans now support ASUS, MSI, GIGABYTE, BIostar, and ASRock sync software.

Note: This product requires motherboard sync for ARGB lighting effects

Sync with Motherboard RGB Software

Designed to synchronize with ASUS Aura Sync, GIGABYTE RGB Fusion, MSI Mystic Light Sync, and ASRock Polychrome. It supports motherboards with a 5V addressable RGB header, allowing you to control the lights directly from the software mentioned above without installing any extra lighting software or controllers. For more details, please visit ASUS, GIGABYTE, MSI, and ASRock official websites.

Specifications:

ComX Computers

Product Specification Sheet

© 2023 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	CL-F149-PL12SW-A
P/N	CL-F149-PL12SW-A
FAN DIMENSION	120 x 120 x 25 mm
STARTED VOLTAGE	5 V
RATED CURRENT	0.11 A & 0.31A (one fan)
RATED VOLTAGE	12 V & 5V
POWER INPUT	1.32 W & 1.55W (one fan)
FAN SPEED	PWM 500~2000 R.P.M
MAX. AIR PRESSURE	2.23 mm-H2O
MAX AIR FLOW	57.05 CFM
NOISE LEVEL	25.8 dB-A
BEARING TYPE	Hydraulic Bearing
LIFE EXPECTATION	40,000 hrs, 25 degreesC
CONNECTOR	4 PIN PWM
	3 PIN-ARGB
OTHER	PWM Cable x 2
	ARGB Cable x2
	ARGB Cable Clip x 2

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/CL-F149-PL12SW-A-Thermaltake-CT120-ARGB-Sync-PC-cooling-Buy-p-286422.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-25 17:59:55.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.