DS-2CD2T26G2-ISU/SL4MM

Hikvision DS-2CD2T26G2-ISU/SL(D) 2 MP AcuSense Strobe Light and Audible Warning Fixed Bullet Network Camera with 4mm lens

Product Overview

Hikvision DS-2CD2T26G2-ISU/SL(D) 2 MP AcuSense Strobe Light and Audible Warning Fixed Bullet Network Camera with 4mm lens. A reliable 2 MP AcuSense bullet camera delivering sharp Full HD imaging with intelligent human/vehicle detection. Built-in strobe and alarm improve deterrence. Rugged weatherproof build, efficient compression, versatile power options-perfect for South African outdoor surveillance needs.







Specifications

Overview Summary

Hikvision DS-2CD2T26G2-ISU/SL4MM 2MP AcuSense Bullet Camera

This Hikvision 2 MP AcuSense bullet camera offers sharp Full HD video, human/vehicle classification to reduce false alarms, plus built-in strobe light and audible warning for active deterrence. Optimised for both day and night surveillance, it delivers reliable performance in challenging environments.

Performance tier: Professional surveillance

Uses:perimeter security, property monitoring, intrusion detection, night surveillance

Description

The DS-2CD2T26G2-ISU/SL4MM is a high-performance bullet camera designed for robust perimeter surveillance. Its 2 MP Full HD sensor and advanced DarkFighter technology ensure clear, colour-accurate footage even in near-darkness. The deep learning-based AcuSense feature intelligently filters out non-human or vehicle motion, offering higher alarm accuracy. In addition, the built-in strobe and audible alert act as proactive deterrents against intruders.

Equipped with efficient video codecs including H.265+ and support for multiple streams, this camera balances storage and network load effectively. Its rugged IP67-rated metal housing makes it ideal for outdoor use in harsh South African weather. Flexible power options-either via PoE or 12 V DC-and comprehensive network storage support make installation and operation seamless.

Features

- 2 MP Full HD resolution for clear, detailed imaging
- Power-by-DarkFighter low-light performance for effective night vision
- 120 dB true WDR (Wide Dynamic Range) ensures clear imaging in high-contrast lighting
- AcuSense deep learning human/vehicle classification drastically reduces false alarms
- Built-in strobe light and audible alarm for active intrusion deterrence
- IR illumination up to 60 m with smart supplement light support
- IP67 weatherproof housing for reliable outdoor operation
- Supports H.265+, H.265, H.264+, H.264, MJPEG for efficient video compression
- Two-way audio with built-in microphone and speaker for real-time security interaction

What's in the Box

- DS-2CD2T26G2-ISU/SL4MM Network Bullet Camera
- Mounting screws and wall anchors
- Water-resistant cap for cable entry
- Quick installation guide
- Warranty card

Specifications:

© 2025 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	DS-2CD2T26G2-ISU/SL4MM
Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Max. Resolution	1920 x 1080
Min. Illumination	Color: 0.002 Lux @ (F1.4, AGC ON), B/W: 0 Lux with IR
Shutter Time	1/3 s to 1/100, 000 s
Day & Night	IR cut filter
Angle Adjustment	Pan: 0degrees to 360degrees, tilt: 0degrees to 90degrees, rotate: 0degrees to 360degrees
Lens	

Lens Type	Fixed focal lens, 4 mm optional
Focal Length & FOV	4 mm, horizontal FOV: 86degrees, vertical FOV: 47degrees, diagonal FOV: 102degrees
Lens Mount	M12
Iris Type	Fixed
Aperture	F1.4
Depth of Field	4 mm: 1.2 m to ?
DORI	
DORI	4 mm: D: 53 m, O: 21 m, R: 11 m, I: 5 m
Illuminator	
Supplement Light Type	IR
Supplement Light Range	Up to 60 m
Smart Supplement Light	Yes
IR Wavelength	850 nm
Video	
Main Stream	50 Hz: 25 fps (1920 x 1080, 1280 x 720)
	60 Hz: 30 fps (1920 x 1080, 1280 x 720)
Sub-Stream	50 Hz: 25 fps (640 x 480, 640 x 360)
	60 Hz: 30 fps (640 x 480, 640 x 360)
Third Stream	50 Hz: 10 fps (1920 x 1080, 1280 x 720, 640 x 480, 640 x 360)
	60 Hz: 10 fps (1920 x 1080, 1280 x 720, 640 x 480, 640 x 360)
	*Third stream is supported under certain settings.
Video Compression	Main stream: H.265/H.264/H.264+/H.265+
	Sub-stream: H.265/H.264/MJPEG
	Third stream: H.265/H.264
	*Third stream is supported under certain settings.
Video Bit Rate	32 Kbps to 8 Mbps
H.264 Type	Baseline Profile, Main Profile, High Profile
H.265 Type	Main Profile
Bit Rate Control	CBR
Scalable Video Coding (SVC)	H.264 and H.265 encoding
Region of Interest (ROI)	1 fixed region(s) for main stream and sub-stream
Audio	
Audio Type	Mono sound
Audio Compression	G.711/G.722.1/G.726/MP2L2/PCM/MP3/AAC-LC
Audio Bit Rate	64 Kbps (G.711ulaw/G.711alaw)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 192 Kbps (MP2L2)/8 to 320 Kbps (MP3)/16 to 64 Kbps (AAC-LC)
Audio Sampling Rate	8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz

Environment Noise Filtering	Yes
Network	
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, WebSocket, WebSockets
Simultaneous Live View	Up to 6 channels
API	Open Network Video Interface (Profile S, Profile G, Profile T), ISAPI, SDK
Smooth Streaming	Yes
User/Host	Up to 32 users
	3 user levels: administrator, operator, and user
Security	Password protection, complicated password, HTTPS encryption, 802.1X authentication (EAP-TLS, EAP-LEAP, EAP-MD5), watermark, IP address filter, basic and digest authentication for HTTP/HTTPS, WSSE and digest authentication for Open Network Video Interface, RTP/RTSP over HTTPS, control timeout settings, security audit log, TLS 1.3, host authentication (MAC address)
Network Storage	NAS (NFS, SMB/CIFS), Auto Network Replenishment (ANR)
	Together with high-end Hikvision memory card, memory card encryption and health detection are supported.
Client	iVMS-4200, Hik-Connect, Hik-Central
Web Browser	Plug-in required live view: IE 10+, IE 11,
	Plug-in free live view: Chrome 57.0+, Firefox 52.0+
	Local service: Chrome 57.0+, Firefox 52.0+
Image	
Image Parameters Switch	Yes
Image Settings	Rotate mode, saturation, brightness, contrast, sharpness, gain, white balance, adjustable by client software or web browser
Day/Night Switch	Day, Night, Auto, Schedule
Wide Dynamic Range (WDR)	120 dB
SNR	>= 52 dB
Image Enhancement	BLC, HLC, 3D DNR
Privacy Mask	Yes
Interface	
Ethernet Interface	1 RJ45 10 M/100 M self-adaptive Ethernet port
On-Board Storage	Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 256 GB
Built-in Speaker	Max. power consumption: 2 W, max. sound pressure level: 10 cm: 97 dB.
Built-in Microphone	Yes
Alarm	1 input(s), 1 output(s) (max. 24 VDC/24 VAC, 1 A)

Audio	1 input (line in), two-core terminal block, max. input amplitude: 3.3 Vpp, input impedance: 4.7 Kohm, interface type: non-equilibrium
	1 output (line out), two-core terminal block, max. output amplitude: 3.3 Vpp, output impedance: 100 ohm, interface type: non-equilibrium
Reset Key	Yes
Event	
Basic Event	Motion detection (support alarm triggering by specified target types (human and vehicle)), video tampering alarm, exception
Smart Event	Line crossing detection, intrusion detection, region entrance detection, region exiting detection (support alarm triggered by specified target types (human and vehicle))
	Scene change detection
Linkage	Upload to FTP/NAS/memory card, notify surveillance center, send email, trigger alarm output, trigger recording, trigger capture, audible warning, white light flashing
Deep Learning Function	
Face Capture	Yes
General	
Power	12 VDC +/- 25%, 0.88 A, max. 10.6 W, Ø5.5 mm coaxial power plug, reverse polarity protection
	PoE: 802.3af, Class 3, 36 V to 57 V, 0.34 A to 0.21 A, max. 12 W
Material	Front cover: metal, back cover: metal
Dimension	289 mm x 93.1 mm x 91.2 mm (11.4" x 3.7" x 3.6")
Package Dimension	386 mm x 156 mm x 155 mm (15.2" x 6.1" x 6.1")
Weight	Approx. 1195 g (2.6 lb.)
With Package Weight	Approx. 1704 g (3.8 lb.)
Storage Conditions	-30 degreesC to 60 degreesC (-22 degreesF to 140 degreesF). Humidity 95% or less (non-condensing)
Startup and Operating Conditions	-30 degreesC to 60 degreesC (-22 degreesF to 140 degreesF). Humidity 95% or less (non-condensing)
Language	33 languages: English, Russian, Estonian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Turkish, Korean, Traditional Chinese, Thai, Vietnamese, Japanese, Latvian, Lithuanian, Portuguese (Brazil), Ukrainian
General Function	Heartbeat, anti-flicker, mirror, flash log, password reset via email, pixel counter
Flashing Light	Yes
Approval	
EMC	FCC: 47 CFR Part 15, Subpart B
	CE-EMC: EN 55032: 2015, EN 61000-3-2:2019, EN 61000-3-3: 2013+A1:2019, EN 50130-4: 2011 +A1: 2014,
	KC: KN32: 2015, KN35: 2015

Safety	UL: UL 62368-1
	CB: IEC 62368-1: 2014+A11
	CE-LVD: EN 62368-1: 2014/A11: 2017,
	LOA: IEC/EN 60950-1
Environment	CE-RoHS: 2011/65/EU
	WEEE: 2012/19/EU
	Reach: Regulation (EC) No 1907/2006
Protection	IP67: IEC 60529-2013

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/DS-2CD2T26G2-ISU-SL4MM-Hikvision-DS-2CD2T26G2-ISU-SL-D-2-MP-AcuSense-Strobe-Light-p-327543.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-22 07:31:58.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.