

DS-3T1512HP-SI-8P4F

Hikvision DS-3T1512HP-SI-8P4F 8 Port Gigabit Smart Managed Industrial POE Switch

Product Overview

Hikvision DS-3T1512HP-SI-8P4F L2, Smart Managed, 8 Gigabit PoE ports, 4 Gigabit SFP ports, 802.3af/at/bt, port 1-4 support Hi-PoE 90w, power budget 300w(based on power supply, power supply unit not included), -40 degreesC to 75 degreesC, HPP Cloud managed, VLAN, STP/RSTP /ERPS, DHCP



Specifications

Features:

- 8 x Gigabit PoE RJ45 ports,4 x Gigabit SFP fiber optical ports
- Support 802.1Q VLAN
- Support 802.3bt Hi-PoE, Max. 90W for one port
- Support STP/RSTP/ERPS Loop prevention, storm control
- Support cable detection to locate failure
- Support SNMP, QoS, DHCP snooping
- 6 kV Surge Protection
- Wider Temperature (-40 degreesC to 75 degreesC) Design
- Up to 300 m Long-range Transmission

Specifications:

© 2024 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.	
Specifications	
Product Code	DS-3T1512HP-SI-8P4F
General	
Shell	Metal material, IP40
Net Weight	0.84 kg (1.85 lb)
Gross Weight	1.16 kg (2.56 lb)

ComX Computers

Product Specification Sheet

Dimensions (W x H x D)	155.00 mm x 46.00 mm x 130.00 mm (6.10" x 1.81" x 5.12")
Operating Temperature	-40 degreesC to 75 degreesC (-40 degreesF to 167 degreesF)
Storage Temperature	-40 degreesC to 85 degreesC (-40 degreesF to 185 degreesF)
Operating Humidity	5% to 95% (no condensation)
Relative Humidity	5% to 95% (no condensation)
Power Supply	48~57 V DC, 7.5 A
	52 V~57 V recommended input voltage to ensure stable power supply.
	Support dual power inputs and hot backup.
Installation Mode	Desk-Mounted, Rail
Max. Power Consumption	307 W
Power Consumption in Idle	7 W
Surge Protection	6 KV
Network Parameters	
Ports	8 x Gigabit PoE port, 4 x Gigabit fiber optical port
MAC Address Table	8 K
Switching Capacity	Whole-Device Performance: 56 Gbps
	Port Performance: 24 Gbps
Packet Forwarding Rate	Whole-Device Performance: 41.66 Mpps
	Port Performance: 17.86 Mpps
Internal Cache	4.1 Mbits
PoE Power Supply	
PoE Standard	Ports 1 to 4: IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt
	Ports 5 to 8: IEEE 802.3af, IEEE 802.3at
PoE Power Pin	Ports 1 to 4: 8-pin power: 1/2(-), 3/6(+), 4/5(+), 7/8(-)
	Ports 5 to 8: End-span: 1/2(-), 3/6(+)
Max. Port Power	Ports 1 to 4: 90 W
	Ports 5 to 8: 30 W
PoE Port	Hi-PoE: Ports 1 to 4
	PoE: Ports 5 to 8
PoE Power Budget	300 W
Software Function	
Long Range	Ports 1 to 8: up to 300 m.
	Long range performance may vary depend on camera model or cable condition.
Port Isolation	Ports 1 to 8: port isolation mode to improve network security
	Ports in an isolation group cannot communicate with each other, but they can communicate with ports outside the isolation group.
PoE Watchdog	Ports 1 to 8: auto detect and restart the cameras that do not respond.

Link Aggregation	Link aggregation is used to aggregate multiple physical ports to form a logical port for load balancing, bandwidth expansion, and port protection.
	Support static link aggregation.
	Support 8 aggregation groups.
Loop Prevention	Loop prevention is used to prevent the switching network from forming loops, which will seriously affect network communication. Disabled by default.
	Support 802.1D STP.
	Support 802.1w RSTP.
	Support G.8032 ERPS.
QoS	QoS is used to allocate bandwidth to different services so as to provide end-to-end service quality assurance.
	Support port-based priority configuration.
	Support SP, WRR priority schedule mode.
VLAN	VLAN is used for network scale planning and network health improvement.
	Support 802.1Q.
	Configurable VLAN ID from 1-4094.
	Support Trunk, Access port mode.
	Support Max. 4094 VLAN.
HPP	Support one-click activation and remote management via Hik-Partner Pro. Functions supported:
	1. Display the port rate.
	2. Display the port bandwidth utilization rate.
	3. Display the PoE power usage.
	4. Display topology information.
	5. Display the alarm status.
	6. Restart ports and devices.
	7. Enable port long-range mode.
	8. Remotely upgrade the device.
System Maintenance	Support device management via web.
	Support DHCP Client. Enabled by default for dynamic assignment of management IP addresses.
	Support Super IP, which is a fixed IP address (10.180.190.200) for direct access.
	Support management via Hik-Central Pro.
	Support remote management via Hik-Partner Pro.
	Support cable detection. Abnormal open circuits and short circuits as well as network cable length can be detected.
	Supports 802.1ab LLDP for peer device discovery.
	Support SNMP v1/v2c for third-party management platform access.
	Support port mirroring for fault locating.

ComX Computers

Product Specification Sheet

Port Rate-Limiting	Port rate-limiting is used for port bandwidth adjustment to prevent network congestion.
Storm Control	Storm control is used to prevent switch ports from being blocked by broadcast or multicast storms in the LAN, which may affect network communication.
	Support port rate limiting based on broadcast, multicast, and unknown unicast packets.
DHCP Snooping	DHCP Snooping can prevent unauthorized connections to DHCP servers from disrupting the network and affecting normal network communication, and only allow DHCP packets from trusted ports to pass through. Disabled by default.
ACL	Port security strategy.
	Support up to 64 ACL entries.
	Support up to 128 configuration rules under all ACL entries.
IPSG	IPSG can control the security of port access device.
	Support port, MAC, IP binding.
	Support 256 security entries.
Approval	
EMC	CE-EMC (EN 55032: 2015+A11: 2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011+A1: 2014, EN 55035: 2017+A11: 2020), IC (ICES-003: Issue 7:2020), RCM (AS/NZS CISPR 32: 2015)
Safety	CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition)), CE-LVD (EN 62368-1: 2014+A11: 2017)
Chemistry	CE-RoHS (2011/65/EU), WEEE (2012/19/EU), Reach (Regulation (EC) No.1907/2006)

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/DS-3T1512HP-SI-8P4F-Hikvision-DS-3T1512HP-SI-8P4F-8-Buy-p-311598.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-14 02:34:21.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.