ComX Computers
Product Specification Sheet

DS-3WR4G12C

Hikvision DS-3WR4G12C AC1200 4G CAT4 Wireless Router

Product Overview

Hikvision DS-3WR4G12C 4G LTE Wi-Fi Router, Max 4G speed: DL: 150Mbps; UL: 50Mbps Wi-Fi speed: 2.4GHz: 300Mbps; 5GHz:867Mbps 4G Cartgory LTE CAT.4 Support FDD LTE, TDD-LTE, WCDMA





Specifications

Features:

- AC1200 Dual-band Wi-Fi
- 4G Boost Faster Speed
- Instantly Access a Mobile Network With a SIM Card

Specifications:

© 2024 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	DS-3WR4G12C
General	
Product Dimensions (W x H x D)	233.9mmx151.4mmx40.3mm
Package Dimensions (W x H x D)	405mmx307mmx80mm
Net Weight	0.560kg

Packing List	4G LTE Router x 1
	Power Adapter x 1
	Detachable Antenna x 2
	Ethernet Cable x 1
	SIM Card Adapter x 1
	Quick Start Guide x 1
	Regulatory Compliance and Safety Information x 1
Packing Method	Single pack
Working Temperature	0 degreesC to 40 degreesC (32 degreesF to 104 degreesF)
Working Humidity	10% to 90% RH non-condensing
Storage Temperature	-40 degreesC to 70 degreesC (-40 degreesF to 158 degreesF)
Storage Humidity	5% to 90% RH non-condensing
Installation Mode	Desktop installation
Max. Power Consumption	<= 9 W
Gross Weight	0.620 kg
Wireless Parameter	
Max. Transmission Rate of Air Interface	<= 1167 Mbps
	2.4 GHz: 300 Mbps
	5 GHz: 867 Mbps
Wireless Standard	IEEE 802.11/a/n/ac wave 2 @5GHz, IEEE 802.11b/g/n @2.4GHz
Working Frequency Band	2.4 GHz, 5 GHz
Transmitting Power	16dBm @ 2.4G-mcs7, 17dBm @ 5G-mcs9
Wireless Performance	2*2 MIMO supported
Receiving Sensitivity	-58 +/- 2 dB@AC80 -MCS9
	-84 +/- 2 dB@AC80 -MCS0
Antenna	2 high gain antennas
Network Type	LTE CAT.4
Mobile Standards	FDD LTE, TDD-LTE, WCDMA
Mobile Bands	4G FDD LTE: B1/B3/B7/B8/B20/B28AB, 4G TDD-LTE: B38/B40/B41, 3G WCDMA: B1/B8
4G Speed	DL: 150 Mbps, Upload: 50 Mbps
Hardware Parameter	
Network Interface	2 x RJ45, 10/100 Mbps auto-negotiation
LED Indicator	power LED*1, internet LED*1, WiFi LED*1, RJ45 LED*1, LTE LED*3
Reset	Reset button*1
Power Supply Method	9 VDC, 1 A power adapter power supply
Power Specifications	9 VDC, 1 A
Software Function	

Application Function	3G/4G Route Mode, Wireless Router Mode, and AP Mode supported
	DHCP Server supported
	Guest Network Configuration supported
	Signal Adjustment supported
	WiFi Schedule supported
Security Mode	WPA-PSK, WPA2-PSK, WPA and WPA2 supported
Security Mechanism	Hide SSID
Management Method	Web
Upgrade	Web
System Log	System log

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/DS-3WR4G12C-Hikvision-DS-3WR4G12C-AC1200-4G-CAT4-Wireless-Router-p-311703.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-07 05:10:58.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.