

DS-D6065UN-DP

Hikvision DS-D6065UN-DP 65" 4K 3840x2160 Slim Digital Signage Display - 24/7, HDMI, DP

Product Overview

Hikvision DS-D6065UN-DP 65" 4K 3840x2160 Slim Digital Signage Display, E-led backlight, 178 degree viewing angle, 500nits brightness, 5000:1 contrast ratio, 8ms response time, 85% NTSC Colour Gamut, 7 x 24 H reliability, 60Hz Refresh Rate, Android 13 Operating system, 4GB Memory, 32GB eMMC Built-In storage, 3x HDMI, 1x DisplayPort, 1x line out, 20 W x 2 Speaker, 1x RJ45, Wi-Fi, 1x RS232 in, 1x RS232 out, 1x USB 2.0, 1x USB 3.0, 1x Bluetooth 5.0



Specifications

Overview Summary:

The Hikvision DS-D6065UN-DP 65-inch 4K Digital Signage Display is designed for high-impact commercial environments requiring reliable, continuous operation. With ultra-clear 3840 x 2160 resolution, 500 nits brightness, and wide 178degrees viewing angles, it delivers sharp, consistent visuals for professional communication and advertising.

Powered by Android 13 with built-in 4GB memory and 32GB storage, this display supports flexible content scheduling, remote management, and a wide range of media formats. Its slim industrial design and 24/7 reliability make it suitable for demanding business environments where performance and uptime are critical. Buy now or shop now in South Africa to upgrade your digital signage infrastructure.

Performance tier:Enterprise-grade Commercial Display

Uses:Retail advertising displays, corporate communications, hospitality digital signage, menu boards, information kiosks, wayfinding systems

Overview:

65-inch 4K Slim Digital Signage Display for Business Environments

The Hikvision DS-D6065UN-DP is a 65-inch 4K ultra high-definition digital signage display designed for professional environments that require clear, reliable, and continuous visual communication. Built with a slim profile and industrial-grade panel technology, it delivers consistent performance for retail, corporate, hospitality, and public information systems where impactful content delivery is essential.

Description:

The DS-D6065UN-DP combines a high-brightness 4K display with an integrated Android 13 system to support flexible content playback and remote management. It is engineered for continuous 7 x 24 hour operation, making it suitable for demanding commercial deployments. With advanced image enhancement processing, wide viewing angles, and strong connectivity options, it supports both static and dynamic content formats including video, images, scrolling text, live feeds, and interactive signage layouts.

Features:**Designed for High Impact Visual Communication**

This digital signage unit is built to support modern digital communication needs with a focus on clarity, flexibility, and centralized control. The slim frame and all-in-one design make it suitable for both wall-mounted vertical and horizontal installations.

Key functional advantages include:

- Support for multiple content formats including video, images, PDFs, webpages, and live video feeds
- Scheduled playback modes such as daily, weekly, loop, and custom scheduling
- Centralized remote management for single or multiple displays
- Multi-level user and permission control for structured content administration
- Secure content handling with encryption and controlled release validation

The product SKU DS-D6065UN-DP is positioned within Hikvision's professional signage range for scalable deployment across business networks.

Display Performance and Image Quality

The 65-inch panel is engineered for sharp visuals and consistent color reproduction, making it suitable for environments with varying lighting conditions.

Display characteristics include:

- Resolution: 3840 x 2160 (4K UHD)
- Brightness: 500 cd/m2 for strong visibility
- Contrast ratio: 5000:1 for deep image definition
- Viewing angle: 178 degree horizontal and vertical
- Color gamut: 85% NTSC with 10-bit processing (8-bit + FRC)
- Response time: 8 ms for smooth motion display
- Refresh rate: 60 Hz
- Backlight: E-LED technology for stable illumination

The panel also features industrial A+ grade display quality with image enhancement processing for improved clarity and color consistency.

Built-in Android System and Processing Capability

The integrated Android 13 platform allows the display to operate independently without external media players.

System specifications:

- Processor: Cortex-A55 quad-core at 1.92 GHz
- Memory: 4 GB RAM
- Internal storage: 32 GB eMMC
- Supported video formats: AV1, H.265, H.264, VP9, MPEG variants, MJPEG
- Audio support: AAC, FLAC, MP3, OGG, ALAC and more

ComX Computers

Product Specification Sheet

This built-in system enables direct content scheduling, playback, and application-based signage control.

Connectivity and Integration Options

The DS-D6065UN-DP is equipped with a wide range of input and output interfaces to support professional AV integration.

Connectivity includes:

- 3 x HDMI inputs
- 1 x DisplayPort
- 1 x line out audio
- 2 x built-in speakers (10W each, 6 ohm)
- RJ45 Ethernet port
- Wi-Fi support (2.4G and 5G, WiFi 6 compatible standards)
- RS232 in and RS232 out ports
- USB 2.0 and USB 3.0 ports
- Bluetooth 5.0 support

These options allow seamless integration into both standalone and networked signage systems.

Content Management and Remote Control Capabilities

The system supports centralized control across multiple displays, making it suitable for large-scale deployments.

Management capabilities include:

- Remote scheduling of power on and off cycles
- Adjustable brightness and volume scheduling
- Remote program deployment and updates
- Screenshot preview for real-time monitoring
- USB-based local content updates
- Structured user permission levels with up to 5 organizational layers

Security is reinforced through encrypted data storage and transmission, as well as controlled content approval workflows.

Installation and Physical Design

Designed with a slim industrial form factor, the display is optimized for professional mounting environments.

Physical details:

- Screen size: 65 inch
- Active display area: 1428.48 mm x 803.52 mm
- Dimensions without backboard: 1459.2 mm x 837.1 mm x 38.9 mm
- Dimensions with backboard: 1459.2 mm x 837.1 mm x 68.9 mm
- Net weight: 25.3 kg
- Mounting: wall installation (horizontal or vertical support)

The narrow frame design supports a clean, modern installation aesthetic suitable for commercial interiors.

Operational Conditions and Reliability

Built for continuous operation, the DS-D6065UN-DP is suitable for environments requiring long-duration display uptime.

Operating parameters:

- Working temperature: 0 C to 40 C
- Storage temperature: -20 C to 60 C

ComX Computers

Product Specification Sheet

- Humidity tolerance: up to 80% operating RH
- Designed for 7 x 24 hour continuous usage
- Power consumption: 90W typical, 150W maximum, standby under 0.5W

This ensures stable performance in retail, corporate, transport, and public signage environments.

Included Accessories and Package Contents

The package includes all essential components required for deployment:

- Digital signage display unit
- Wall-mounted backboard with mounting bolts
- Power cable (Europe standard)
- RS232 cable
- Remote control
- User manual and quick start guide
- Compliance and regulatory documentation
- Branding and energy efficiency labels

Specifications:

© 2026 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.	
Specifications	
Product Code	DS-D6065UN-DP
Product Model	
Product Model	DS-D6065UN-DP
Display	
Screen Size	65 inch
Color Temperature	10000K
Resolution	3840 x 2160
Active Display Area	1428.48 (H) mm x 803.52 (V) mm
Pixel Pitch	0.124(H) mm x 0.372 (V) mm
Backlight	E-LED
Viewing Angle	178degrees(H)/178degrees(V)
Brightness	500 cd/m²
Contrast Ratio	5000:1
Color Depth	10 bit (8 bit + FRC)
Response Time	8 ms
Color Gamut	85% NTSC
Reliability	7 x 24 h
Refresh Rate	60 Hz
Haze	25%

ComX Computers

Product Specification Sheet

Built-in System	
Operation System	Android 13
Processor	Cortex-A55, 4-core, main frequency 1.92 GHz
Memory	4 GB
Built-in Storage	32 GB EMMC
Video Format	AV1, H.265, H.264/AVC, MVC, VP9, AVS2, MPEG4, MPEG2, MPEG1, VP8, MJPEG, H263
Audio Format	MPEG, APE, FLAC, AAC, OGG, AIF, AIFF, ALAW, ALAC
Interface	
Video & Audio Input	HDMI x 3, DP x 1
Video & Audio Output	LINE OUT x 1, speaker (6ohm 10 W) x 2
Network Interface	RJ45 x 1, Wi-Fi (2.4G/5G, 802.11 a/b/g/n/ac/ax) x 1, RS232 in x 1, RS232 out x 1
Data Transmission Interface	USB 2.0 x 1, USB 3.0 x 1, BT 5.0 x 1
Power	
Input Voltage	100 to 240 VAC, 50/60 Hz
Standby Consumption	<= 0.5 W
Power Consumption	90W(typ), 150W(max)
Working Environment	
Working Temperature	0 degreesC to 40 degreesC (32 degreesF to 104 degreesF)
Working Humidity	10% to 80% RH (Condensation)
Storage Temperature	-20 degreesC to 60 degreesC (-4 degreesF to 140 degreesF)
Storage Humidity	10% to 90% RH (Condensation)
General	
Material Type	DAT, VOB, TS, AVI, MKV, MOV, 3GP, FLV, ASF, MP3, WMA, OGG, JPG, BMP, PNG
Mounting Type	Wall mounting (horizontally or vertically)
Product Dimensions (W x H x D)	1459.2mm x 837.1mm x 38.9 mm (without wall-mounted backboard)
	1459.2mm x 837.1mm x 68.9 mm (with wall-mounted backboard)
Package Dimensions (W x H x D)	1640 mm x 990 mm x 164 mm
Net Weight	25.3 kg
Gross Weight	35.2 kg
Packing List	Digital signage x 1, wall-mounted backboard (including package of mounting bolts) x 1, power cord for europe x 1, RS232 cable x 1, remote control x 1, user manual x 1 , quick start guide x 1, Regulatory Compliance and Safety Information x 1, logo stickers x 1, energy efficiency label x 1

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/DS-D6065UN-DP-Hikvision-DS-D6065UN-DP-65-4K-3840x2160-Buy-p-337125.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-12 18:17:58.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.