

# DS-K4H258S

Hikvision single-door Magnetic lock

## Product Overview

Hikvision single-door Magnetic lock, 280kg linear thrust, 12 VDC, 340mA Power draw, Current interruption unlock Method



## Specifications

### Overview:

#### DS-K4H258 - Value Series Magnetic Lock

- Magnetic lock supports static linear thrust of 280 kg (617 Lbs)
- Power supply can be 12VDC or 24VDC, (default voltage is 12VDC)
- Suitable for wooden door, glass door, metal door and fireproof door
- LED indicator displays door lock status
- Abrasion-proof materials

### Specifications:

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                       |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------|
| © 2025 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC ( <a href="http://www.comx.co.za">http://www.comx.co.za</a> ), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered. |                                                       |
| Specifications                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                       |
| Product Code                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | DS-K4H258S                                            |
| General                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                       |
| Indicator                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Green (Work Status)                                   |
| Power Supply                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 12 VDC, 340 mAx2                                      |
| Working Temperature                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | -10 degreesC~+55 degreesC (14 degreesF~131 degreesF)  |
| Working Humidity                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 0~95% (Relative Humidity)                             |
| Dimensions                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Lock Body: 238 x 45 x 25 mm (9.4 x 1.8 x 1.0")        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Armature Plate: 182 x 38 x 12.5 mm (7.2 x 1.5 x 0.5)" |
| Weight                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 2.1 kg (4.6 Lbs)                                      |

---

## ComX Computers

### Product Specification Sheet

|                              |                                                                               |
|------------------------------|-------------------------------------------------------------------------------|
| <b>Material</b>              | Shell: hard Anodizing Electroplating Operated                                 |
|                              | Lock Body: eco-friendly Nickel Electroplating Operated                        |
|                              | Armature Plate: eco-friendly Zinc Electroplating Operated                     |
| <b>Thrust</b>                | Max. 280 kg (617 lb)                                                          |
| <b>Door Type</b>             | Single leaf, Double leaf, Wooden Door, Glass Door, Metal Door, Fireproof Door |
| <b>Magnetic Lock/General</b> |                                                                               |
| <b>Unlock Method</b>         | Current Interruption                                                          |
| <b>Surface Temperature</b>   | <= Ambient Temperature +20 degreesC (68 degreesF)                             |

## Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

**Product page:** <https://www.comx-computers.co.za/DS-K4H258S-Hikvision-single-door-Magnetic-lock-Buy-p-321904.php>

---

*Images and specifications are provided for reference and are subject to change without notice. E&OE.*

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

---

PDF generated: 2026-10-17 08:34:12.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.