ComX Computers
Product Specification Sheet

DS-K5671-ZV

Hikvision Face Recognition module for Turnstile

Product Overview

Hikvision Face Recognition module for Turnstile, 7-inch capacitive Touch Screen, 2 MP Resolution camera, 2 Lens, Gigabit Self-Adaptive Wired Network, 1 Network Interface, 1 lock control, 1 door contact Input, 2 alarm Input, 1 alarm Output, 50000 face capacity, 100000 event capacity



Specifications

Overview:

DS-K5671-ZV - Face Recognition Module For Turnstile

- Forced mask wearing alert: If the recognizing face does not wear a mask, the device will prompt a voice reminder. At the same time, the authentication or attendance will be failed
- Face mask wearing alert: If the recognizing face does not wear a mask, the device will prompt a voice reminder. At the same time, the authentication or attendance is valid
- Face recognition terminal for turnstile
- Built-in IO output or Wiegand output to communicate with the third-party turnstile
- 7 inch LCD Touch Screen, 2 M camera
- Max. 50,000 faces, and Max. 100,000 events
- Face recognition distance: 0.3 m to 3 m; Face recognition duration < 0.2 s/User; Accuracy rate >= 99%
- TCP/IP, Wi-Fi communication
- Remote live view via RTSP protocol
- IP65

Specifications:

© 2023 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	DS-K5671-ZV
Display	

Screen Size	7-inch
Operation Method	Capacitive touch screen
Video	
FOV	HFOV= 87 degrees, VFOV= 46 degrees
Resolution	2 MP
Lens	2
Network	
Communication Protocol	TCP/IP, SIP, RTSP, HikCentral Pro OpenAPI, Hik-ProConnect OpenAPI
Wired Network	10 M/100 M/1000 M self-adaptive
Wi-Fi	Support
Interface	
Network Interface	1
Lock Control	1
Door Contact Input	1
Alarm Input	2
Alarm Output	1
Capacity	
Face Capacity	50000
Event Capacity	100000
Authentication	
Face Recognition Duration	< 0.2 s per person
Face Recognition Accuracy Rate	>= 99%
Face Recognition Distance	0.3 to 3 m
Function	
Audio Prompt	Support
Time Synchronization	Support
General	
Power Supply	12 VDC/ 2 A
Working Temperature	-30 degreesC to 60 degreesC(-22 degreesF to 140 degreesF)
Working Humidity	10~90% (No condensing)
Protective Level	IP65
Language	English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil)
Platform	Hik-ProConnect and HikCentral Professional

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/DS-K5671-ZV-Hikvision-Face-Recognition-module-for-Turnstile-p-282536.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-11 03:46:03.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.