DS-PWA96-Kit-WE

Hikvision DS-PWA96-Kit-WE Panel Kit Middle Level

Product Overview

Hikvision DS-PWA96-Kit-WE Panel Kit Middle Level, Component: DS-PWA96-M-WE * 1, DS-PKF1-WE * 1, DS-PDP15P-WG2-WE * 1, DS-PDMC-EG2-WE * 1



Specifications

Specifications:

© 2021 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	DS-PWA96-Kit-WE
Software features	
Tag	48
Area	32
Zones	96 (up to 48 PIRCAMs)
Onboard video clips	4
Installer	1
User	46
Admin	1
Voice Prompt	Supported
Loudspeaker built in	Supported
Tag reader built in	Supported
Memory Log stored	5000
Programming tools	Hik-Connect/Hik-ProConnect/Web Portal/ IVMS4200/ Convergence Cloud

Firmware upgrade	APP/Web Portal
Arm modes	Away/Stay
Automatic Arm/Disarm Timers	Supported
Forced Arming with Open Zones	Supported
Diagnostics via the APP or Web	Supported
ARC protocol	SIA DC09(SIA level 2, Contact ID), ISUP, ISAPI (SDK)
	Hik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685)
	Supports video verification and remote control
User APP for operating	Supported
Installer APP for programming	Supported
Web server for maintenance (offline configuration)	Supported
Hardware features	
RS232 output	Supported
SIM slot	Dual
RF transmission	
Two-way Wireless Communication	Support
RF Frequency	868Mhz
Wireless Security	Frequency Hoping 128 AES Encryption
3/4G on board	Supported
Electrical characteristics	
Power supply	Built in power supply
Battery type	Built in on board Battery Li
Battery life span	12 hours
Wireless transmission	
Wired network	Supported
Wi-Fi Standard	Supported
Display	
LEDs Status	Arm/Disarm, Alarm, Tamper, Fault, Cloud, Power
General	
Operation temperature	-10 degreesC to +55 degreesC
Shell material	Plastic
Dimension(WxHxD)	170.0 mm (6.7") x 170.0 (6.7") mm x 38.6 mm (1.5")
	557.5 g(19.7 oz)
Color	white
Device management	
Keyfob	48

Wireless sounder	6
Keypad	8 (Including Tag reader)
Wireless Repeater	4
PIR Cam	Supported

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/DS-PWA96-Kit-WE-Hikvision-DS-PWA96-Kit-WE-Panel-Kit-Middle-Level-p-251042.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-08 08:10:48.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.