

DS6100C

Microworld 2D Barcode handheld Scanner USB

Product Overview

Microworld DS6100C 2D Barcode handheld Scanner USB, Red light LED light source, 640 x 480 Resolution, 4mil Resolution, 10mm-500mm depth of Field



Specifications

Overview:

DS6100 is a high-performance 2D barcode scanner with leading CMOS image recognition technology

- It can easily read the paper, goods, screen and other media barcodes
- Widely used in manufacturing, warehouse, logistics, health care, retail chain
- Mobile payment, express delivery, inventory management, food traceability, asset inventory, etc

Features:

- Ergonomic design, comfortable using, cost-effective.
- Read all mainstream 1D 2D barcodes in the market easily. (4mil)
- Interface: USB.
- Support multiple languages and systems
- Support USB barcode information transmission. (languages customization)
- Widely used in supermarket, warehouse, mobile payment, chain stores.

Specifications:

© 2021 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	DS6100C
Physical Parameter	
Weight	110g(without cable)
Dimension	L150mm x W70mm x H95mm

ComX Computers

Product Specification Sheet

Interface Type	USB
Communication Way	USB(USB-KBW, USB-COM)
Power Supply	DC 5V@130mA(work)
Performance	
Scan type	CMOS
Light source	Red light LED 625+/-10nm(aim), 5600K LEDs(lighting)
CPU	32-bit
Resolution	640 x 480
Resolution	4mil/0.1mm(PCS90%, Code 39)
Scan Tolerance	10CM/S
Depth of Field	10mm-500mm
Scan Mode	Manual, Continuous, Auto sense
Scan Angle	Roll 360, Pitch+/-60, Skew+/-60 (PCS90%, Code 39, 10mil/0.25mm)
Print Contrast Signal	25%
Ambient Light	Dark, indoor natural light
Symbolologies	1D:UPC-A, UPC-E, EAN-8, EAN-13, Code 128, GS1-128, Code 39
	2D: QR Code, PDF417, Data Matrix, etc
Environmental	
Operating temperature	10 to 50
Storage temperature	30 to 60
Humidity	5% to 5% (non-condensing)
Drop Height	1.5m
Transport Vibration Test	10H @ 125RPM
Depth Of Field	
4MIL	30-60mm (PCS90%, Code 39)
13MIL	40-210mm (PCS90%, EAN-13)
20MIL	50-260mm (PCS90%, Code 39)
40MIL	130-500mm (PCS90%, Code 39)
20MIL	100-180mm (PCS90%, QR Code)
Accessories List	
Data Cable	USB, connect the scanner to a host device

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/DS6100C-Microworld-2D-Barcode-handheld-Scanner-USB-Buy-p-261288.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-07 16:18:29.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.