

EAP225-OUTDOOR

TP-Link EAP225-Outdoor AC1200 Wireless MU-MIMO Gigabit Indoor/Outdoor Access Point

Product Overview

TP-Link EAP225-Outdoor AC1200 Wireless MU-MIMO Gigabit Indoor/Outdoor Access Point



Specifications

Features:

- Durable, weatherproof enclosure for outdoor Wi-Fi applications
- Up to 1200Mbps with 2x2 MIMO technology
- High transmission power and high gain antennas provide a long-range coverage area
- Free Omada Controller software enables administrators easily manage hundreds of EAPs
- Captive portal provides a convenient method for guest authentication
- Facebook Wi-Fi and SMS authentication help to boost your business
- 802.3af/Passive PoE (PoE Adapter Included) compatible and simple mounting design allow for flexible deployment and convenient installation

Gigabit Wi-Fi Speeds with MU-MIMO Technology

EAP225-Outdoor supports simultaneous dual band speed of up to 1200Mbps. Outfitted with the latest 802.11ac Wave 2 MU-MIMO technology, EAP225-Outdoor can communicate with multiple clients at the same time which making it ideal for high density environment.

Excellent Hardware Designs

With special design of its antenna, appearance, power options and installation methods, EAP225-Outdoor can perfectly fit for different scenarios both indoors and outdoors.

Detachable Antennas

EAP225-Outdoor is designed with 2 Omni-directional detachable antennas, which means other antennas can also be attached for your specific demands.

Wi-Fi That Goes the Distance

With high transmission power and high gain omnidirectional antennas, EAP225-Outdoor provides stable wireless coverage at a range up to 200m * at 2.4GHz and 300m * at 5GHz in outdoor settings.

Specially Designed Weatherproof Enclosure for Outdoor Environment

ComX Computers

Product Specification Sheet

Rated as IP65 during Ingress Protection testing, a resilient weatherproof enclosure protects the access points against harsh outdoor condition.

Efficient Centralized Network Management

With Omada Controller software, small and medium-sized businesses can take command of hundreds of indoor and outdoor access points all from a single location. It's network management as it should be - efficient and intuitive.

Specifications:

© 2019 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.	
Specifications	
Product Code	EAP225-OUTDOOR
HARDWARE FEATURES	
Interface	Gigabit Ethernet (RJ-45)Port*1(Support 802.3af PoE and Passive PoE)
Button	Reset
Power Supply	802.3af/A PoE
	24V Passive PoE (4, 5pins; -7, 8pins. PoE Adapter Included)
Power Consumption	10.5W
Dimensions (W x D x H)	8.5 x 1.8 x 1.1in. (215 x 46 x 27 mm)
Antenna	2.4GHz: 2 * 3dBi, 5GHz: 2 * 4dBi
Weatherproof Enclosure	IP65
Mounting	Pole/Wall Mounting (Kits included)
Hardware Watch Dog	Yes
WIRELESS FEATURES	
Wireless Standards	IEEE 802.11a/b/g/n/ac
Frequency	2.4GHz, 5GHz
Signal Rate	802.11ac: 5G:6.5 Mbps to 867Mbps(MCS0-MCS9, NSS = 1 to 2 VHT20/40/80) 2.4G:78Mbps to 300Mbps (MCS8-MCS9 VHT20/40, NSS=1 to 3)
	802.11n: 6.5 Mbps to 300 Mbps (MCS0-MCS15, VHT 20/40)
	802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
	802.11b: 1, 5.5, 11Mbps
	802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps

ComX Computers

Product Specification Sheet

Wireless Functions	Multiple SSIDs(Up to 16 SSIDs, 8 for each band)
	Enable/Disable Wireless Radio
	Automatic Channel Assignment
	Transmit Power Control (Adjust Transmit Power on dBm)
	QoS(WMM)
	MU-MIMO
	Airtime Fairness
	Beamforming
	Band Steering
	Load Balance
	Rate Limit
	Reboot Schedule
	Wireless Schedule
	Wireless Statistics based on SSID/AP/Client
Wireless Security	Captive Portal Authentication
	Access Control
	Wireless Mac Address Filtering
	Wireless Isolation Between Clients
	SSID to VLAN Mapping
	Rogue AP Detection
	802.1X Support
Transmission Power	CE:
	FCC:
MANAGEMENT	
Omada Controller Software	Yes
Email Alerts	Yes
Management MAC Access Control	Yes
System Logging Local/Remote Syslog	Yes
Web-based Management	Yes
L3 Management	Yes
Multi-site Management	Yes
Management VLAN	Yes
OTHERS	
Certification	CE, FCC, RoHS

ComX Computers

Product Specification Sheet

Package Contents	AC1200 Wireless MU-MIMO Gigabit Indoor/Outdoor Access Point
	EAP225-Outdoor
	Power Adapter
	Mounting Kits
	Installation Guide
Environment	Operating Temperature: -30 degreesC~70 degreesC (-22 degreesF~158 degreesF)
	Storage Temperature: -40 degreesC~70 degreesC (-40 degreesF~158 degreesF)
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/EAP225-OUTDOOR-TP-Link-EAP225-Outdoor-AC1200-Wireless-Buy-p-216277.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-11 06:33:07.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.