ComX Computers
Product Specification Sheet

EDX1000H

Eaton E Series DX 1000VA 700Watt On-Line Essential Tower UPS

Product Overview

Eaton E Series DX 1000VA 700Watt On-Line Essential Tower UPS, 7-14min Back-up time



Specifications

Overview:

The E Series DX UPS double-conversion UPS affordably protects mission critical applications from downtime, data loss and corruption. The double-conversion architecture incorporates rectifier and inverter stages to completely isolate the output power from all input anomalies. By adapting to a wide range of input voltages, the E Series DX avoids battery usage during minor power fluctuations, saving its capacity for times when utility power is completely lost.

Features:

- Double conversion topology assures maximum reliability
- Wide input-voltage range appropriate for the harshest electrical environments
- Standard Models for fixed-run time performance
- Tested for generator compatibility
- Automatic bypass for fault-tolerance
- Optional SNMP communications provides remote network-based monitoring

Specifications:

© 2015 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	EDX1000H
General	

Topology	Online double-conversion IGBT with micro-controller
Configuration	Tower
Style Number	EDX1000H
Part Number	EDX1000H
Rating (VA/Watts)	1000VA/700W
Efficiency	>85%
UPS Bypass	In-Built Automatic Relay Bypass
Dimensions (H x W x D, mm)	220 x 145 x 400
Weight (kg)	14
Electrical Input	
Connection	(1) IEC-320-C14
Input Voltage Range	122V to 300V
Nominal Voltage	220V
Voltage Range	208/220/230/240V
Frequency	'50/60Hz, auto-detection
Frequency Range	46Hz - 64Hz
Input Power Factor	> 0.95pf
Input Current Distortion	
Electrical Output	
Voltages	208/220/230/240V
Nominal Voltage	220V
Voltage Range	208/220/230/240V
Output voltage regulation	+/-2%
Output Receptacles	(4) IEC-320-C13
Power Factor	0.7
Output Frequency	50 / 60Hz
Load Crest Factor	3:1
Battery	
Battery Description	Valve Regulated Lead Acid, AGM
Battery Type	3x 12V, 7.2 Ah
Start On Battery	Unit can be started without being connected to AC utility power -- allows for portable power source
Recharge Time	< 5 hours to recover 90 percent of nominal backup
Communications	
User Interface	Led's
LEDs	LED mimic diagram with 4 x LEDs for Utility, Bypass, Inverter & Battery Status
Audible Alarms	Battery Operation Mode, Low Battery, General Fault, Overload, On Bypass

Communication Ports	1 off Intelligent-Slot (Empty), 1 x RS232 DB9 Serial Port
Power Management Software	WINPOWER power management software, included on CD
Environmental & Standards	
Audible Noise	
Operating Temperature	0 degreesC to 40 degreesC
Safety markings	CE
EMC Markings	IEC/EN 62040-2 Category C3
Markings	CE, C–Tick
Data Line Protection	Input / output jacks included for telephone / modem / internet line surge protection
Storage Temperature	0 degreesC to 40 degreesC
Relative Humidity	5 to 95%, no condensation allowed
Altitude	1000m above sea level

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/EDX1000H-Eaton-E-Series-DX-1000VA-700Watt-On-Line-Essential-Tower-UPS-p-116822.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-14 23:02:23.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.