ComX Computers
Product Specification Sheet

ELITE-1200PRO

Mercury Elite 1200 Pro UPS

Product Overview

Elite 1200 Pro UPS, 1200VA, 3x Output Socket, 2x Output Cable, 1x Bypass Socket, SA Power Cord, 220V/50Hz



Specifications

Features:

- Wide input voltage range
- Compatible with generators
- Overload protection
- Short circuit protection
- Built-in AVR
- Battery deep discharge protection & overcharge protection
- Green function (No load cut off)

Specifications:

© 2013 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Product Code	ELITE-1200PRO
Specifications	
Input voltage	220VAC
Input frequency	50Hz
Input phase	Single phase
Input socket	With Fuse
Cold Start (0 to 100% load)	Press the ON/OFF switch
Input range (220V)	140-300
Rating output (VA).	1200VA

Rating output (W).	720W
Waveform	Battery mode(simulated sine wave), AC mode(sine wave)
Power factor	0.6
Rating voltage	220V
Output range	220Vac-7% to +15% in battery mode
Rear Output Socket	4 x Universal - Battery backup
Transfer time	TYPICAL4-8ms
Communication Interface	optional RS232/RJ11
Rating frequency	50Hz
Line-mode	Synchronize with the Utility
Battery mode	50 Hz+/-1Hz
Line Mode	FUSE& firmware protection
Battery Mode	Software protection controlled by firmware
Line Mode	110%+/-5%; Go to fault mode after 5 minutes, 120%+/-5%; Go to fault mode immediately.
Battery Mode	110%+/-5%; Shutdown after 5 seconds, 120%+/-5%, Shutdown immediately
Rating	2 X 12V/7.5AH (Actual rating 7AH)
Backup time - Typical	20 to 30 mins (depending on load)
Charge current	About 1A at normal mode.
Over charge protection	29V+/-0.2V stop charging, 27.4+/-0.2V recharge
Weight	8.6+/-0.3 Kg
Dimensions per unit packaging	395x205x258mm
Packsize per Master carton	2
Dimensions per Master carton	410x430x273mm

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: https://www.comx-computers.co.za/ELITE-1200PRO-Mercury-Elite-1200-Pro-UPS-p-64868.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-09 07:02:45.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.