ComX Computers
Product Specification Sheet

ELITE-2000PRO

Mercury Elite 2000 Pro UPS

Product Overview

Elite 2000 Pro UPS, 2000VA, 3x Output Socket, 3x Output Cable, 1x Bypass Socket, SA Power Cord, 220V/50Hz



Specifications

Features:

- Wide input voltage range
- Compatible with generators
- Overload protection
- Short circuit protection
- Built-in AVR
- Battery deep discharge protection & overcharge protection

Specifications:

© 2013 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Product Code	ELITE-2000PRO
Specifications	
Rating input voltage	2000 VA / 1200 W
Rating input frequency	60/50Hz (auto sensing)
Input phase	Single phase
Input socket	With Fuse
Cold Start (0 to 100% load)	Press the ON/OFF Switch
Input Range	(220V) 140-300
Rating output(VA)	2000
Rating output (W)	1200

Rating output (W)	1200
Power factor	0.6
Rating output voltage (V)	220
Waveform	Battery mode (simulated sine wave)
	AC mode(sine wave)
AC Voltage Regulation	+/-10% (Battery mode)
Rear output socket	4 x Universal - Battery backup
Waveform	Simulated Sine Wave (Battery mode)
Line Mode	Synchronize with the utility
Rating frequency	60Hz or 50 Hz +/- 1 Hz
Battery Mode	Yellow flashing
Short circuit protection Line Mode	Fuse & Firmware protection
Short circuit protection Battery Mode	Firmware Protection
Overload protection Line Mode	110%+/-5%; Go to fault mode Line Mode after 5 minutes, 120%+/-5%; Go to fault mode immediately.
Overload protection Battery Mode	110%+/-5%; Shutdown after 5 seconds, 120%+/-5%, Shutdown immediately
Indicators AC mode	Green Lighting
Indicators Battery Mode	Yellow Flashing
Indicators Fault	Red Lighting
Alarm Battery Mode	Sounding every 10 Seconds
Alarm Low Battery	Sounding every Second
Alarm Overload	Sounding every 0.5 second
Alarm Fault	Continuously sounding
Full Protection	Overload, discharge, and
	Overcharge protection
Transfer Time	Typical 2-6ms, 10ms max.
Transfer Time	Typical 2-6ms, 10ms max.
Communication Interface	Optional RS232/RJ11
Battery and runtime Rating	2 X 12V/9AH
Recharge time - Typical	6-8 hours recover to 90% capacity
Charge current	About 1A at normal mode.
Dimension, D X W X H (mm)	390 x 125 x 225
Net Weight (kgs)	12.7KGS
Humidity	0-90 % RH @ 0- 40 degreesC (non-condensing)
Noise Level	Less than 45dB

Compatible with OS	Supports Windows
	2000/2003/XP/Vista/2008/7
Communication interface	Elite 2000pro (N/A)
	Elite 2000ipro (USB/RJ11)

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: https://www.comx-computers.co.za/ELITE-2000PRO-Mercury-Elite-2000-Pro-UPS-p-64870.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-11 10:10:18.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.