ComX Computers
Product Specification Sheet

ELP1200IEC

Eaton Ellipse Pro 1200 1200VA / 750W line-interactive UPS

Product Overview

Eaton Ellipse Pro 1200 1200VA / 750W line-interactive Tower UPS, ELP1200IEC, Rack/Tower Configuration, LCD User Interface, USB Port communication Ports, C14, 4x C13 Outputs, 4x C13 surge only





Specifications

Specifications:

© 2022 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	ELP1200IEC
General specifications	
Product Name	Eaton Ellipse PRO UPS
Catalog Number	ELP1200IEC
UPC	743172437952
Product Length/Depth	82 mm
Product Height	275 mm
Product Width	390 mm
Product Weight	9.9 kg
Compliances	CE Marked
Certifications	IEC/EN 62040-1
	IEC/EN 62040-2
	CE
	EAC

Product specifications	
Secondary frequency - max	60 Hz
Wattage	750W
Output power factor	0.6
Form factor	Tower
Includes network card	No
Input connection	C14
Input voltage - min	150 V
Output voltage - max	284 V
Secondary frequency - min	50 Hz
Software compatibility	Eaton UPS Companion (enables safe system shutdown, energy usage metering and configuration of UPS settings)
Battery replacement	User replaceable
Battery type	Sealed, lead-acid
Efficiency	97
Special features	Convenient extra-flat design for easy installation in any office environment
	Automatic Voltage Regulation (AVR)
	High performance surge-protection device compliant with IEC 61643-11 standard
	Data line protection to ensure that the internet line (including xDSL) is protected against surges
	LCD display for real-time status and measurements
	8 outlets to connect your PC + peripherals
	EcoControl function helps you save up to 20 % energy compared to previous generation UPSs
	HID-compliant USB port (cable supplied), for automatic integration with major operating systems (Windows/Mac OS/Linux)
	Easy to replace battery helps to extend UPS service life
Construction type	Free standing model
Output voltage - min	176 V
Color	Black
Extended battery capability	No
Output voltage range	176-284 V
Topology	Line-interactive
Surge protection	Yes
Back-up time	9 min
Input nominal voltage	230V default (220/230/240V)
Input frequency range	46-70 Hz
Input voltage - max	285 V
Voltage type	AC

Phase (output)	1
Battery management	Replaceable batteries, Automatic battery test, deep-discharge protection, cold-start capable
Auto shutdown function	Yes
Number of Outputs C13	8
Operating temperature - min	0 degreesC
VA rating	1200 VA
Potential free switch contact	No
Receptacle	(4) C13, (4) C13 surge only
Phase (input)	1
Package contents	(2) IEC-IEC cables
	USB cable
	User manual
	Safety instructions
Noise level	
Feed type	1
Runtime graph	View runtime graph
User interface	LCD (UPS status and measurements, configuration of UPS settings)
Battery quantity	2
Operating temperature - max	35 degreesC
Voltage	230V
Temperature range	0 degrees to 35 degreesC (32 degrees to 95 degreesF)
Ethernet interface	No
Communication	USB port (HID compliant)
Relative humidity	0-85% non-condensing
Output apparent power	1200 VA
Rack mounting kit	No
Output frequency	50/60 Hz
Runtime at full load	2 min
Type of interface	USB
Primary frequency - min	46 Hz
Battery rating	12 V / 7 Ah
Type	UPS
Output nominal voltage	230V default (220/230/240V)
Expansion slots	No
Input voltage range	165-285 V (adjustable to 150-285 V)
Nominal frequency	50/60 Hz
Primary frequency - max	70 Hz

Altitude	2000 m

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/ELP1200IEC-Eaton-Ellipse-Pro-1200-1200VA-750W-line-interactive-UPS-p-265994.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-14 03:09:04.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.