ComX Computers
Product Specification Sheet

FS608-400PES

NETGEAR PROSAFE FS608 - 8 PORT FAST ETHERNET SWITCH

Product Overview

NETGEAR PROSAFE FS608 - 8 PORT FAST ETHERNET SWITCH, 8 Port 10/100 Fast Ethernet switch. Plastic case



Specifications

Overview:

The ProSafe 8-Port 10/100 Desktop Switch from Netgear is an 8-port Ethernet switch that can operate at speeds of up to 200 Mbps in full-duplex mode. The switch features Store and Forward packet switching and Auto Uplink ports for automatic MDI/MDI-X detection. The switch features a compact desktop form factor, making it an excellent addition to your network.

Full Duplex Support

The switch not only supports standard 10/100 Mbps devices in half-duplex mode, but is also capable of speeds of up to 200 Mbps in full-duplex mode. This makes the switch an excellent option for use in networks where data transfer bandwidth is crucial.

Autosensing MDI/MDI-X Ports

Every port on the switch is autosensing MDI/MDI-X, so you won't have to worry about switching between standard Ethernet and crossover cables when configuring your network.

Compact Form Factor

The switch features a compact form factor that allows you to easily integrate it into almost any work environment.

Specifications:

© 2015 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	FS608-400PES
Standards	IEEE 802.3, IEEE 802.3u
Protocols	Standard Network Protocols
Ports	8x 10/100 Auto-Negotiation RJ-45 Ports
Speed	Half-Duplex: 10/100 Mbps
	Full-Duplex: 20/200 Mbps
MAC Address Table Size	48-bit
Switching Method	MDI/MDI-X
VLANs	None
Management	None
Form Factor	Desktop
System Requirements	Network card for each connected PC
	Network cables
	Network software (Windows, Linux, Mac OS, etc)
Environmental Requirements	Operating
	Temperature: 32-104 degrees F (0-40 degrees C)
	Humidity: 0-90%, non-condensing
	Altitude: 10, 000' (3000 m)
	Storage
	Temperature: 14-158 degrees F (-10-70 degrees C)
	Humidity: 0-95%, non-condensing
	Altitude: 10, 000' (3000 m)
Power Requirements	AC: 110 VAC
	DC: 7.5 VDC, 1 amp
Dimensions (WxHxD)	6.2 x 1.1 x 4.1" (15.8 x 2.7 x 10.3 cm)
Weight	1.1 lb (0.49 kg)
Package Weight	1.7 lb
Box Dimensions (LxWxH)	8.661 x 6.772 x 4.331"

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/FS608-400PES-NETGEAR-PROSAFE-FS608-8-PORT-FAST-ETHERNET-SWITCH-p-130550.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-12 05:10:04.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.