


GA-Z890-AORUS-MASTER

Gigabyte Z890 Aorus Master Intel Core Ultra Socket LGA 1851 ATX Motherboard

Product Overview

Gigabyte Z890 Aorus Master Intel Core Ultra Socket LGA 1851 ATX Motherboard, Intel Z890 Express Chipset, 4 x DDR5 DIMM Memory slots, 2 x Intel Thunderbolt 4 connectors (USB4 USB Type-C Ports) supporting DisplayPort and Thunderbolt Video Outputs, High Definition audio, Marvell aqtion AQC113c 10GbE LAN Chip, Intel Wi-Fi 7, Bluetooth 5.4, 1x PCI Express x16 slot supporting PCI-e 5.0 and running at x16, 1x PCI Express x16 slot supporting PCI-e 4.0 and running at x4, 1x PCI Express x16 slot, Supporting PCI-e 4.0 and running at x1, 4x SATA 6Gb/s connectors, 5x M.2 connectors with PCI-e 5.0 x4/x2 & PCI-e 4.0 x4/x2 support, USB 3.2 Gen 2 Type-A Ports, USB Type-C Port with USB 3.2 Gen 2x2 support, USB 3.2 Gen 1 Ports, USB 2.0/1.1 Ports, 1x Q-Flash Plus Button, 2x audio jacks, 1x Optical S/PDIF out connector





Specifications

Overview:

Z890 AORUS MASTER

- Supports Intel Core Ultra processors (Series 2)
- Digital twin 18+1+2 phases VRM solution
- D5 Bionic Corsa for Infinite Memory Performance
- AORUS AI SNATCH : Auto-Overclocking Software by AI models
- AI Perfdrive : Provides optimal and customized BIOS preset profile for users
- Premium Compatibility : 4*DDR5 with XMP Memory Module Support
- DDR Wind Blade : Enhanced Active Cooling for Memory Modules
- WIFI EZ-Plug : Quick and easy design for Wi-Fi antenna installation
- EZ-Latch Plus : PCIe and M.2 slots with Quick Release & Screwless Design
- EZ-Latch Click : M.2 heatsinks with screwless design
- Sensor Panel Link : Onboard video port for hassle-free in-chassis panel setup
- Friendly UI : Multi-Theme, AIO Fan Control, and Q-Flash Auto Scan in BIOS and SW
- NewPower Monitor in HWinfo for real-time monitoring on CPU power phases
- Ultra-Fast Storage : 5*M.2 slots, including 2* PCIe 5.0 x4
- Efficient Thermal : VRM Thermal Armor Advanced & M.2 Thermal Guard XL
- Fast Networking : 10GbE LAN & Wi-Fi 7 with directional Ultra-high gain antenna
- Extended Connectivity : Dual THUNDERBOLT 4 Type-C with DP-Alt
- DTS : X Ultra Audio : ALC1220 & Rear ESS SABRE Hi-Fi 9118 DAC
- Ultra Durable PCIe Armor : The metal back plate of PCIe x16 slot for enhanced durability
- PCIe UD Slot X : PCIe 5.0 x16 slot with 10X strength for graphics card

Features:

Infinite Memory Performance

AORUS gaming motherboards boost DDR5 memory performance and offer top-notch compatibility using various advanced methods.

Comprehensive Thermal

AORUS motherboards come with advanced full-metal thermal design and durable heatsinks to keep your system cool and efficient

Hassle-free Assembly

Our cutting-edge motherboard is designed for the ultimate DIY experience. Creating your own PC becomes a delightful and smooth process.

WIFI EZ-Plug

The WIFI EZ-Plug design integrates Wi-Fi antenna plugs into one adapter, EZ to install.

EZ-Latch Designs

User-friendly designs simplifying the assembly process.

M.2 EZ-Latch Click

screwless installation for M.2 heatsink

Connectivity

Experience ultimate connectivity with next-generation network, storage, and Wi-Fi solutions, delivering lightning-fast data transfer speeds.

- Dual THUNDERBOLT 4
- Wi-Fi 7
- Directional Ultra-high Gain Antenna
- 10GbE LAN

Born from Ultra Durable

Technology embodies our commitment to excellence, providing gamers with a platform that's not only powerful but also built for longevity and reliability. AORUS series motherboards are engineered to endure and excel.

PCIe UD Slot X

The latest PCIe UD Slot X offers unparalleled robustness, delivering superior protection for your graphics card.

Memory UD Slot D5

employs a unibody, stainless-steel shield design, reinforcing memory slots and optimizing signal integrity and overclocking potential.

UD Power Connector

Our innovative UD Power Connector design enhances power conductivity and thermal dissipation.

Solid Pins

Delivers superior conductivity and signal transmission and reduces metal wear from repeated connections.

Ultra Durable PCIe Armor

Features a metal reinforcement plate for the PCIe x16 slot, enhancing stability and durability to support large graphics cards.

Specifications:

© 2024 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.	
Specifications	
Product Code	GA-Z890-AORUS-MASTER
CPU	LGA1851 socket: Support for Intel Core Ultra Processors
	L3 cache varies with CPU
Chipset	Intel Z890 Express Chipset

Memory	Support for DDR5 9500(O.C) / 9466(O.C) / 9333(O.C) / 9200(O.C) / 9066(O.C) / 8933(O.C) / 8800(O.C) / 8600(O.C) / 8400(O.C) / 8266(O.C) / 8200(O.C) / 8000(O.C) / 7950(O.C) / 7900(O.C) / 7800(O.C) / 7600(O.C.) / 7400(O.C.) / 7200(O.C.) / 7000(O.C.) / 6800(O.C.) / 6600(O.C.) / 6400 / 6200 / 6000 / 5800 / 5600MT / s memory modules.
	4 x DDR5 DIMM sockets supporting up to 256 GB (64 GB single DIMM capacity) of system memory
	Dual channel memory architecture
	Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode)
	Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules
	Support for Extreme Memory Profile (XMP) memory modules
	Support CUDIMM memory module
	(The CPU and memory configuration may affect the supported memory types, data rate (speed), and number of DRAM modules, please refer to "Memory Support List" for more information.)
Onboard Graphics	Integrated Graphics Processor-Intel HD Graphics support:
	- 2 x Intel Thunderbolt 4 connectors (USB4 USB Type-C ports), supporting DisplayPort and Thunderbolt video outputs
	When a Thunderbolt monitor is installed, the maximum resolution supported is 5120x2880@60 Hz with 24 bpp (single display output).
	When a USB4 USB Type-C monitor is installed, the maximum resolution supported is 3840x2160@240 Hz (single display output).
	* Because of the limited I/O resources of the PC architecture, the number of Thunderbolt devices that can be used is dependent on the number of the PCI Express devices being installed. (Refer to Chapter 2-6, "Back Panel Connectors, " for more information.)
	* Support for DisplayPort 2.1 version and HDCP 2.3
	- 1 x front HDMI port, supporting a maximum resolution of 1920x1080@30 Hz
	* Support for HDMI 1.4 version.
	(Graphics specifications may vary depending on CPU support.)
	Support for up to triple-display at the same time
Audio	Realtek ALC1220 CODEC
	* The front panel line out jack supports DSD audio.
	ESS ES9118 DAC chip
	Support for DTS:X Ultra
	High Definition Audio
	2/4/5.1-channel
	* You can change the functionality of an audio jack using the audio software. To configure 5.1-channel audio, access the audio software for audio settings.
	Support for S/PDIF Out
LAN	Marvell AQtion AQC113C 10GbE LAN chip
	(10 Gbps/5 Gbps/2.5 Gbps/1 Gbps/100 Mbps)

ComX Computers

Product Specification Sheet

Wireless Communication module	Intel Wi-Fi 7 BE200NGW
	- 802.11a, b, g, n, ac, ax, be, supporting 2.4/5/6 GHz carrier frequency bands
	- BLUETOOTH 5.4
	- Support for 11be 320MHz wireless standard
	(Actual data rate may vary depending on environment and equipment.)
	* Wi-Fi 7 features require Windows 11 SV3 to function properly. (There is no support driver for Windows 10.)
	** Wi-Fi 7 channels on 6 GHz band availability depends on individual country's regulations.
Expansion Slots	CPU:
	- 1 x PCI Express x16 slot, supporting PCIe 5.0 and running at x16 (PCIEX16)
	* The PCIEX16 slot can only support a graphics card or an NVMe SSD. If only one graphics card is to be installed, be sure to install it in the PCIEX16 slot.
	* The PCIEX16 slot shares bandwidth with the M2D_CPU connector. The PCIEX16 slot operates at up to x8 mode when a device is installed in the M2D_CPU connector.
	Chipset:
	- 1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x4 (PCIEX4)
	- 1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x1 (PCIEX1)
Storage Interface	CPU:
	- 1 x M.2 connector (Socket 3, M key, type 25110/22110/2580/2280 PCIe 5.0 x4/x2 SSD support) (M2A_CPU)
	- 1 x M.2 connector (Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSD support) (M2B_CPU)
	- 1 x M.2 connector (Socket 3, M key, type 22110/2280 PCIe 5.0 x4/x2 SSD support) (M2D_CPU)
	Chipset:
	- 1 x M.2 connector (Socket 3, M key, type 2280 PCIe 4.0 x4/x2 SSD support) (M2P_SB)
	- 1 x M.2 connector (Socket 3, M key, type 2280 SATA and PCIe 4.0 x4/x2 SSD support) (M2M_SB)
	- 4 x SATA 6Gb/s connectors
	RAID 0, RAID 1, RAID 5, and RAID 10 support for NVMe SSD storage devices
	RAID 0, RAID 1, RAID 5, and RAID 10 support for SATA storage devices

USB	CPU:
	- 2 x Intel Thunderbolt 4 (USB Type-C) ports on the back panel
	*Support up to 40Gbps with Thunderbolt devices
	*Support up to 20Gbps with USB4 devices
	*Support up to 10Gbps with USB 3.2 devices
	Chipset:
	- 6 x USB 3.2 Gen 2 Type-A ports (red) on the back panel
	Chipset+USB 3.2 Gen 2x2 Hub:
	- 1 x USB Type-C port with USB 3.2 Gen 2x2 support, available through the internal USB header
	Chipset+2 USB 3.2 Gen 1 Hubs:
	- 8 x USB 3.2 Gen 1 ports (4 ports on the back panel, 4 ports available through the internal USB headers)
	Chipset+2 USB 2.0 Hubs:
	- 6 x USB 2.0/1.1 ports (2 ports on the back panel, 4 ports available through the internal USB headers)

ComX Computers

Product Specification Sheet

Internal I/O Connectors	1 x 24-pin ATX main power connector
	2 x 8-pin ATX 12V power connectors
	1 x CPU fan header
	1 x CPU fan/water cooling pump header
	4 x system fan headers
	4 x system fan/water cooling pump headers
	4 x addressable RGB Gen2 LED strip headers
	1 x RGB LED strip header
	5 x M.2 Socket 3 connectors
	4 x SATA 6Gb/s connectors
	1 x front panel header
	1 x front panel audio header
	1 x USB Type-C header, with USB 3.2 Gen 2x2 support
	2 x USB 3.2 Gen 1 headers
	2 x USB 2.0/1.1 headers
	1 x noise detection header
	1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only)
	1 x HDMI port (Note)
	1 x power button
	1 x reset button
	1 x reset jumper
	1 x Clear CMOS jumper
	2 x temperature sensor headers
	Voltage Measurement Points
	(Note) Actual support may vary by CPU
Back Panel Connectors	1 x Q-Flash Plus button
	1 x Clear CMOS button
	2 x Intel Thunderbolt 4 connectors (USB Type-C ports)
	6 x USB 3.2 Gen 2 Type-A ports (red)
	4 x USB 3.2 Gen 1 ports
	2 x USB 2.0/1.1 ports
	1 x RJ-45 port
	2 x antenna connectors (2T2R)
	2 x audio jacks
	1 x optical S/PDIF Out connector
I/O Controller	iTE I/O Controller Chip

ComX Computers

Product Specification Sheet

H/W Monitoring	Voltage detection
	Temperature detection
	Fan speed detection
	Water cooling flow rate detection
	Fan fail warning
	Fan speed control
	* Whether the fan (pump) speed control function is supported will depend on the fan (pump) you install.
	Noise detection
BIOS	1 x 256 Mbit flash
	Use of licensed AMI UEFI BIOS
	PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0
Unique Features	Support for GIGABYTE Control Center (GCC)
	* Available applications in GCC may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications.
	Support for Q-Flash
	Support for Q-Flash Plus
	Support for Smart Backup
Bundled Software	Norton Internet Security (OEM version)
	LAN bandwidth management software
Operating System	Support for Windows 11 64-bit
Form Factor	ATX Form Factor , 30.5cm x 24.4cm

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/GA-Z890-AORUS-MASTER-Gigabyte-Z890-Aorus-Master-Intel-Buy-p-314257.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-14 06:09:06.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.