ComX Computers
Product Specification Sheet

GS-DP725

Grandstream DECT HD handset - Compatible with DP750 / DP752 / DP755

Product Overview

Grandstream DECT HD Handset - compatible with DP750 / DP752 / DP755, 400 meters Outdoor range, 50 meters Indoor range, 1.8 inch 128x160 Colour TFT LCD, Each Handset may Access up to 20 lines, 3.5mm Headset jack, Removable belt clip, Type-C USB Port

Specifications

Overview:

DP725

DECT Cordless HD Handset for Mobility

The DP725 is a DECT cordless HD handset for mobility and allows the user to move freely and efficiently throughout any work environment and is supported by the DP750, DP752, and DP755 DECT VoIP base stations to provide a combination of mobility and top-notch telephony performance.

- Supports a range of up to 400 meters outdoors (with DP755) and 50 meters indoors
- 1.8 inch (128x160) color TFT LCD with 2 programmable soft keys
- Offers 50-hour talk time and 500-hour standby time
- Supports up to 20 SIP accounts and 20 lines per handset as well as 3-way conferencing
- DECT authentication & encryption technology to protect calls & account
- Dedicated push-to-talk button
- Automated provisioning options include TR-069 and XML config files
- Use with Grandstream's UCM series of IP PBXs for Zero Config provisioning
- HD audio to maximize audio quality and clarity; full duplex speakerphone
- Supports advanced telephony features, including call transfer, call forward, call-waiting, do not disturb, message waiting indication, multi language prompts, flexible dial plan and more

Features:

Full Office Coverage

The DP725 provides up to 50 meters of indoor range to cover any office, store, and home.

Extended Outdoor Range

Pair the DP725 with our DP755 DECT Base Station to experience up to 400m range outdoors, ideal for stadiums, campuses, and more.

Long Battery Life

The DP725 provides up to 50 hours talk time and 500 hours standby time from one charge.

Fast Charging

With just a 10-minute charge, the DP725 provides up to 4 hours of talk time.

Push-to-Talk

A dedicated and customizable Push-to-Talk button provides instant communication for teams and home users.

Pair Up to 10 Handsets

Each DP755 DECT Base Station supports up to 10 DP725 handsets and 20 SIP accounts, while each DP725 handset can support up to 20 lines.

Facility Access Control

Pair the DP725 with our GDS Series to control door entry and facility access from anywhere in a facility.

Specifications:

© 2024 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	GS-DP725
Range	Outdoor Range: 400 meters (DP755), Indoor Range: 50 meters
Display	1.8 inch (128x160) color TFT LCD
Voice Codecs	G.722 codec for HD audio and G.726 codec for narrow band audio (G.711u/a-law, G.723.1, G.729A/B, iLBC and OPUS are supported via companion DECT base station, AEC, AGC, Ambient noise reduction on handset mic, advanced noise suppression for incoming audio
Multi-Line Access	Each handset may access up to 20 lines
SIP Accounts	N/A
Device Management	Yes, GDMS
Air Interface	Telephony standards: DECT
	Frequency bands:
	1880 - 1900 MHz (Europe), 1920 - 1930 MHz (US)
	1910 - 1920 MHz (Brazil), 1786 - 1792 MHz (Korea)
	1893 - 1906 MHz (Japan), 1880 - 1895 MHz (Taiwan)
	Number of Channels: 10 (Europe), 5 (US, Brazil or Japan), 3 (Korea), 8 (Taiwan)
	Outdoor Range: up to 400 meters (DP752/DP755) or up to 300 meters (DP750)
	Indoor Range: up to 50 meters

Peripherals	1.8 inch (128x160) color TFT LCD
	27 keys including 2 soft keys, 5 navigation/ menu keys, 5 dedicated function keys for SPEAKERPHONE, MUTE, SEND, POWER/END, 3 side keys including 2 volume (up and down) and 1 Push-to-Talk key
	3-color MWI LED
	3.5mm headset jack
	Removable belt clip
	Type C USB port for alternative charging and non-battery operation
Protocol/Standards	Hearing Aid Compatibility (HAC) compliant
Voice Codecs	G.722 codec for HD audio and G.726 codec for narrow band audio (G.711u/a-law, G.723.1, G.729A/B, iLBC and OPUS are supported via companion DECT base station, AEC, AGC, Ambient noise reduction on handset mic, advanced noise suppression for incoming audio
Telephony Features	Hold, transfer, forward, 3-way conference, push-to-talk, intercom, downloadable phonebook, call waiting, call log, auto answer, click-to-dial, flexible dial plan
HD Audio	Yes, both on Handset and Speakerphone
Security	DECT authentication & encryption
Multi-language	English, Czech, German, Spanish, French, Hebrew, Italian, Dutch, Polish, Portuguese, Russian, Turkish, Arabic, Chinese Simple, Chinese Tradition, Japanese, Korean, Slovakian, Serbian, Greek, Swedish
Upgrade/ Provisioning	Software Upgrade Over-The-Air (SUOTA), handset provisioning Over-The-Air
Multi-line Access	Each handset may access up to twenty (20) lines
Power & Green Energy Efficiency	Universal Power Supply Input AC 100-240V 50/60Hz, Output 5VDC 1A, USB-C Connector
	Rechargeable 1500mAh Li-ion battery
	(500 hours of standby time and 50 hours of talk time)
Package Content	Handset unit, universal power supply, charger cradle, belt clip, 1 battery, Quick Start Guide
Dimensions (H x W x D)	Handset: 135 x 49 x 15.5mm, Charger cradle: 85 x 85 x 25mm
Weight	Handset: 107g, Charger cradle: 61g, Universal power supply: 55g, Package: 364g
Temperature and Humidity	Operation: -10º to 45ºC (14 to 113ºF), Charging: 0 to 45ºC (32 to 113ºF)
	Storage: -20º to 60ºC (-4 to 140ºF), Humidity: 10% to 90% non-condensing
Compliance	FCC, CE, RCM, IC

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/GS-DP725-Grandstream-DECT-HD-handset-Compatible-with-DP750-DP752-DP755-p-304998.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

ComX Computers

Product Specification Sheet

PDF generated: 2026-10-31 05:34:46.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.