ComX Computers
Product Specification Sheet

GV-N208SGAMING OC-8GC

Gigabyte nVidia GeForce RTX 2080 AORUS 8192MB GDDR6 256-Bit Graphics Card

Product Overview

Gigabyte nVidia GeForce RTX 2080 AORUS - 8192MB GDDR6, 256-Bit Memory Bus, PCI Express 3.0, Connections: USB Type C (support VirtualLink), 1x HDMI, 3x DisplayPort, Core: 1845MHz, Memory: 15500MHz



Specifications

Features:

WINDFORCE 3X COOLING SYSTEM
The WINDFORCE 3X cooling system features 3x 82mm unique blade fans, alternate spinning fan, 6 composite copper heat pipes, heat-pipe direct touch and 3D active fan functionality, together delivering an effective heat dissipation capacity for higher performance at lower temperatures.

ALTERNATE SPINNING
The GIGABYTE patent "Alternate Spinning" is the only solution that can solve the turbulent airflow of three fans. The biggest problem with the three fans is turbulence. Since the fans rotate in the same direction, the airflow direction is opposite between the fans, which will cause turbulent airflow and reduce heat dissipation efficiency. GIGABYTE turns the middle fan in the opposite direction, so that the airflow direction between the two fans is the same, reducing the turbulence and enhancing the airflow pressure.

UNIQUE BLADE FAN
The airflow is spilt by the triangular fan edge, and guided smoothly through the 3D stripe curve on the fan surface, effectively enhancing the airflow.

3D ACTIVE FAN
The 3D Active Fan provides semi-passive cooling, and the fans will remain off when the GPU is in a low load or low power game. It allows gamers to enjoy gameplay in complete silence when the system is running light or idle.

HEAT PIPES DIRECT TOUCH
The shape of the pure copper heat pipe maximizes the direct contact area with the GPU, enhancing heat transfer. The heat pipe also covers the VRAM through a large metal plate contact to ensure proper cooling.

COMPOSITE HEAT-PIPE
The composite heat-pipe combines thermal conductivity and phase transition to efficiently manage the heat transfer between

two solid interfaces which increases cooling capacity.

RGB FUSION 2.0
With 16.7M customizable color options and numerous lighting effects, you can choose lighting effects or synchronize with other AORUS devices.

Extreme durability and overclocking
The graphics card uses the better power phase design to allow the MOSFET to operate at lower temperature, and over-temperature protection design and load balancing for each MOSFET, plus the Ultra Durable certified chokes and capacitors, to provide excellent performance and longer system life.

Protection Metal Back Plate
The metal back plate not only provides an aesthetical shape, but also enhances the structure of the graphics card to provide complete protection.

POWER INDICATORS
The smart power LED indicator alerts the player when any PCI-E power supply is abnormal.

NVIDIA NVLink TM Support
Support for NVIDIA NVLinkTM (NVIDIA SLI) technology, which combines 2 identical GPUs with an GeForce RTX NVLink Bridge to deliver the ultimate experience in 4K gaming or VR gaming. You can also adjust the light effect on the bridge with the AORUS Engine.

IN TOTAL COMMAND
The interface and functionality of the software is subject to each model.

AORUS Engine
The cutting edge intuitive interface allows you to adjust the clock speed, voltage, fan performance and power target in real-time according to your game's requirements.

Specifications:

© 2019 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	GV-N208SGAMING OC-8GC
Graphics Processing	GeForce RTX 2080 SUPER
Core Clock	1845 MHz (Reference Card: 1815 MHz)
RTX-OPS	64
CUDA Cores	3072
Memory Clock	15500 MHz
Memory Size	8 GB
Memory Type	GDDR6
Memory Bus	256 bit
Memory Bandwidth (GB/sec)	496 GB/s
Card Bus	PCI-E 3.0 x 16

Digital max resolution	7680x4320@60Hz
Multi-view	4
Card size	L=286.5 W=114.5 H=50.2 mm
PCB Form	ATX
DirectX	12
OpenGL	4.5
Recommended PSU	650W
Power Connectors	8 Pin*1, 6 Pin*1
Output	DisplayPort 1.4 *3
	HDMI 2.0b *1
	USB Type-C (support VirtualLink) *1
SLI support	2-way NVIDIA NVLINK
Accessories	1. Quick guide
	2. Driver CD
	3. 4-year warranty registration

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/GV-N208SGAMING-OC-8GC-Gigabyte-nVidia-GeForce-RTX-2080-AORUS-8192MB-GDDR6-256-Bit-p-226343.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-14 21:41:03.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.