

HK-302915236

Hikvision 50W Power Box

Product Overview

Hikvision 50W Power Box, DS-K7M-AW50, Output Voltage 12 VDC, Output Power 50 W



Specifications

Overview Summary:

The Hikvision DS-K7M-AW50 50W Power Box provides a dependable power supply for access control terminals and locks. With 100-240 VAC input, 12 VDC output and 50 W output power, it is designed for practical access control installations.

Buy the Hikvision DS-K7M-AW50 online in South Africa for a reliable power solution for your security system. Shop now for dependable power delivery with short-circuit, overload and over-voltage protection.

Performance tier:Professional

Uses:Access control terminals, electronic locks, security systems, access control installations

Overview:

Hikvision DS-K7M-AW50 50W Power Box

The Hikvision DS-K7M-AW50 is a 50W power box designed to provide a reliable power source for access control systems. It can supply power to one access control terminal and one lock, making it a practical solution for installations where stable and protected power delivery is required.

Description:

The DS-K7M-AW50 provides 12 VDC output power with a maximum output of 50 W and accepts a wide 100 to 240 VAC input range. Built-in protection helps safeguard connected equipment against short circuits, excessive load and over-voltage conditions. The power box also supports a storage battery, providing additional flexibility for access control installations.

With an MTBF of more than 200,000 hours, the Hikvision DS-K7M-AW50 is designed for dependable long-term operation. Its dedicated power supply design makes it suitable for powering an access control terminal together with an electric lock.

Features:**Reliable Power for Access Control Systems**

The DS-K7M-AW50 is intended for access control applications where a dedicated power supply is required. Its 50W output provides sufficient capacity for one access control terminal and one lock, helping simplify the power requirements of a typical access control installation.

The unit accepts standard mains input from 100 to 240 VAC and converts this to a stable 12 VDC output for compatible access control equipment.

Key points include:

- 50W power output for access control applications
- 12 VDC output voltage
- Supports one access control terminal and one lock
- 100 to 240 VAC input voltage
- Storage battery support
- Short-circuit protection
- Excess load protection
- Over-voltage protection
- MTBF greater than 200,000 hours

Protected 12 VDC Power Output

Protection is built into the DS-K7M-AW50 to help reduce the risk of damage caused by common electrical conditions. Short-circuit, excess load and over-voltage protection help provide a safer power solution for connected access control equipment.

The storage battery support also allows the power box to be integrated into installations where battery backup capability is required.

Technical Details

- Model: DS-K7M-AW50
- Product type: 50W Power Box
- Input voltage: 100 to 240 VAC
- Output voltage: 12 VDC
- Output power: 50 W
- Supported equipment: 1 access control terminal and 1 lock
- Battery support: Yes
- MTBF: More than 200,000 hours
- Protection: Short circuit, excess load and over-voltage

Part Number / SKU

The part number / SKU for this Hikvision power box is HK-302915236 . This reference can be used when searching for or ordering the DS-K7M-AW50.

A Practical Access Control Power Solution

For access control installations requiring dependable 12 VDC power, the Hikvision DS-K7M-AW50 combines a 50W output with electrical protection and storage battery support. It is a suitable choice for powering a compatible access control terminal and lock from a dedicated power supply.

Specifications:

ComX Computers

Product Specification Sheet

© 2026 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	HK-302915236
Working temperature	-10 degreesC to 70 degreesC (14 degreesF to 158 degreesF)
Working humidity	< 95%
Dimensions	235 mm x 384 mm x 90 mm (9.3" x 15.1" x 3.5")

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx-computers.co.za/HK-302915236-Hikvision-50W-Power-Box-Buy-p-340492.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-08 12:42:03.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.