

HK-302919041

Hikvision Value Series face Access Terminal

Product Overview

Hikvision Value Series face Access Terminal, DS-K1T341CMW, 4.3 inch capacitive Touch Screen screen, 2MP Resolution camera, Noise suppression and Echo cancellation, Wi-Fi, 1x RJ-45 10/100 m Self-Adaptive Network Interface, 1 lock control, 1 Exit Button, 1 Door contact Input, 1 tamper, 1x RS-485, 1 Wiegand, 1x USB, Greater than 2m Face Recognition distance, M1 card



Specifications

Overview Summary:

The Hikvision DS-K1T341CMW Value Series Face Access Terminal provides reliable biometric access control for businesses, offices and other secure environments in South Africa. It combines face recognition and M1 card authentication with a 4.3-inch capacitive touch screen, 2MP camera, Wi-Fi and built-in access control.

With support for Hik-Connect, QR code recognition, anti-spoofing and secure door control connections, this terminal is designed for practical, modern entry management. Buy now for a dependable Hikvision access control solution, or shop now to upgrade your door security.

Performance tier:Value Series

Uses:biometric access control, office entry management, secure door access, employee access control, visitor access, commercial security

Overview:

Hikvision DS-K1T341CMW Face Access Terminal

The Hikvision DS-K1T341CMW Value Series face access terminal provides fast and convenient access control with reliable face recognition and card authentication. Designed for modern door security applications, it combines a 4.3-inch capacitive touch screen with a 2 MP wide-angle dual-lens camera for accurate user identification and simple operation.

With support for up to 3,000 faces, 3,000 cards and 150,000 events, this Hikvision access control terminal is suitable for offices, businesses, commercial buildings and other environments requiring controlled entry. Multiple authentication methods

provide flexibility, while the deep learning algorithm helps deliver fast face recognition in less than 0.2 seconds per user.

Description:

The DS-K1T341CMW is designed to make daily access management faster and more convenient while maintaining strong security. Face and card authentication provide flexible entry options, while mask wearing detection adds another useful security function. The terminal can also connect to external access controllers or Wiegand card readers, giving it greater flexibility for different access control installations.

For enhanced door security, the terminal supports RS-485 communication with a secure door control unit. This helps prevent the door from being opened if the access terminal itself is damaged or destroyed. Two-way audio communication is also supported through compatible client software, door stations, indoor stations and main stations.

Features:**Fast Face Recognition and Touch Control**

The 4.3-inch capacitive touch screen provides an intuitive interface for users and administrators. The 2 MP wide-angle dual-lens camera supports accurate face recognition at a distance of greater than 2 metres, while the deep learning algorithm helps provide rapid authentication.

Face recognition takes less than 0.2 seconds per user, making the terminal well suited to locations where people need to enter and exit efficiently.

Access Management Capacity

The Hikvision DS-K1T341CMW offers practical storage capacity for everyday access control management:

- Up to 3,000 face records
- Up to 3,000 card records
- Up to 150,000 event records
- Supports face and card authentication
- M1 card support
- Mask wearing detection

Flexible Door Security Connections

The terminal provides several connection options for integrating with existing access control equipment. Wiegand communication allows connection to an external access controller or Wiegand card reader, while RS-485 can be used to connect to a secure door control unit.

Additional access control connections include:

- 1 lock control
- 1 exit button input
- 1 door contact input
- 1 tamper input
- 1 x RS-485
- 1 x Wiegand
- 1 x USB
- 1 x RJ-45 10/100M self-adaptive network interface
- Wi-Fi connectivity

Audio and Communication

Two-way audio communication allows the DS-K1T341CMW to work with compatible Hikvision client software, door stations, indoor stations and main stations. This can be useful for visitor management and controlled entry applications where communication is required before granting access.

Compact Networked Access Control Solution

With wired and wireless network connectivity, fast face recognition, card authentication and support for external access control equipment, the Hikvision DS-K1T341CMW provides a versatile solution for modern access management. Its combination of touchscreen control, camera-based authentication and multiple interfaces makes it suitable for a wide range of commercial and professional security installations.

Product part number / SKU: HK-302919041

Model: Hikvision DS-K1T341CMW Value Series Face Access Terminal

Specifications:

© 2026 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.	
Specifications	
Product Code	HK-302919041
Display	
Screen size	4.3 inch
Operation method	Capacitive touch screen
Video	
Lens	2
Resolution	2 MP (video stream: 720P)
FOV	HFOV = 41.5degrees , VFOV = 75.5degrees , DFOV = 87degrees
Audio	
Audio quality	Noise suppression and echo cancellation
Network	
Wired network	Support
Wi-Fi	Support, 2.4 G, 802.11b/g/n
Interface	
Network interface	1 RJ-45, 10/100 M self-adaptive
Lock control	1
Exit button	1
Door contact input	1
TAMPER	1
RS-485	1,RS-485 (Half duplex,HIKVISION)
Wiegand	1,Wiegand (Hik 26bit,Hik 34bit)
USB	1
Authentication	
Face recognition distance	> 2 m

ComX Computers

Product Specification Sheet

Card type	M1 card
General	
Built-in access controller	Support
Power supply	12 VDC to 24 VDC, 2 A
Power consumption	<= 10 W
Working temperature	-30 degreesC to 60 degreesC (-22 degreesF to 140 degreesF)
Protective level	IP65
Language	English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil), Korean
Function	
Hik-Connect	Support
QR code recognition	Support
Face anti-spoofing	Support

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/HK-302919041-Hikvision-Value-Series-face-Access-Terminal-Buy-p-340512.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-17 12:20:42.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.