

HK-317500556

Hikvision DS-D5019S0-1P0 18.5" WXGA HD 1366x768 borderless Monitor, HDMI, VGA

Product Overview

Hikvision DS-D5019S0-1P0 18.5" WXGA HD 1366x768 borderless Monitor, E-led backlight, 200 nits brightness, 178 degree viewing angle, 1000:1 contrast ratio, 14 ms response time, 7x 12 hour reliability, 72% NTSC Colour Gamut, 1x HDMI 1.4, 1x VGA, 75 mm x 75mm VESA, DS-D5019S0-1P0(O-STD)



Specifications

Overview Summary:

The Hikvision DS-D5019S0-1P0 18.5 inch HD borderless monitor is a dependable display solution designed for everyday professional and commercial use. With a clear WXGA resolution, wide viewing angles, and a slim borderless design, it delivers consistent visuals while fitting neatly into offices, control rooms, and retail environments.

Equipped with both HDMI and VGA inputs, this monitor is easy to integrate with existing systems. Its low blue light design supports comfortable long viewing sessions, making it suitable for extended daily use. If you are looking for a practical, space-efficient display from a trusted brand, buy now and upgrade your workspace today.

Performance tier:Entry-level professional

Uses: office computing, CCTV monitoring, point-of-sale systems, reception desks, basic business applications

Overview:

The Hikvision DS-D5019S0-1P0 is a compact 18.5 inch HD borderless monitor designed for everyday business, security, and general computing use. Its WXGA resolution delivers clear visuals for monitoring systems, office tasks, and multimedia playback, while the slim bezel design keeps the display looking modern and unobtrusive. With wide viewing angles, stable color reproduction, and efficient power consumption, this monitor fits easily into workstations where reliability and comfort matter.

Description:

The Hikvision DS-D5019S0-1P0 monitor offers a sharp 1366 x 768 HD display with E-LED backlighting, wide 178 degree viewing angles, and a borderless design that maximizes screen space. It supports HDMI and VGA connections for flexible compatibility, includes eye-care technologies such as low blue light and noise reduction, and is built for extended daily operation. VESA mounting support and a compact footprint make it suitable for desks, walls, or control room environments.

Features:

Display and visual performance

This monitor uses an E-LED backlight to provide consistent brightness and energy efficiency. With 200 nits brightness and a 1000:1 contrast ratio, it produces balanced images suitable for indoor environments. The 72 percent NTSC color gamut and 8 bit color depth allow for accurate color rendering, while a 14 ms response time ensures smooth transitions for video and monitoring feeds. The 178 degree horizontal and vertical viewing angles help maintain image clarity even when viewed from the side.

Key display highlights include:

- 18.5 inch screen with 1366 x 768 resolution
- 178 degree wide viewing angles for flexible placement
- 72 percent NTSC color coverage for natural color output
- Anti-glare surface with haze control for reduced reflections

Comfort and everyday usability

Designed with eye comfort in mind, the monitor includes a low blue light design to help reduce eye strain during long viewing sessions. Integrated noise reduction improves image stability, making it suitable for security monitoring, office applications, and continuous display use. The slim bezel enhances focus on the screen while keeping the overall size compact.

Connectivity and mounting options

The DS-D5019S0-1P0 supports both modern and legacy systems through its HDMI 1.4 and VGA inputs. This dual interface setup allows easy integration with a wide range of computers, DVRs, and other video sources. VESA 75 mm x 75 mm mounting support gives users the flexibility to install the monitor on a wall or arm mount, freeing up desk space when needed.

Connection and installation options include:

- HDMI 1.4 input for digital video
- VGA input for analog compatibility
- VESA 75 mm x 75 mm mounting support

Build quality and operating conditions

Housed in a durable plastic casing, the monitor is built for reliable daily use, supporting operation for extended hours each day. It performs consistently across a broad range of temperatures and humidity levels, making it suitable for offices, control rooms, and commercial environments. Its lightweight design allows for easy setup and repositioning.

What's included in the box

ComX Computers

Product Specification Sheet

The package includes the monitor, base components, power adapter, HDMI cable, and user documentation, providing everything needed for quick installation and immediate use.

Specifications:

© 2026 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	HK-317500556
--------------	--------------

Display

Screen Size	18.5 inch
Active Display Area	409.8 (H) mm x 230.4 (V) mm
Resolution	1366 x 768
Backlight	E-LED
Pixel Pitch	0.300 mm (H) x 0.300 mm (V)
Brightness	200 cd/m ²
Viewing Angle	178degrees (H) / 178degrees (V)
Color Depth	8bit , 16.7 M
Contrast Ratio	1000 : 1
Response Time	14 ms
Refresh Rate	Max. 75Hz , Typ. 60 Hz
Haze	Haze 25%, 3H
Reliability	7 x 12 H
Color Gamut	72% NTSC

Interface

Video & Audio Input	HDMI 1.4 x 1, VGA x 1
Video & Audio Output	None
Data Transmission Interface	None
Control Interface	None

Power

Power Supply	DC 12V, 2.0A
Power Consumption	<= 24 W
Standby Consumption	<= 0.5 W

Working Environment

Working Temperature	0degreesC to 40 degreesC (32 degreesF to 104 degreesF)
Working Humidity	20% to 90% RH (Non-Condensing)
Storage Temperature	-20 degreesC to 60 degreesC (-4 degreesF to 140 degreesF)

ComX Computers

Product Specification Sheet

Storage Humidity	10% to 90% RH (Non-Condensing)
General	
Casing Material	Plastic
VESA	75 mm x 75mm (4 - M4 x 6 mm)
Bezel Width	17.84mm (left/right), 18.39 mm (top) , 26.39 mm (bottom)
Product Dimensions (W x H x D)	With base: 447.00 (W) mm x 351.04 (H) mm x200.21(D) mm
	(17.60 x 13.82" x 7.88" inch)
	Without base: 447.00(W) mm x 276.00 (H) mm x 46.00 (D) mm
	(17.60 x 10.87" x 1.81" inch)"
Package Dimensions (W x H x D)	487 (W) mm x 363 (H) mm x 97 (D) mm
Net Weight	1.9 +/- 0.5 kg (4.19 + 1.1 lb)
Gross Weight	2.4 +/- 0.5 kg (5.29 + 1.1 lb)
Packing List	Monitor x 1, Base component x 1, Power adapter (12 V, 2.0 A) x 1, HDMI cable (1.5 m) x 1, User manual x 1, Multilingual manual x 1
Remarks	The base is included by default.
	The product appearance and parameters in this specification may vary from your actual device. Please consult our local sales staff for further information

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/HK-317500556-Hikvision-DS-D5019S0-1P0-18-5-WXGA-HD-Buy-p-339162.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-16 15:12:44.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.