ComX Computers
Product Specification Sheet

HUSMR7632BDP301

HGST Ultrastar SN200 3200GB 2.5" NVMe Solid State Drive

Product Overview

HGST Ultrastar SN200 SSD - 3200GB 2.5" NVMe (PCIe 3.0 x4 / 2x2 NVMe 1.2) SSD, Mixed Workload, 3 DWPD, Read: Upto 3350MB/s, Write: Upto 2100MB/s, 15mm, IOPS (Upto): Random Read (max IOPS, 4KiB): 835,000 / Random Write (max IOPS, 4KiB): 200,000 / Mixed Rand



Specifications

Overview:

HGST extends its technology leadership with the introduction of the Ultrastar® SN200 Series solid-state drives (SSDs). The Ultrastar SN200 Series SSDs deliver a new level of performance and capacity for Enterprise, Cloud and Hyperscale environments. Enabling faster intelligence in the expanding digital demands of business applications the Ultrastar SN200 Series SSDs are a reliable resource for fast access to critical data. The HGST Ultrastar SN200 Series SSDs double the speed of the previous generation within the same power envelope. By offering exceptional 580,000 mixed read/write random 70/30 4KiB I/O performance on the 6.4TB HH-HL add-in card (AIC), the Ultrastar SN200 Series SSD will enable OLTP applications to scale to new levels.

Specifications:

© 2018 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	HUSMR7632BDP301
General	
Interface	PCIe 3.0 x4 or 2x2 NVMe 1.2
Capacity (GB)	3.2TB
Form Factor	U.2 2.5-inch drive
Performance	

Sequential Read (max MB/s, 128KiB)	3, 350
Sequential Write (max MB/s, 128KiB)	2, 100
Random Read (max IOPS, 4KiB)	835, 000
Random Write (max IOPS, 4KiB)	200,000, 75,000
Mixed Random Read/Write (max IOPS 70%R/30%W, 4KiB)	550,000, 240,000
Latency	20us (Write, 512B)
Reliability	
Error Rate (non-recoverable, bits read)	< 1 in 1017
MTBF (M hours)	2M hours
Annual Failure Rate (AFR)	0.0044
Endurance	3, 1 (Drive writes per day)
Data Durability	3-month at 40 degreesC
Power	
Requirement	3.3V (aux) & 12V (DC +/- 5%)
Operating (W, typical)	25
Idle (W)	9
Physical Size	
Z-Height (mm)	15
Dimensions (width x depth, mm)	100.45 x 69.85
Weight, Without Bracket (g)	184 / NA
Environmental (operating)	
Ambient Temperature	N/A
Case Temperature	0 degreesC to 70 degreesC
Environmental	
Airflow (LFM)	N/A

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/HUSMR7632BDP301-HGST-Ultrastar-SN200-3200GB-2-5-NVMe-Solid-State-Drive-p-204696.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

ComX Computers

Product Specification Sheet

PDF generated: 2026-11-22 04:30:21.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.