ComX Computers
Product Specification Sheet

KA02014-B511

Fujitsu DL3850+ 24 pin 136 columns Serial Dot Matrix Printer, USB, Centronics

Product Overview

Fujitsu DL3850+ 24 pin 136 columns Serial Dot Matrix Printer, USB, Centronics, 113 characters per second printing speed (10 CPI), 60 ms per 1/6" line feed speed, 5.6 inches per second form feed speed, 360x360 dots per inch Resolution, 5 copies including original, 136 columns print line (10cpi)



Specifications

Overview:

Fujitsu DL3850+ Serial Dot Matrix Printer, USB, Centronics (KA02014-B511)

Fujitsu DL3850+ High performance Serial Dot Matrix Printer, USB, Centronics (KA02014-B511)

24-Pin Dot Matrix Printer

High Quality. Silent Printing. Low Profile.

- Compact, low profile 136 column design
- Ultra-low noise emissions - 49dBA
- 24-pin printhead for high-quality output
- Multiple Interface Options

Compatible Ribbons :

Fujitsu Serial Dot Matrix Ribbon Cartridge (DL3750+, DL3850+, DL7400,DL7400Pro), BLACK, Keying Ribbon, KA02086-C802

Specifications:

© 2024 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	KA02014-B511
Print Technology	Dot Matrix
Printing speed (letter, 10 cpi)	113 characters per second
Printing speed (letter, 12 cpi)	135 characters per second

Printing speed (draft, 10 cpi)	360 characters per second
Printing speed (draft, 12 cpi)	432 characters per second
Printing speed (high draft, 10 cpi)	448 characters per second
Printing speed (high draft, 12 cpi)	537 characters per second
Line feed speed	60 ms per 1/6" line
Form feed speed	5.6 inches per second
Resolution	360 x 360 dots per inch
Number of copies	5 including original
Emulation (standard)	Fujitsu DPL24C PLUS, Epson ESC/P 2, IBM
	Proprinter XL24E
Barcode	Code 3 of 9, UPC Type A, UPC Type A with check character, Codabar(NW7), EAN13, EAN8, Industrial 2 of 5, Matrix 2 of 5,Interleaved 2 of 5, Code 128, POSTNET, UPC-E
Interface (standard)	Parallel (IEEE1284 Nibble Mode), Serial
	(RS232C, 25Pin)
	USB Ver.2.0 (TYPE B)
Print line (10cpi)	136 columns
Input Buffer	Max:128KB
Physical Specifications	
Width	600 mm (23.62 inch)
Depth	350 mm (13.78 inch)
Height	290 mm (11.42 inch)
Weight	Approx: 17 kg
Acoustic noise	49 dB
Reliability Specifications	
Head life	400 million strokes (each wire)
Ribbon life	7.5 million characters (Life is a readable number of characters. It varies depending on the customer's usage environment.)
Mean Time Between Failures (MTBF)	20,000 hrs @ 25% duty cycle

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/KA02014-B511-Fujitsu-DL3850-24-pin-136-columns-Serial-Dot-Matrix-Printer-USB-Centronics-p-295551.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

ComX Computers

Product Specification Sheet

PDF generated: 2026-11-21 03:17:52.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.