ComX Computers
Product Specification Sheet

KIN-1000APRM

PCM King Pro Rackmount 1000va Line-Interactive UPS

Product Overview

PCM King Pro Rackmount 1000va Line-Interactive, RS232 Port, Cable, UPSMon Plus, 1x RJ11, RJ45, Surge Protector, 4x Outputs.



Specifications

Description:

Most enterprises have resorted to the Internet to take care of business; however, once the Internet got disconnected due to problems of power, the enterprises may suffer enormous lose and damage. While corporations are much more dependent upon the Internet, the reliability of network cannot be guaranteed from failure-proof. Viewing this, the world-leading PCM launches the series of King Pro to deliver mighty output power. King Pro is endowed with strong accommodation to net, and it will not contaminate net; in addition, King Pro is efficient at dealing with various complexity of loading so that it can ensure that the large-sized network and critical conducting appliances are operating with constancy, security, and stability.

Specifications:

© 2013 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Product Code	KIN-1000APRM
Specifications	
Model Type	KING RM
Model Name	KIN-1000APRM
AC INPUT	
AC Input Capacity on Battery	1000VA
AC Input Voltage	(+/-) 25% at line input
AC Input Frequency	50 or 60 Hz+/-10% (auto sensing)
AC OUTPUT	

AC Output Voltage	Simulated sine ware at 100V or 110V/115V/120V or 220V/230V/240V +/-5%
AC Output Frequency	50 or 60 Hz +/- 0.5%
AC Output Voltage Regulation	AVR automatically increase output voltage 15% above input voltage if -9% to -25% of nominal. AVR decrease output voltage 13% below input voltage if +9% to +25% of nominal
AC Output Transfer	2/4 milliseconds, including detection time
PROTECTION	
Protection Spike	320 Joules, 2ms
Protection EMI/RFI	10dB at 0.15 MHz, 50 dB at 30 MHz
Protection Overload	UPS automatic shutdown if overload exceeds 110% nominal at 60 sec and 130% at 3 sec
Protection Unit	Fuse for overload & short circuit protection
Protection 10 BaseT	Network (UTP, RJ-45) compatible jacks
Protection Short Protection	UPS output cut off immediately or input fuse protection
BATTERY	
Battery Type	Sealed, Maintenance-free lead acid
Battery Typical	8 hours (to 90% of full capacity)
Battery Protection	Automatic self-test & discharge protection, replace battery indicator
BACKUP TIME	
Battery Backup Time Full Load	7 minutes
Battery Backup Time Half Load	15 minutes
PHYSICAL	
Physical Weight kgs RM	10.5
Physical Weight lbs RM	23.1
Physical Shipping Weight kgs	11.7
Physical Shipping Weight lbs	25.7
Physical Dimension mm RM	483x362x44 (1U)
Physical Dimension inch RM	19x14.2x1.7
INDICATOR	
LED	LED
ALARM	
Alarm Battery Backup	Slow beeping sound (about 0.47 Hz)
Alarm Battery Low	Rapid beeping sound (about 1.82Hz)
Alarm Overload	Continue beeping sound
INTERFACE	
Interface RS-232	RS-232C Bi-directional communication port
ENVIRONMENT	
Environment Ambient	3, 500 meters max. elevation, 0-95% humidity non-condensing, 0-40 deg c

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/KIN-1000APRM-PCM-King-Pro-Rackmount-1000va-Line-Interactive-UPS-p-75236.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-11 10:31:56.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.