ComX Computers
Product Specification Sheet

LC-APB328Q

Asus PB328Q 32" Wide LED Display

Product Overview

Asus PB328Q 32" Wide LED Display with 1073.7million display colours + QuickFit Virtual Scale, intuitive 5-way Navigation Key as joystick, 2x 3w speaker, 4-way adjustable (tilt+swivel+pivot+height) stand, 2560x1440 (16:9 WQHD), 12-bit colour look-up table + 100% sRGB + Rec. 709 colour space support, 6-axis colour adjustment; brightness - 300cd/m2; contrast ratio - 1000:1 / 100000000:1, response time- 4ms - Dvi+ Display Port+ HDMi - 100x100mm vesa wall-mountable



Specifications

Features:

True to Life Picture Detail & Colors
PB328Q offers a wide color gamut of 100% sRGB to deliver impresive and lifelike picture quality.

10-bit color for smoother gradations
The PB328Q offers 10-bit display color for over one billion onscreen colors and support 12 bit internal lookup table (LUT), which gives smoother gradations and a more natural transition between hues.

Wide Viewing angle
178 degrees wide-viewing-angle to minimize the color shift and promise for a better viewing experience also features 100,000,000 ASUS Smart Contrast Ratio for enhanced image contrast.

See Better and Wider
The PB328Q WQHD monitor equaling four times the resolution of stand 720p sets. It allows users to view greater image detail and do more with an onscreen footprint larger than that of standard displays.

Made for Work and Play
With its WQHD display, you enjoy 77% more desktop space than a full HD screen to spread out your windows and palettes.

6-axis independent color adjustment
Customized hue and saturation control with 6 color adjustment allows you to adjust six colors (red, green, blue, cyan, magenta and yellow) independently without effecting other colors.

Hassle-free setting
The user-friendly and exclusive intuitive 5-way navigation joystick allows users to do the OSD setting with simple mind - go

right, left, up, or down on your OSD menu setting has never been so easy. PB328Q also features customizable OSD shortcuts through two designated hotkeys for quick address to the 8 most frequently used OSD function.

Picture-in-Picture and Picture-by-Picture
ASUS exclusive innovations Picture-in-Picture (PIP) and Picture-by-Picture (PBP) allows users to view images from different signals in almost anyway they want. PIP and PBP let users view images from different signals and let them switch between the main and PIP source, including audio, easily.

QuickFit Virtual Scale Function
ASUS included its exclusive QuickFit Virtual Scale Function with the PB328Q , allowing users to preview photos and documents on screen in their actual sizes prior to printing. It can activated via a hotkey on monitor and used as a guide to accurately view and edit photos. Additionally, the PB328Q also comes with a choice of seven different background colors for users to choose from.

Ergonomic Design
As with most ASUS displays, the PB328Q is VESA-wall mount compliant and comes with a versatile stand with full tilt, swivel, pivot, and height adjustment. A user-friendly Quick Release Stand for hassle-free setting.

Ultra-low Blue Light Monitor
The TÜV Rheinland-certified ASUS Blue Light Filter protects you from harmful blue light, and you can easily access its four different filter settings via a hotkey. PB328Q has undergone stringent performance tests and has been certified by TÜV Rheinland laboratories, a global provider of technical, safety, and certification services, to be flicker-free and to emit low blue light levels.

Flicker-free Technology
It's time to say goodbye to those tired, strained eyes. PB328Q features TÜV Rheinland-certified ASUS Flicker-Free technology to reduce flicker for a comfortable viewing experience. This technology helps minimize instances of eyestrain and other damaging ailments, especially when you spend long, countless hours in front of a display watching favorite videos.

Specifications:

© 2016 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	LC-APB328Q

Display	Panel Size: Wide Screen 32" (81.28cm) 16:9
	Panel Backlight / Type : VA
	True Resolution : 2560x1440
	Display Viewing Area(HxV) : 708.48 x 398.52 mm
	Display Surface Non-glare
	Pixel Pitch : 0.277mm
	Brightness(Max) : 300 cd/
	ASUS Smart Contrast Ratio (ASCR) : 100000000:1
	Viewing Angle (CR 10) : 178 degrees(H)/178 degrees(V)
	Response Time : 4ms (Gray to Gray)
	Display Colors : 1073.7M (10bit)
	Flicker free
	Look-up Table :12-bit
Video Feature	Gamma adjustment : Yes (Support Gamma 1.8/2.0/2.2/2.4)
	Low Blue Light : Yes
	VividPixel : Yes
Audio Features	Stereo Speakers : 3W x 2 Stereo RMS
Convenient Hotkey	Blue Light Filter
	Brightness Adjustment
	Input Selection
	QuickFit
	5-way OSD Navigation Joystick
I/O Ports	Signal Input : HDMI, D-Sub, DisplayPort, Dual-link DVI-D
	USB Port(s) : 3.0x4
Signal Frequency	Analog Signal Frequency : 30~83 KHz(H) / 49~76 Hz(V)
	Digital Signal Frequency : Display port 29~130 KHz(H) / 49~76 Hz(V)
Power Consumption	Power On: < 32.36 W
	Power Saving Mode:
	Power Off Mode: 0W
	Voltage: 100-240V, 50/60 Hz

Mechanical Design	Chassis Colors : Black
	Tilt : +25 degrees~-5 degrees
	Swivel : +60 degrees~-60 degrees
	Pivot : 0 degrees~+90 degrees
	Height Adjustment : 0~150 mm
	VESA Wall Mounting : 100x100mm
	Super Narrow Bezel Design : Yes
	Quick Release Stand Design : Yes
Security	Kensington lock
Dimensions	Phys. Dimension with Stand(WxHxD):735x625x242mm
	Phys. Dimension without Stand(WxHxD):734.4x431x66.85mm (for VESA Wall Mount)
	Box Dimension(WxHxD):847x552x350mm
Weight	Net Weight (Esti.): 11.8Kg
	Gross Weight (Esti.): 16.5Kg
Accessories	Dual-link DVI cable
	VGA cable
	Audio cable
	Power cord
	DisplayPort cable
	USB 3.0 cable
	HDMI cable
Compliance and Standards	Energy Star, BSMI, CB, CCC, CE, CU, ErP, FCC, ISO-9241-307, J-MOSS, KCC, PSE, RoHS, TCO6.0, UkrSEPRO, UL/cUL, VCCI, WEEE, WHQL (Windows 8, Windows 7), RCM, KC, eStandby

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: https://www.comx-computers.co.za/LC-APB328Q-Asus-PB328Q-32-Wide-LED-Display-p-151023.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-11 17:28:46.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.