ComX Computers
Product Specification Sheet

LOCO-M2

Ubiquiti A/M NanoStation Loco M2 - 2.4GHz Mini Outdoor CPE

Product Overview

Ubiquiti LOCO-M2 A/M NanoStation Loco M2 - 2.4GHz Mini Outdoor CPE, including PoE, 150+ Mbps Throughput, 5+ km range, 1x 10/100 Ethernet LAN







Specifications

Overview:

Indoor/Outdoor airMAX CPE

Featuring a panel antenna and dual-polarity performance, the NanoStation M is ideal for Point-to-MultiPoint (PtMP) applications requiring high-performance CPE devices with a sleek form factor.

Models: locoM2, locoM5, locoM9, NSM2, NSM3, NSM365, NSM5

Features:

Compact CPE Design

The NanoStation M features the CPE design that expanded the global Wireless ISP industry.

Plug and Play Installation

The NanoStation M requires no tools for assembly; only a single wrench is required for pole-mounting.

Versatile Application Use

The NanoStation M can be deployed for Point-to-Point (PtP) bridging, wireless connectivity to a video surveillance system, or use as an airMAX CPE.

Dual Ethernet Connectivity

With software-enabled PoE output, the secondary Ethernet port can power an external device, such as a PoE security camera, for seamless IP video integration.

Powerful airOS

Ubiquiti's versatile airOS firmware technology enables high-performance, outdoor multi-point networking. airOS provides features such as wireless settings, bridge or routing configuration and system management services.

Advanced Software Technology

Ubiquiti's airMAX technology is proven in millions of deployments worldwide, exhibiting outstanding performance in outdoor environments. The TDMA airMAX protocol enables unprecedented scalability, high throughput and low latency in unlicensed, multipoint networks.

Window/Wall Mounting Kit

Use the NanoStation Mount to quickly mount the NanoStationM on a window or wall. 180 degrees vertical or horizontal adjustment allows for custom positioning.

Wall/Pole Mounting Kit

The Universal Arm Bracket is designed for convenient wall or pole mounting of the NanoStation M. 90 degrees tilt adjustment allows for easy positioning.

Specifications:

© 2024 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	LOCO-M2
Frequency	2.4 GHz
Throughput	150+ Mbps
Range	5+ km

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/LOCO-M2-Ubiquiti-A-M-NanoStation-Loco-M2-2-4GHz-Mini-Outdoor-CPE-p-311167.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-15 18:39:47.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.