

LP-C6200D

Canon Lbp-6200D mono laser printer

Product Overview

Canon Lbp-6200D mono laser printer with auto-duplex unit; a4, 600 / 2400x600dpi; 25ppm, 250s input tray, 100sheets output tray, duty: 8000pages per month - USB 2.0



Specifications

Overview:

With automatic double-sided printing, this compact laser printer is a great addition to the home or small office. Benefit from maintenance free prints and a host of energy and time-saving features.

Features:

- Space-saving design
- 25 ppm, 6 seconds First Print Out Time
- Automatic double-sided printing
- Energy efficient
- Quiet operation
- All-in-One cartridge for maintenance free operation

Specifications:

PRINTER ENGINE	
Print Speed	25 ppm mono (A4)
Printing Method	Monochrome laser beam printing
Print Quality	Up to 2400 x 600 dpi with Automatic Image Refinement
Print Resolution	Up to 600 x 600 dpi
Warm-up Time	Approx 0.5 seconds from Sleep
	Approx. 10 seconds or less from power on
First Page Out Time	Approx. 6 seconds or less
Duty Cycle	Max 8, 000 pages per month

ComX Computers

Product Specification Sheet

Print Margins	5 mm-top, bottom, left and right
MEDIA HANDLING	
Paper Input (Standard)	250-sheet multi-purpose tray
	1-sheet manual feed slot
Paper Output	100-sheet face down
Media Types	Plain paper, Heavy Paper, Transparency
	Label, Index card, Envelope
Media Sizes	Multi-purpose tray:
	A4/B5/A5/LGL/LTR/EXE/16K/Custom sizes
	COM10/Monarch/C5/DL/ISO-B5
	width76.2 x 215.9mm x length 187 x 355.6mm
	Manual feed slot:
	A4/B5/A5/LGL/LTR/EXE/16K/Custom sizes
	COM10/Monarch/C5/DL/ISO-B5/Index card
	width76.2 x 215.9mm x length 127 x 355.6mm
Media Weights	Multi-purpose tray:
	60 to 163 g/m ²
	Manual feed slot:
	60 to 163 g/m ²
GENERAL FEATURES	
Power Requirements	AC 220-240V (+/-10%), 50/60Hz (+/-2Hz)
Power Consumption	Maximum: Approx 1200W or less
	Active: Average approx 280W or less
	Standby: Average approx. 1.6W
	Sleep: Average approx 1.4W
	Typical Electricity Consumption (TEC): 0.7 kWh/week
Noise Level	Sound power ¹ :
	Active: 6.77 B or less
	Standby: Inaudible
	Sound pressure ¹ :
	Active: 53 dB(A)
	Standby: Inaudible
Dimensions (W x D x H)	379mm x 293mm x 243mm
Weight	Approx. 7 kg
Operating Environment	temperature:10~30degreesC
	Humidity:20~80%RH(no condensation)
Control Panel	1 LED indicator, 1 operation key

ComX Computers

Product Specification Sheet

CONTROLLER	
Printer Languages	Canon Advanced Printing Technology (CAPT)
Interface and Connectivity	USB 2.0 Hi-Speed
Operating Systems Compatibility	Win 7(32/64bit)/Win Vista(32/64bit)/XP(32/64bit)
	Server 2008(32/64bit) / Server 2008 R2(64bit)/ Server 2003 (32/64bit)/ 2000/
	Mac OS10.4.9 - 10.6.x ¹ /Linux

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx-computers.co.za/LP-C6200D-Canon-Lbp-6200D-mono-laser-printer-p-41707.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-28 14:03:52.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.