

LP-LE360D

Lexmark E360D printer

Product Overview

Lexmark E360D printer, built-in auto duplex unit, grey; 400 MHz processor, 32mb upto 288, 600/2400dpi; 38ppm, 250+50 sheet input tray upto 850, 150sheets output, duty: 80000 pages per month - USB + parallel



Specifications

Overview:

The Lexmark E360d monochrome laser with paper-saving built-in duplex printing is small in size, big in performance with rapid speeds up to 38 ppm and a 50-sheet multipurpose feeder for special media. Its intuitive 2-line display makes operation easy. For added value, you can choose between the standard yield (3.5K) or high yield toner cartridge (9K).

Features:

- Up to 38 ppm print speeds
- 50-sheet multipurpose feeder
- Intuitive 2-line LCD display
- 3.5K and 9K Lexmark Toner Cartridges available
- Recommended average volume: 740 to 6,000 pages

Specifications:

UNSPSC Code	43212105
Print Speed (A4, Black): Up to	38 ppm
Print Speed (A4, Black) Duplex: Up to	18 spm
Print Speed (Letter, Black): Up to	40 ppm
Print Speed (Letter, Black) Duplex: Up to	18 spm
Time to First Page (Black) As fast as	6.5 seconds

ComX Computers

Product Specification Sheet

Print Resolution, Black	1200 Image Quality
	1200 x 1200 dpi
	2400 Image Quality
	600 x 600 dpi
Processor	400 MHz
Memory, Standard	32 MB
Memory, Maximum	288 MB
Expandable Memory Options	Yes
Apple Macintosh Operating Systems Supported	Apple Mac OS X (10.2 or later)
	Apple Mac OS 9.2
Citrix MetaFrame	Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 3.0, 4.0
	Microsoft Windows Server 2003 running Terminal Services with Citrix Presentation Server 3.0, 4.0, 4.5
	Microsoft Windows Server 2003 x64 running Terminal Services with Citrix Presentation Server 4.0 x64, 4.5 x64
Linux Operating Systems Supported	Linpus Linux Desktop 9.2, 9.3
	Red Hat Enterprise Linux WS 3.0, 4.0, 5.0
	SUSE Linux Enterprise Server 8.0, 9.0, 10, 11
	SUSE Linux Enterprise Desktop 10
	openSUSE 10.2, 10.3, 11.0, 11.1
	Linspire Linux 6.0
	Debian GNU/Linux 4.0
	Red Flag Linux Desktop 5.0, 6.0
	Ubuntu 7.10
	Ubuntu 8.04 LTS
	SUSE Linux Enterprise Desktop 11
	Debian GNU/Linux 5.0
	Ubuntu 8.10, 9.04

ComX Computers

Product Specification Sheet

Microsoft Windows Operating Systems Supported	Microsoft Windows 2000
	Microsoft Windows XP
	Microsoft Windows Server 2003
	Microsoft Windows XP x64
	Microsoft Windows Server 2003 running Terminal Services
	Microsoft Windows 2000 Server running Terminal Services
	Microsoft Windows Server 2003 x64
	Microsoft Windows Server 2003 x64 running Terminal Services
	Microsoft Windows Vista
	Microsoft Windows Vista x64
	Microsoft Windows Server 2008
	Microsoft Windows Server 2008 x64
	Microsoft Windows Server 2008 running Terminal Services
	Microsoft Windows Server 2008 x64 running Terminal Services
	Microsoft Windows 7
Paper Handling Standard	150-Sheet Output Bin
	Integrated Duplex
	Single Sheet Exit
	250-Sheet Input Tray
	50-Sheet Multipurpose Feeder
Paper Handling Optional	550-Sheet Drawer
	Only one drawer may be installed at a time
	250-Sheet Drawer
Paper Input Capacity, Standard: Up to	300 pages 75 gsm bond
Paper Input Capacity, Maximum: Up to	850 pages 75 gsm bond
Paper Output Capacity, Standard: Up to	150 pages 75 gsm bond
Paper Output Capacity, Maximum: Up to	150 pages 75 gsm bond
Envelope Capacity	7
Finishing Option	No
Number of Paper Inputs, Standard	2
Number of Paper Inputs, Maximum	3

ComX Computers

Product Specification Sheet

Media Types Supported	Card Stock
	Envelopes
	Paper Labels
	Plain Paper
	Transparencies
	Refer to the Card Stock & Label Guide
Media Sizes Supported	10 Envelope
	7 3/4 Envelope
	9 Envelope
	A4
	A5
	B5 Envelope
	C5 Envelope
	DL Envelope
	A6 Card
	Executive
	Folio
	JIS-B5
	Legal
	Letter
	Statement
	Universal
	Oficio
Supplies Yield	*Average standard page yield value declared in accordance with ISO/IEC 19752.
	9, 000*-page High Yield Toner Cartridge
	3, 500*-page Toner Cartridge
Standard Ports	Centronics IEEE 1284 Bidirectional Parallel
	USB 2.0 Specification Hi-Speed Certified (Type B)
Optional Network Ports	Lexmark N4000e Fast Ethernet (Print Only)
	Lexmark N4050e 802.11g Wireless Print Server (Print Only)
	External MarkNet N7020e Gigabit Ethernet
	External MarkNet N7000e Fast Ethernet (USB)
	External MarkNet N7002e Fast Ethernet (parallel)

ComX Computers

Product Specification Sheet

Fonts and Symbol Sets	3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide
	2 PCL bitmap fonts
	39 scalable PPDS fonts
	5 PPDS bitmap fonts
	84 scalable PCL fonts
	89 scalable PostScript fonts
	OCR-A, OCR-B scalable PCL 5e fonts
	For more information, refer to the Technical Reference.
Printer Languages (Standard)	PCL 5e Emulation
	PCL 6 Emulation
	PPDS
	PostScript 3 Emulation
Packaged Size (mm - H x W x D)	355 x 460 x 420 mm
Size (mm - H x W x D)	260 x 406 x 370 mm
Weight (kg)	13.83 kg
Noise Level, Idle	inaudible dBA
Print Noise Level, Operating	53 dBA

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: <https://www.comx-computers.co.za/LP-LE360D-Lexmark-E360D-printer-p-37901.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-28 14:03:38.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.