ComX Computers
Product Specification Sheet

MICRO2000

GiCom 2000VA Line Interactive UPS

Product Overview

GiCom 2000VA Line Interactive UPS, Typical 2-6ms transfer Time, Simulated Sine Wave, 2x 12V 9Ah Battery



Specifications

Overview:

GICOM 2000VA series is a line-interactive UPS that is integrated with AC voltage stabilizer, standby power, and surge voltage suppression, meanwhile with compact size, full function, high efficiency, high reliability, ease to be used. It can supply comprehensive power protection for terminal equipment, PC, station, SOHO equipment.

- AVR Boost and buck
- Cold start function
- Smart RS-232/USB interface for power management
- Built-in self-diagnostic function
- Modem/LAN internet protection
- Fast charging
- Auto charging at off mode
- Auto-restart function

Specifications:

© 2022 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	MICRO2000
Input	
Voltage	110/120 VAC or 220/230/240 VAC
Voltage Range	81-145 VAC or 162-290 VAC
Frequency Range	60 or 50 Hz (auto sensing)

Output	
AC Voltage Regulation (Batt. Mode)	+-10%
Frequency Range (Batt. Mode)	60 Hz or 50 Hz +- 1Hz
Transfer Time	Typical 2-6 ms
Waveform (Batt. Mode)	Simulated Sine Wave
Battery	
Battery Type and Number	12V / 9AH x2
Typical Recharge Time	6-8 hours recover to 90% capacity
Indicators	
AC Mode	Green LED lighting
Battery Mode	Amber LED flashing
Fault	Red LED lighting
Protection	
Full Protection	Overload and overcharge protection
Alarm	
Battery Mode	Sounding every 10 seconds
Low Battery	Sounding every second
Overload	Sounding every 0.5 second
Battery Replacement Alarm	Sounding every 2 seconds
Fault	Continuously sounding
Operating Environment	
Humidity	0-90 % RH @ 0-40 degrees C
Noise Level	Less than 40dB
Management	
Optional USB/RS-232 Port	Supports Windows 2000/2003/XP/Vista/2008, Windows 7, Linux, UNIX and MAC

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page: https://www.comx-computers.co.za/MICRO2000-GiCom-2000VA-Line-Interactive-UPS-p-274318.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-10 08:27:15.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing

decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.