

N3D

Netis Systems N3D AC1200 Wireless Dual Band FE Router

Product Overview

Netis Systems N3D AC1200 Wireless Dual Band fe Router, 4x 5dBi high gain antennas, Up to 300 Mbps @ 2.4GHz, Up to 867 Mbps @ 5GHz, Wireless modes - Access Point / Repeater / Client Wireless modes



Specifications

Overview:

N3D

The NETIS router N3D equipped with 802.11AC Wi-Fi technology, will offer you simultaneous dual band connection with 867Mbps wireless speeds over the crystal clear 5GHz band and 300Mbps over the 2.4GHz band, ideal for faster downloading, online gaming, Internet calling and HD video streaming.

Specifications:

© 2021 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.	
Specifications	
Product Code	N3D
Wireless	
Standards	IEEE 802.11b/g/n 2.4GHz
	IEEE 802.11a/n/ac 5GHz
Signal Rate	Up to 300Mbps2.4GHz
	UP to 867Mbps 5GHz
Frequency Range	2.4-2.4835GHz, 5.180-5.825GHZ
Transmit Power	20dBm(MAX)

ComX Computers

Product Specification Sheet

Data Transfer Rate	802.11ac:80MHZ(433Mbps, 867Mbps)
	802.11n: 40MHz(300Mbps, 270Mbps, 240Mbps, 180Mbps, 120Mbps, 90Mbps, 60Mbps, 30Mbps)
	20MHz (144Mbps, 130Mbps, 115Mbps, 86Mbps, 57Mbps, 43Mbps, 28Mbps, 14Mbps) (Auto-Sense)
	802.11g:(54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps)
	802.11b:(11Mbps, 9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps)
Wireless Modes	AP, Repeater, Client, Multi-SSID
Wireless Security	WEP/WPA-PSK/WPA2-PSK Encryption
	Wireless MAC Filtering
Hardware	
Standards	IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T
Interface	1*10/100/100Mbps Auto MDI/MDIX RJ45 WAN port
	3*10/100/100Mbps Auto MDI/MDIX RJ45 LAN port
LED Indicators	PER, Internet
Buttons	Reset
Antenna	4* external fixed 5dBi antenna
Power Supply	DC 12V/1.0A(Output)
Dimensions (L x W x H)	182mm x 108mm x 25mm
Software	
WAN Type	DHCP, Static IP, PPPoE, L2TP, PPTP, WISP
Others	Bandwidth Control, Access Control, IPTV, Virtual Server, DMZ
	VPN Pass-through, Dynamic DNS, Static Routing, Backup & Restore
Certification	FCC, CE, EAC
Environment	Operating Temperature: 0 degreesC~40 degreesC
	Storage Temperature: -40 degreesC~70 degreesC
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing
Package	1* N3D
	1* 12V/1.0A Power Adapter
	1* Quick Installation Guide (Multilingual)

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/N3D-Netis-Systems-N3D-AC1200-Wireless-Dual-Band-FE-Buy-p-262139.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-17 15:08:04.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.