

NET-TL-POE2412G

TP-Link TL-POE2412G PoE Adapter

Product Overview

TP-Link TL-POE2412G PoE Adapter



Specifications

Features:

- 24V passive PoE supported
- Auto-determine the necessary power requirements
- Convenient wall-mounting design
- Gigabit speed support
- Plug-and-Play, requires no configuration

Power Your Devices

Use the passive PoE adapter TL-POE2412G to simultaneously supply power and transmit data to a passive PoE device.

Convenient Wall-Mounting Design

TL-POE2412G offers a convenient wall-mounting brackets to be easily installed on a wall.

Compatible Devices

TL-POE2412G is recommended to offer power supply to TP-Link's passive PoE products which as follows.

Specifications:

© 2020 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (<http://www.comx.co.za>), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications

Product Code	NET-TL-POE2412G
--------------	-----------------

HARDWARE FEATURES

ComX Computers

Product Specification Sheet

Interface	2 10/100/1000Mbps RJ45 Port
	AUTO Negotiation/AUTO MDI/MDIX
	1 24VDC POWER INPUT PORT
Network Media	10BASE-T: UTP category 3, 4, 5 cable (Max 100m)
	EIA/TIA-568 100ohm STP (Max 100m)
	100BASE-TX: UTP category 5, 5e cable (Max 100m)
	EIA/TIA-568 100ohm STP (Max 100m)
	1000BASE-T: UTP category 5, 5e, 6 cable (Max 100m)
Power Supply	12W (Max. 24VDC)
LED Indicator	PWR
Dimensions (W x D x H)	3.4*1.7*1.4 in.(85.8mm*43.9mm*35mm)
OTHERS	
Certification	FCC, CE, RoHS
Package Contents	24V 12W Passive PoE Adapter TL-POE2412G
	Power Cord
	Wall Mounting Kits
Environment	Operating Temperature: 0 degreesC~40 degreesC (32 degreesF~104 degreesF)
	Storage Temperature: -40 degreesC~70 degreesC (-40 degreesF~158 degreesF)
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:

<https://www.comx-computers.co.za/NET-TL-POE2412G-TP-Link-TL-POE2412G-PoE-Adapter-Buy-p-242641.php>

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: <https://www.comx-computers.co.za/terms-of-use.php>

Terms of Sale: <https://www.comx-computers.co.za/terms-of-sale.php>

PDF generated: 2026-10-05 07:14:49.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.