
ComX Computers
Product Specification Sheet

NET-TL-SF1005P

TP-Link TL-SF1005P 5-Port 10/100Mbps Desktop Switch with 4-Port PoE

Product Overview

TP-Link TL-SF1005P 5-Port 10/100Mbps Desktop Switch with 4-Port PoE



Specifications

Overview:

TL-SF1005P is a 5 10/100Mbps ports unmanaged switch that requires no configuration and provides 4 PoE (Power over Ethernet) ports. It can automatically detect and supply power with all IEEE 802.3af compliant Powered Devices (PDs). In this situation, the electrical power is transmitted along with data in one single cable allowing you to expand your network to where there are no power lines or outlets, where you wish to fix devices such as APs, IP Cameras or IP Phones, etc.

Features:

- 5 10/100Mbps RJ45 ports
- With four PoE ports, transfers data and power on one single cable
- Working with IEEE 802.3af compliant PDs, expands home and office network
- Supports PoE Power up to 15.4W for each PoE port
- Supports PoE Power up to 58W for all PoE ports
- Requires no configuration and installation

Power over Ethernet
4 of the 5 Auto-Negotiation RJ45 ports (Port 1 to Port 4) of the switch support Power over Ethernet (PoE) function. These PoE ports can automatically detect and supply power with those IEEE 802.3af compliant Powered Devices (PDs).

Overload Arrangement
TL-SF1005P has the priority function which will help protect the system when the system power is overloaded. If all PoE PDs power consumption is >= 58W, a priority will be arranged among the PoE ports, then the system will cut off the power of the lowest-priority port.

Port Priority Function
Priority (port-1=port-2=port-3>port-4): This function will help to ensure the normal operation of the system, it means Port 4 will be cut off when all total PoE PDs power consumption exceed 58W. For an example, Port 1, 2 and 4 is using 15.4W (maximum power for per port is 15.4W); the system power is 46.2W in total. If there is an additional PD inserted to Port 3 with 12W, and

then the system will cut off the power of Port 4 because of the overloaded power, this means Port 1, 2 will use 15.4W, and Port3 will use 12W, no power will be supplied to Port 4.

Easy To Use

TL-SF1005P is easy to install and use. It requires no configuration and installation. With desktop design, outstanding performance and quality, the TP-Link's TL-SF1005P 5-Port 10/100Mbps Desktop Switch with 4-Port PoE is an ideal choice for expanding your home or office network.

Specifications:

© 2018 Respective owners and brand holders. This table has been carefully researched and generated by ComXpert International CC (http://www.comx.co.za), however, errors and omissions may occur. Only references to South Africa apply. All products are sourced in South Africa from the official suppliers and the warranty is that of the local supplier. E&OE. This table and our site's content may be used on condition that this notice and link remains intact and unaltered.

Specifications	
Product Code	NET-TL-SF1005P
HARDWARE FEATURES	
Interface	5 10/100Mbps RJ45 Ports
	AUTO Negotiation/AUTO MDI/MDIX
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)
	EIA/TIA-568 100ohm STP (maximum 100m)
	100BASE-TX: UTP category 5, 5e cable (maximum 100m)
	EIA/TIA-568 100ohm STP (maximum 100m)
Fan Quantity	Fanless
External Power Supply	External Power Adapter(Output: 48VDC / 1.25A)
PoE Ports (RJ45)	Standard: 802.3 af compliant
	PoE Ports: Port1- Port4
	Power Supply: 58W
Mac Address Table	2K
Switching Capacity	1Gbps
Dimensions (W x D x H)	3.9 x 3.9 x 1.0 in. (99.8 x 98 x 25 mm)
Transmission Distance	Store-And-Forward
Max Power Consumption	1.678W (max. no PD connected)
	64.82W (max. with 58w PD connected)
Max Heat Dissipation	5.73BTU/h(no PD connected)
	221.17BTU/h(with 58W PD connected)
SOFTWARE FEATURES	
Transmission Method	Store-And-Forward

Advanced Functions	Compatible With IEEE 802.3af Compliant PDs
	Priority Function
	Mac Address Auto-Learning And Auto-Aging
	IEEE802.3x Flow Control For Full-Duplex Mode And Backpressure For Half-Duplex Mode
OTHERS	
Certification	FCC, CE, RoHS
Package Contents	TL-SF1005P, Power Adapter, User Guide
Environment	Operating Temperature: 0 degreesC~40 degreesC (32 degreesF~104 degreesF)
	Storage Temperature: -40 degreesC~70 degreesC (-40 degreesF~158 degreesF)
	Operating Humidity: 10%~90%RH non-condensing
	Storage Humidity: 5%~90%RH non-condensing

Product Information Online

For the latest product information, availability and purchasing details, please visit the product page:

Product page:
https://www.comx-computers.co.za/NET-TL-SF1005P-TP-Link-TL-SF1005P-5-Port-10-100Mbps-Desktop-Switch-with-4-Port-PoE-p-211179.php

Images and specifications are provided for reference and are subject to change without notice. E&OE.

Terms of Use: https://www.comx-computers.co.za/terms-of-use.php
Terms of Sale: https://www.comx-computers.co.za/terms-of-sale.php

PDF generated: 2026-11-13 06:14:40.

This PDF was generated automatically and may include content prepared or assisted by automated or AI-based systems. While reasonable care is taken to ensure accuracy, errors or omissions may occur.

For the most current and accurate product information, please refer to the product information available on our website. If any specification or other information differs from information published elsewhere, please confirm the details with us before relying on the information or making a purchasing decision.

If you identify an error or discrepancy, please report it to us so that we may investigate and correct it where necessary.